

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 8

SDS No.: 425396

V002.1

Revision: 30.05.2015

printing date: 06.11.2015

Replaces version from: 14.03.2014

Category 2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

UniBond Stop Humidity Power Tab 300g

UniBond Stop Humidity Power Tab 300g

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Air dryer

### 1.3. Details of the supplier of the safety data sheet

Henkel Technologies France SAS

Rue de Silly 161

92100 Boulogne-Billancourt

France

Phone: +33 (0033) 1 4684 9000 Fax-no.: +33 (0033) 1 4684 9090

ua-productsafety.uk@uk.henkel.com

## 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification (CLP):

Serious eye irritation

Corrosive to metals Category 1 H290 May be corrosive to metals

H319 Causes serious eye irritation.

#### 2.2. Label elements

# Label elements (CLP):



Signal word:

MSDS-No.: 425396

V002.1

Hazard statement:	H290 May be corrosive to metals. H319 Causes serious eye irritation.
Precautionary statement:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P280 Wear face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

#### 2.3. Other hazards

None if used properly.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## **General chemical description:**

Dehumidifying agent

# Base substances of preparation:

Calcium chloride

## Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Calcium chloride	233-140-8	>= 65 %	Met. Corr. 1
10043-52-4	01-2119494219-28		H290
			Eye Irrit. 2
			H319

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### General information:

In case of adverse health effects seek medical advice.

### Inhalation:

Move to fresh air, consult doctor if complaint persists.

### Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

### Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remains (intensive smarting, sensivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

#### Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

## 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

V002.1

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

### 5.2. Special hazards arising from the substance or mixture

In the event of fire, chlorine gas may be formed.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Avoid dust formation.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Open and handle container with care.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep only in original container.

Keep container tightly sealed.

Avoid strictly temperatures below 0 °C and above +50 °C.

### 7.3. Specific end use(s)

Air dryer

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Occupational Exposure Limits**

Valid for

Great Britain

None

## **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Calcium chloride 10043-52-4	Workers	Inhalation	Long term exposure - local effects		10 mg/m3	
Calcium chloride 10043-52-4	Workers	Inhalation	Acute/short term exposure - local effects		5 mg/m3	
Calcium chloride 10043-52-4	general population	Inhalation	Long term exposure - local effects		2,5 mg/m3	
Calcium chloride 10043-52-4	general population	Inhalation	Acute/short term exposure - local effects		5 mg/m3	

### **Biological Exposure Indices:**

None

## 8.2. Exposure controls:

Respiratory protection:

Not needed.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

Perforation time > 480 minutes

material thickness > 0.1 mm

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Skin protection:

Suitable protective clothing

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance tablet

solid

blue, white Odor typical

Odour threshold No data available / Not applicable

pН

V002.1

Initial boiling point	No data available / Not applicable
Flash point	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density	No data available / Not applicable
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Soluble

Solubility (qualitative) (20 °C (68 °F); Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable No data available / Not applicable Flammability Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable No data available / Not applicable Partition coefficient: n-octanol/water Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

### 9.2. Other information

No data available / Not applicable

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

At temperatures more than 770 °C, causes decomposition and chlorine evolution.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

None if used for intended purpose.

### 10.5. Incompatible materials

See section reactivity

## 10.6. Hazardous decomposition products

None known.

## **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## Eye irritation:

Causes serious eye irritation.

**OECD 405** 

## Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		

V002.1

## Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time	_	

## Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		

# **SECTION 12: Ecological information**

### General ecological information:

Do not empty into drains, soil or bodies of water.

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## 12.1. Toxicity

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
CA5-110.	турс		Study	tillic		
Calcium chloride	LC50	> 10.000 mg/l	Fish	96 h	Gambusia affinis	OECD Guideline
10043-52-4						203 (Fish, Acute
						Toxicity Test)
Calcium chloride	EC50	3.005 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
10043-52-4						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Calcium chloride	EC50	3.130 mg/l	Algae	96 h	Nitscheria linearis	OECD Guideline
10043-52-4						201 (Alga, Growth
						Inhibition Test)

### 12.2. Persistence and degradability

No data available.

## 12.3. Bioaccumulative potential / 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Calcium chloride	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
10043-52-4	Bioaccumulative (vPvB) criteria.

## 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 060314

# **SECTION 14: Transport information**

### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.4. Packaging group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0,00 %

(VOCV 814.018 VOC regulation

CH)

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 425396

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H290 May be corrosive to metals.

H319 Causes serious eye irritation.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

## Label elements (DPD):

## Xi - Irritant



#### Risk phrases:

R36 Irritating to eyes.

### Safety phrases:

S2 Keep out of the reach of children.

S22 Do not breathe dust.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S46 If swallowed, seek medical advice immediately and show this container or label.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.