

DS-3500 Premium Kit

- 2" full colour display (65,000 colours)
- 256 bit file encryption with DSS Pro audio codec
- Flexible dictation tagging (with DSS Pro)
- Device lock by PIN code

- · Control via Push buttons
- Perfect for recording conferences and interviews in stereo (with external stereo microphones)
- Geared for Dragon Naturally Speaking
- Dedicated docking station with easy and light connection feeling



Mobile dictation via push buttons

With its clear and simple operation concept, the DS-3500 ensures maximum efficiency and productivity. It has a 2" colour TFT LCD with 60,000 colours and white LED backlight. Access to all main commands is cleverly positioned on the unit side to allow intuitive operation via push buttons. For conference recording it also provides additional audio codecs. With an external stereo microphone you can create stereo recordings in MP3 or PCM (WAV).

Specifications

Storage Media

USB functionality

| USB Speed | USB 2.0 High Speed |
|-------------|----------------------|
| USB Classes | USB Composite device |
| | USB Audio class |
| | USB Storage class |
| | USB HID |

Display

| Display Type | Full colour TFT display |
|-------------------|-------------------------|
| Display colour | 65000 colours |
| Resolution | 176 x 220pixels |
| Display Size | 34 x 42mm / 2.1" |
| Display Backlight | LED (White) |

Device operation

| Main Switch | Push |
|---------------------|-----------------|
| Programmable button | 3 Smart Buttons |
| Power switch | Yes |
| HOLD switch | Yes |

PC control function

| Control Buttons | 3 programmable Smart |
|-----------------|----------------------|
| | Buttons |

File Format

| Data format | DSSPro (Digital Speech |
|-------------|--------------------------|
| | Standard Pro), MP3, WAV, |

Recording Modes

| Recording format | DSS Pro / PCM (WAV) / |
|------------------|------------------------|
| | MP3 |
| QP mode | 149h (with 2GB memory) |
| SP | 306h (with 2GB memory) |

Playback Modes

| Playback format | DSS Pro / DSS / PCM |
|-----------------|---------------------|
| | (WAV) / MP3 |



Sampling frequency

| QP | 16kHz |
|-----|-----------------------------|
| SP | 12kHz |
| PCM | 44.1kHz / 16bit |
| MP3 | 44.1kHz / 128kbps 44.1kHz / |
| | 256kbps |

Frequency response

| MP3 | 256kbps / 50 - 20000Hz |
|---------------|------------------------|
| | 128kbps / 50 - 17000Hz |
| PCM | 44.1kHz / 50 - 21000Hz |
| DSS / DSS Pro | QP / 200 - 7500Hz |
| | SP / 200 - 5500Hz |

Record function

| Index | Up to 32 per file |
|--------------------|------------------------------|
| Operation | New button |
| | Pause function |
| | Handsfree recording function |
| | via optional footswitch |
| | Verbal annotations (up to 32 |
| | per file) |
| Auto recording | VCVA recording |
| Sound control | Rec Monitor |
| Advanced recording | Direct recording |
| Editing | Insert |
| | |

Playback function

| Playback speed | Slow/Normal/Fast |
|------------------|-------------------------|
| Playback control | |
| File operation | Forward / Reverse Skip |
| | Fast forward and rewind |
| | Skip Playback |

Data organisation

| No. of folders for Voice | 1 - 7 programmable |
|--------------------------|--------------------|
| Time/date info | Yes |
| User ID setting | Yes |
| Erase | Erase all files |
| | Erase single files |
| | Partial |
| | Erase lock |

Workflow function

| Author ID Setting | 10 |
|---------------------|-------------------------|
| Worktype ID Setting | Yes 20 |
| Items | 10 |
| Dictation tags | Worktypes x Items = 200 |
| Priority setting | Yes |
| Pending File | Yes |

Technical Data

| AC power supply | Yes |
|-------------------------|---------------------|
| Power Supply | Lithium-Ion Battery |
| Individual Folder Names | Yes |

Software

| Corresponding Audio software (name) | ODMS R6 - Olympus Dictation Management System |
|-------------------------------------|---|
| Corresponding solution | DSS Player for MAC For (detailed) software |
| corresponding column | functions of Olympus |
| | dictation management |
| | software please refer to the |
| | relevant software pages. |

Interfaces Input

| SD / SDHC interface | - |
|---------------------|--|
| PC interface | USB cable and docking station |
| Microphone jack | 3.5 ø mm jack, impedance 2 $k\Omega$. |

Interfaces Output

| 235 mW (8 Ω speaker) |
|-----------------------------|
| Built-in ø23 mm round |
| dynamic speaker |
| 3.5 ø mm mini-jack, |
| impedance 8Ω or more |
| Toshiba FlashAir™ Card |
| compatibility |
| FlashAir™ is a trademark of |
| Toshiba Corporation. |
| |



Power Supply

Power Supply Battery: LI-42B

Rechargeable Lithium-Ion

battery

Li-Ion battery life Recording: with DSS Pro

(SP) approx. 21h

External power supply -

Internal Charging AC / USB / Cradle

Note: Internal charging operable only with Olympus rechargable batteries.

Dimensions

| Weight | 107g (incl. battery) |
|----------------|-----------------------|
| HxWxD | 114.5 x 49.8 x 17.5mm |
| Housing colour | Black |

Housing colour Black
Housing material Metal

Languages

| Menu languages | EN, DE, CZ, DK, ES, FR, |
|----------------|-------------------------|
| | NL, PL, RU, SV |

Hardware Security

| Device lock by PIN code | Yes |
|-----------------------------|----------------------------|
| Device Locky by Fingerprint | No |
| Lock single files | Yes DSS Pro real-time |
| | encryption (128 / 256 Bit) |

Operating Systems & Requirements

| Note | For Operating System & |
|------|------------------------------|
| | Requirements of Olympus |
| | dictation management |
| | software please refer to the |
| | relevant software web nages |

Other Features

| Voice recognition support | Geared for Dragon Naturally |
|---------------------------|-----------------------------|
| | Speaking |