



T5 Watt-Miser™ - High Output, G5 Cap FT5/36W/840/GE/WM/SL1/30 61075



# **Product information**

T5 Watt-Miser™ lamps are energy saving triphosphor fluorescent lamps with 16mm outer diameter for general T5 lighting applications.

#### **Application areas**






(III) Education

🔛 Industrial











# Product data

Cap/Base	G5
Bulb Shape	Tubular
Bulb Diameter [mm]	16
Bulb maximum overall diameter [mm]	16
Cap to Cap Length (Max) [mm]	849
Net weight per piece [g]	77
Gross weight per piece [g]	100
Mercury Content [mg]	2.5
UV radiance	Exempt
Regulatory comment	EUP related
Brand	General Electric (GE)

# Performance data

Colour Code	840
Colour Rendering Index (CRI) [Ra]	85
Nominal correlated colour temperature (CCT) [K]	4000
Nominal lumens [lm]	3500
Lumen at 25°C [lm]	3200
Rated efficacy [lm/W]	97
Energy efficiency class (EEC)	A+
Rated Life [h]	25000
Rated median life on electronic (HF) ballast on IEC 12- hour cycle	30000
Rated median life on electronic (HF) ballast on IEC 3- hour cycle	25000
Weighted energy consumption [kWh/1000h]	39.09





# **Electrical data**

Nominal power [W]	36
Design Ambient Temperature [°C]	35
Design Lamp ambient temperature [°C]	35
Starting ambient temperature range	-15
Dimming Capability	No


# Logistic data

DUN Code	10043168610756
EAN Code	0043168883443
Pack Quantity	30
Inner pack type	SLEEVE
Outer pack type	OUTER BOX
Layer quantity	180 EUR, 300 UK
Layer quantity EUR	180
Layer quantity UK	300
Pallet quantity EUR (PC)	1800
Pallet quantity UK (PC)	3000
Outer case size	890 x 120 x 102 (mm)
Product status	Available






#### **Technical drawing**




#### Lumen maintenance data








#### Survival data



#### Service life data







#### **Downloads & Links**

Go to the catalog site (HTTP)

Linear Fluorescent Lamps Catalogue (PDF)

LFL T5 Watt-Miser™ Lamps Data sheet (EN) (PDF)

Lighting design tools & calculators (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)