











CSI/CID

CSI400 99-0201

88495

Product information

A range of discharge lamps from 400 to 1000W giving high lumen for a variety of specialist applications in single ended and PAR format.

Application areas



Other









Product data

Cap/Base	Special
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	32
Maximum Overall Length [mm]	55
Light Center Length [mm]	25.5
Arc Gap	9
Net weight per piece [g]	100
Gross weight per piece [g]	113
Operating position	VBD - Vert Base Down
Brand	General Electric (GE)

Performance data

Colour Code	840
Colour Rendering Index (CRI) [Ra]	80
Nominal correlated colour temperature (CCT) [K]	4000
Nominal lumens [lm]	32000
Energy efficiency class (EEC)	А
Nominal chromaticity coordinate X	0.385
Nominal chromaticity coordinate Y	0.39
Weighted energy consumption [kWh/1000h]	440

Electrical data

Nominal power [W]	400
Nominal lamp voltage [V]	100
Lamp Current [A]	5
Startup time [sec]	30
Dimming Capability	No
Ballast Required	Yes





Logistic data

DUN Code	10043168884959
EAN Code	5021731314025
Pack Quantity	1
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	560 EUR, 720 UK
Layer quantity EUR	560
Layer quantity UK	720
Pallet quantity EUR (PC)	5040
Pallet quantity UK (PC)	5040
Outer case size	195 x 80 x 115 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination