









76 lumens/watt

CSI/CID

CSI1000/PAR64/G38

88514

# **Product information**

A range of discharge lamps from 400 to 1000W giving high lumen for a variety of specialist applications in single ended and PAR format.

#### **Application areas**



Other









### **Product data**

Cap/Base	G38
Bulb Shape	PAR
Bulb Finish	Clear
Bulb Diameter [mm]	204
Maximum Overall Length [mm]	175
Net weight per piece [g]	950
Gross weight per piece [g]	1420
Operating position	HOR - Horizontal
Brand	General Electric (GE)

## Performance data

Colour Code	838
Colour Rendering Index (CRI) [Ra]	80
Nominal correlated colour temperature (CCT) [K]	3800
Nominal beam angle [°]	6
Nominal lumens [Im]	76000
Energy efficiency class (EEC)	С
Nominal chromaticity coordinate X	0.42
Nominal chromaticity coordinate Y	0.41
Weighted energy consumption [kWh/1000h]	1100

#### **Electrical data**

Nominal power [W]	1000
Nominal lamp voltage [V]	80
Lamp Current [A]	14.7
Startup time [sec]	50
Dimming Capability	No
Ballast Required	Yes







### Logistic data

DUN Code	10043168885147
EAN Code	5021731314025
Pack Quantity	1
Layer quantity	8 EUR, 12 UK
Layer quantity EUR	8
Layer quantity UK	12
Pallet quantity EUR (PC)	32
Pallet quantity UK (PC)	60
Outer case size	280 x 280 x 220 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

**Lighting design tools & calculators (HTTP)** 

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### **Disclaimer**

Special purpose lamp - Stage Studio. Not suitable for household illumination.