











CSI/CID CID1000/G22 99-0222

88493

Product information

A range of discharge lamps from 400 to 1000W giving high lumen for a variety of specialist applications in single ended and PAR format.

Application areas



Other









Product data

Cap/Base	G22
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	32
Maximum Overall Length [mm]	115
Light Center Length [mm]	63.5
Arc Gap	15
Net weight per piece [g]	119
Gross weight per piece [g]	170
Operating position	U - Universal
Brand	General Electric (GE)

Performance data

Colour Code	855
Colour Rendering Index (CRI) [Ra]	85
Nominal correlated colour temperature (CCT) [K]	5500
Nominal lumens [lm]	70000
Energy efficiency class (EEC)	A
Nominal chromaticity coordinate X	0.3
Nominal chromaticity coordinate Y	0.3
Weighted energy consumption [kWh/1000h]	1100

Electrical data

Nominal power [W]	1000
Nominal lamp voltage [V]	80
Lamp Current [A]	15
Startup time [sec]	60
Dimming Capability	No
Ballast Required	Yes





Logistic data

DUN Code	10043168884935
EAN Code	5021731314025
Pack Quantity	1
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	162 EUR, 210 UK
Layer quantity EUR	162
Layer quantity UK	210
Pallet quantity EUR (PC)	1458
Pallet quantity UK (PC)	1890
Outer case size	245 x 135 x 110 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination