





PAR 36

24425

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas



Club and Disco









Product data

| Cap/Base | Screw terminal |
|-----------------------------|-----------------------|
| Bulb Shape | PAR |
| Bulb Diameter [mm] | 114 |
| Maximum Overall Length [mm] | 70 |
| Light Center Length [mm] | 41.27 |
| Net weight per piece [g] | 248 |
| Gross weight per piece [g] | 250 |
| Brand | General Electric (GE) |

Performance data

| Nominal beam angle [°] | 15 |
|---|-------|
| Nominal center beam candlepower (CBCP) [cd] | 50000 |

Electrical data

| Nominal power [W] | 30 |
|--------------------------|------|
| Nominal lamp voltage [V] | 12 |
| Lamp Current [A] | 2.34 |
| Coil type | C-6 |
| Ballast Required | Yes |





Logistic data

| DUN Code | 00043168244251 |
|-------------------------|----------------------|
| Pack Quantity | 12 |
| Layer quantity | 1 UK |
| Layer quantity UK | 1 |
| Pallet quantity UK (PC) | 1200 |
| Outer case size | 226 x 211 x 313 (mm) |
| Product status | Available |

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special purpose lamp – Aircraft. Not suitable for household illumination.