



GE
Lighting



1976
kWh/1000h

C
energy class

25
lumens/watt

Double Ended Quartzline

P2/27 FEX 240V

88481


Product information

Precision range of double ended Quartzline® lamps widely used in theatre and many other applications. A range from 350 W to 2,000 W with 3200K.

Application areas



Theatre



WORLDWIDE PARTNER

Product data

Cap/Base	Rx7s
Bulb Shape	Tubular
Bulb Diameter [mm]	30
Maximum Overall Length [mm]	143
Net weight per piece [g]	46
Gross weight per piece [g]	165
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	3200
Nominal lumens [lm]	50000
Energy efficiency class (EEC)	C
Rated Life [h]	300
Weighted energy consumption [kWh/1000h]	1975.92

Electrical data

Nominal power [W]	2000
Nominal lamp voltage [V]	240
Coil type	CC-8
Dimming Capability	Yes
Ballast Required	No

Logistic data

DUN Code	10043168884812
EAN Code	0043168884815
Pack Quantity	12
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	144 EUR, 180 UK
Layer quantity EUR	144
Layer quantity UK	180
Pallet quantity EUR (PC)	1152
Pallet quantity UK (PC)	1440
Outer case size	350 x 190 x 120 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination