











# Single Ended Halogen M38 230-240V

88442

# **Product information**

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs -Chromised seal protection up to 500° C.

#### **Application areas**





) Film and Broadcast









## **Product data**

Cap/Base	GY9.5
Bulb Shape	Tubular
Bulb Diameter [mm]	28.5
Maximum Overall Length [mm]	80
Light Center Length [mm]	45.5
Net weight per piece [g]	15
Gross weight per piece [g]	30
Brand	General Electric (GE)

### Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	2900
Nominal lumens [lm]	5500
Energy efficiency class (EEC)	E
Rated Life [h]	2000
Weighted energy consumption [kWh/1000h]	297.52

## **Electrical data**

Nominal power [W]	300
Nominal lamp voltage [V]	240
Coil type	CC-7A
Ballast Required	No





### Logistic data

DUN Code	10043168884423
EAN Code	0043168884426
Pack Quantity	24
Layer quantity	504 EUR, 600 UK
Layer quantity EUR	504
Layer quantity UK	600
Pallet quantity EUR (PC)	4032
Pallet quantity UK (PC)	4800
Outer case size	255 x 175 x 130 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination