# FLOOR MAINTAINER

Marble • Vinyl • Rubber • Stone • Sealed Wood

## **USES**

Mock

Floor Maintainer is a floor maintainer that recoats and repairs floors to leave a flexible, slip resistant finish. Keeps floors at the peak of their appearance and restores those that are losing their shine.

The fragrant, low viscosity, opaque, rose-coloured liquid can either be applied with a mop and left to dry or used through spray cleaning equipment.


Suitable for use on marble, terrazzo, linoleum, vinyl, rubber, tiles, sealed wood and sealed cork.

# **DIRECTIONS**

Shake before use and dilute according to the job. Always brush floor to remove loose debris prior to application. Clean heavily soiled floors prior to application.

SPRAY CLEANING/BURNISHING - Spray *Floor Maintainer* solution onto the immediate floor area. Allow a few seconds contact time and burnish the floor dry.

DAMP MOPPING - Apply *Floor Maintainer* solution using a mop, agitate and remove any excess liquid. Allow the floor to dry. Machine burnish for a high gloss.







### **AREAS OF USE**





Rubber

Wood





Marble

PVC

### **DILUTIONS**

FLOOR MAINTAINER: WATER

SPRAY BURNISHING 1:10

DAMP MOPPING 1:20



