

3M50773

3M50786

3M Photomount (PL 9479)



## Safety Data Sheet

Copyright, 2017, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 27-7280-4 Version number: 6.01  
Revision date: 22/09/2017 Supersedes date: 20/05/2016  
Transportation version number: 4.00 (03/08/2016)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier  
3M Photomount (PL 9479)

Product Identification Numbers  
YP-2080-6060-5 YP-2080-6063-9  
7000116732 7000116734

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses  
Adhesive aerosol.

1.3. Details of the supplier of the safety data sheet  
Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
Telephone: +44 (0)1344 858 000  
E Mail: tox.uk@mmm.com  
Website: www.3M.com/uk

1.4. Emergency telephone number  
+44 (0)1344 858 000

### SECTION 2: Hazard identification

2.1. Classification of the substance or mixture  
CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:  
Aerosol, Category 1 - Aerosol 1; H222, H229  
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319  
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

## 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

### SIGNAL WORD

DANGER.

### Symbols:

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS09 (Environment) |

### Pictograms



### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Acetone	67-64-1	200-662-2	15 - 40

### HAZARD STATEMENTS:

H222	Extremely flammable aerosol.
H229	Pressurised container. may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS

#### General:

P102 Keep out of reach of children.

#### Prevention:

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.

#### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

#### Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

42% of the mixture consists of components of unknown acute oral toxicity.

Contains 5% of components with unknown hazards to the aquatic environment.

### Notes on labelling

H304 is not required on the label because the product is an aerosol.

## 2.3. Other hazards

May cause frostbite.

### SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Acetone	67-64-1	200-662-2		15 - 40	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066
Propane	74-98-6	200-827-9	01-2119486944-21	25 - 35	Flam. Gas 1, H220; Liquified gas, H280 - Nota U
Non-volatiles	Trade Secret			10 - 30	Substance not classified as hazardous
Cyclohexane	110-82-7	203-806-2		10 - 30	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1
Resin acids and Rosin acids, esters with diethylene glycol	68153-38-8	268-884-2		0 - 3	Substance not classified as hazardous
Non Hazardous Ingredients	Mixture			1 - 2	Substance not classified as hazardous

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### Inhalation

Remove person to fresh air. Get medical attention.

##### Skin contact

Thaw frosted skin with lukewarm water. Do not rub affected area. Get medical attention.

##### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

##### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

#### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Cyclohexane	110-82-7	UK HSC	TWA:350 mg/m <sup>3</sup> (100 ppm);STEL:1050 mg/m <sup>3</sup> (300 ppm)	
Acetone	67-64-1	UK HSC	TWA:1210 mg/m <sup>3</sup> (500 ppm);STEL:3620 mg/m <sup>3</sup> (1500 ppm)	
Propane	74-98-6	UK HSC	Limit value not established:	asphyxiant

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
Indirect vented goggles.

##### Applicable Norms/Standards

Use eye protection conforming to EN 166

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

## 3M Photomount (PL 9479)

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

### Applicable Norms/Standards

Use gloves tested to EN 374

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

### Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

### Thermal hazards

Wear cold insulating gloves/face shield/eye protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Appearance/Odour	Mild solvent odour; Clear mist
Odour threshold	No data available.
pH	Not applicable.
Boiling point/boiling range	Not applicable.
Melting point	Not applicable.
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	-47 °C
Autoignition temperature	No data available.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Relative density	0.7 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	No data available.
Decomposition temperature	No data available.
Viscosity	Not applicable.
Density	0.7 kg/m <sup>3</sup>

### 9.2. Other information

EU Volatile Organic Compounds	No data available.
Percent volatile	84.3 % weight [Test Method:Estimated]

## SECTION 10: Stability and reactivity

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

#### 10.5 Incompatible materials

None known.

#### 10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Intentional concentration and inhalation may be harmful or fatal. Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Frostbite: Signs/symptoms may include intense pain, discoloration of skin, and tissue destruction. Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

#### Eye contact

Frostbite: Signs/symptoms may include intense pain, clouding of the cornea, redness, swelling, and blindness. Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause:

Cardiac sensitisation: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Propane	Rabbit	Minimal irritation
Acetone	Mouse	Minimal irritation
Cyclohexane	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Propane	Rabbit	Mild irritant
Acetone	Rabbit	Severe irritant
Cyclohexane	Rabbit	Mild irritant

**Skin Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Propane	In Vitro	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cyclohexane	In Vitro	Not mutagenic



3M Photomount (PL 9479)

Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
-------------	---------	--

**Carcinogenicity**

Name	Route	Species	Value
Acetone	Not specified.	Multiple animal species	Not carcinogenic

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Propane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic	Not classified	Human	NOAEL 3	6 weeks

**3M Photomount (PL 9479)**

		system			mg/l	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart   liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks

**Aspiration Hazard**

Name	Value
Cyclohexane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l

**3M Photomount (PL 9479)**

Acetone	67-64-1	Crustacea other	Experimental	24 hours	LC50	2,100 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Propane	74-98-6		Data not available or insufficient for classification			
Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
Cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
Non-volatiles	Trade Secret		Data not available or insufficient for classification			
Resin acids and Rosin acids, esters with diethylene glycol	68153-38-8		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 % weight	OECD 301D - Closed bottle test
Acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	Other methods
Propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	Other methods
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 % BOD/ThBOD	OECD 301F - Manometric respirometry
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.14 days (t 1/2)	Other methods
Non-volatiles	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Resin acids and Rosin acids, esters with diethylene glycol	68153-38-8	Experimental Aquatic Biodegrad. - Aerobic	28 days	CO2 evolution	19.7 % weight	OECD 301B - Modified sturm or CO2

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	Other methods
Propane	74-98-6	Experimental Bioconcentration		Log Kow	2.36	Other methods
Cyclohexane	110-82-7	Experimental BCF-Carp	56 days	Bioaccumulation factor	129	OECD 305E - Bioaccumulation flow-through fish test
Non-volatiles	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Resin acids and Rosin acids, esters with diethylene glycol	68153-38-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

No information available at this time, contact manufacturer for more details

**12.6. Other adverse effects**

3M Photomount (PL 9479)

Material	CAS Nbr	Ozone Depletion Potential	Global Warming Potential
acetone	67-64-1	0	

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. The facility should be equipped to handle gaseous waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

#### EU waste code (product as sold)

- 08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 16 05 04\* Gases in pressure containers (including halons) containing dangerous substances
- 20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

#### EU waste code (product container after use)

- 15 01 04 Metallic packaging

## SECTION 14: Transportation information

YP-2080-6060-5, YP-2080-6063-9

ADR/RID: UN1950, AEROSOLS, LIMITED QUANTITY, 2.1, (E), ADR Classification Code: 5F.

IMDG-CODE: UN1950, AEROSOLS, 2.1, IMDG-Code segregation code: NONE, LIMITED QUANTITY, EMS: FD,SU.

ICAO/IATA: UN1950, AEROSOLS, FLAMMABLE, 2.1.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information.

### 15.2. Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

### List of relevant H statements

- EUH066 Repeated exposure may cause skin dryness or cracking.
- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.

H225	Highly flammable liquid and vapour.
H229	Pressurised container. may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

**Revision information:**

Section 01: SAP Material Numbers information was added.

CLP: Ingredient table information was modified.

Label: CLP Percent Unknown information was modified.

Section 3: Composition/ Information of ingredients table information was added.

Section 3: Composition/ Information of ingredients table information was deleted.

Section 7: Conditions safe storage information was modified.

Section 7: Precautions safe handling information information was modified.

Section 9: Property description for optional properties information was modified.

Section 9: Relative density information information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 13: Standard Phrase Category Waste GHS information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at [www.3M.com/uk](http://www.3M.com/uk)

