

# Samsung Mono Laser Printer ML-5510ND/ML-6510ND





#### Key Features:

- Print Speeds up to 52ppm/62ppm in A4
- First Print Out Time 7.8 seconds (from Ready Mode)
- Improved Print Quality with up to 1,200 x 1,200 dpi
- Maximum Monthly Duty Cycle 275,000 sheets
- Quiet Operation at less than 56dBA (printing)
- Standard Cartridge Yield of 10,000 pages
- Samsung 700MHz processor
- 520-sheet input capacity, 100-sheet multi-purpose tray
- Direct Printing from USB memory
- Secure Printing

#### Seamless integration for a simple business workflow solution

The Samsung ML-5510ND/ML-6510ND provides hassle-free integration for a simple business workflow solution.

Delivering a business print solution that answers both simplicity and productivity needs can be a challenge, especially across today's diverse business environment. With hassle-free integration and easy-to-use functionality, the Samsung Mono Laser Printer ML-5510ND/ML-6510ND delivers unlimited productivity – simply.


With innovative features and high capacity toner cartridges, the Samsung ML-5510ND/ML-6510ND enables your business to deliver considerable savings on your print costs.

#### Top 4 Reasons to Buy:

### 1

#### Value for money

- Lower cost per page and fewer toner replacements with extra high yield toner cartridges.
- Separate toner and drum cartridges allows for a reduction in TCO by replacing the drum unit only when required and not with every new toner cartridge.



- 700MHz dual-core processor, and 1Gigabit LAN -Enables large size of documents from multiple users to be transmitted and processed fast.
- Fast printout speeds of up to 62ppm and a First Print Out Time of 7.8 seconds.

#### 3 User friendly and reliable

• Easy to use 4 line LCD control panel and numeric keypad for effective operation.

#### 4 Out-of-box security solution

- Secure Job Release with numeric keypad
- Optional Barcode Printing Solution



Product Datasheet

## Samsung Mono Laser Printer ML-5510ND/ML-6510ND

## **Product Specifications**

ML-5510ND/SEE

ML-6510ND/SEE

Print		
, · · · · · ·		
Speed (Mono)	Up to 52ppm in A4 (55ppm in Letter)	Up to 62ppm in A4 (65ppm in Letter)
Resolution	Up to 1,200 x 1,200 dpi effective output	
First Print Out Time (Mono)	As fast as 7.8 seconds	
Emulation	PCL5e, PCL6, KS/KSSM, KS5895, IBM ProPrinter, EPSON, PostScript3, PDF Direct V1.7, XPS v1.0	
Duplex	Built-in	
Paper Handling		
Input Capacity and Types	520-sheet Cassette, 100-sheet Multi-Purpose Tray / Max 3,660 Sheet Paper Capacity	
Output Capacity and Type	500-sheet Face-Down	
Media Size	76mm x 127mm (3"" x 5"") ~ 216mm x 356mm (8.5"" x 14""), (Envelope: Monarch, No10, DL, C5, C6, No9)	
Media Type	Printer Default, Plain Paper, Thick Paper, Thin Paper, Bond Paper, Colour Paper, CardStock, Labels, Transparency, Envelope, Pre-printed, Recycled Paper, Archive, Extra Thick	
Envelope Capacity	50 sheets from Cassette and 50 sheets from optional 1st Second Cassette, (Max. 100 sheets)	
General		
Processor	Samsung 700MHz processor	
Memory/Storage	256MB (Max. 768MB) & Optional 160GB Hard Disk Drive	
OS Compatibility	Windows 2000/XP (32/64bits)/Vista (32/64bits)/2003 Server (32/64bits)/2008 Server (32/64bits)/7 (32/64bits)/2008 Server R2 (64bits) Various Linux OS: RedHat Enterprise Linux WS 4, 5 (32/64 bit) Fedora 4, 5, 6, 7, 8, 9, 10, 11, 12 (32/64 bit) SuSE Linux 10.0, 10.1 (32 bit) OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) Mandriva 2005, 2006, 2007, 2008, 2009, 2009.1 (32/64 bit) Ubuntu 5.04, 5.10, 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10 (32/64 bit) SuSE Linux Enterprise Desktop 10, 11 (32/64 bit) Debian 4.0, 5.0 (32/64 bit) Mac OS 10.3 ~ 10.6UNIX OS: Sun Solaris 9,10 (x86, SPARC) HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) IBM AIX 5.1, 5.2, 5.3, 5.4	
Interface	Ethernet 10/100/1000 Base TX, High Speed USB 2.0, Host USB 2 Port (Rear 1 Port & Front 1 Port), IEEE 1284B Parallel connector (Option), 802.11 b,g, n wireless network (Option)	
Noise Level	Less than 56dBA (Printing), Background Noise Only (Less tha (Standby)	n 30dBA) Less than 58dBA (Printing), Background Noise Only (Less than 30dBA) (Standby)
Duty Cycle, Monthly	275,000 sheets	
Dimension (WxDxH)	464mm x 540mm x 420mm	
Weight	34.8kg (Inc. Imaging Unit/Toner/WTB), 31.2kg (exc. Imaging Unit/Toner/WTB)	
Power Consumption	820W(Active)/100W(Ready)/10W(Sleep)	900W(Active)/120W(Ready)/10W(Sleep)

Consumables		
Yield	Standard: Average Cartridge Yield 10,000 standard pages High Yield: Average Cartridge Yield 30,000 standard pages (ships with 10,000 pages Starter Toner Cartridge) Imaging Unit: Average Yield 80,000 standard pages; Declared Cartridge Yield in accordance with ISO/IEC 19752.	
Туре	2-piece Cartridge (Toner and Imaging Unit (Drum Unit))	
Codes	Toner Cartridge: MLT-D309L/ELS –10,000 Pages,, MLT-D309S/ELS – 30,000 Pages, Imaging Unit: MLT-R309/ELS – 80,000 Pages	
Options		
Options	520 Sheet Paper Tray - ML-S6510A/SEE 2,000 Sheet High Capacity Feeder - ML-H6510A/SEE Short Stand - ML-DSK65S/SEE 512mb Memory - ML-MEM170/SEE 160GB Hard Disk Drive - ML-HDK465/SEE 500 Sheet Staple Finisher - ML-OCT65/SEE 400 Sheet 4 Bin Mailbox - ML-MBT65/SEE Wireless Network Card - ML-NWA65L/SEE IEEE 1284B Parallel Connector - ML-PAR100/SEE Barcode Solution - SOL-BPSV1/SEE	































