



Printing date 15.08.2018 Revision: 17.07.2018

### SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

- · 1.1 Product identifier
- · Trade name: QCONNECT® LEXMARK® C540H2KG BLACK HIGH YIELD
- · Article number: OB02347
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Product category PC18 Ink and toners
- · Process category

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

- Environmental release category ERC7 Use of functional fluid at industrial site
- · Article category AC13 Plastic articles
- · Application of the substance / the mixture Printing inks
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Static Control Components (Europe) Ltd.

Unit 30, Worton Drive

Reading

Berkshire RG2 0TG

United Kingdom

info@scceurope.co.uk

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: During normal opening times (08:00-17:00): +44 (0) 118-923-8800

### **SECTION 2: Hazards Identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) NO. 1272/2008

The product is not classified, according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 None required
- · Hazard pictograms None required
- · Signal word None required
- · Hazard statements None required
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

## **SECTION 3:** Composition/Information on Ingredients

· **Description:** Resin mixture

· Dangerous components:				
CAS: 1333-86-4	Carbon black (bound)	substance with a Community workplace exposure limit	>2.5-≤10%	
EINECS: 215-609-9				

(Contd. on page 2)



Printing date 15.08.2018 Revision: 17.07.2018

Trade name: QCONNECT® - LEXMARK® C540H2KG BLACK HIGH YIELD

(Contd. of page 1)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First Aid Measures**

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting Measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

Like most finely divided organic powders, toner dust may form an explosive mixture in air.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

### **SECTION 6: Accidental Release Measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Vacuum or sweep the material into a sealed container. If a vacuum is used it must be dust explosion-proof. Dispose of in compliance with national, state, regional or provincial regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and Storage**

### · 7.1 Precautions for safe handling

No special measures required.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

No special precautions are necessary if used correctly.

Use only in well ventilated areas.

(Contd. on page 3)





Printing date 15.08.2018 Revision: 17.07.2018

Trade name: QCONNECT® - LEXMARK® C540H2KG BLACK HIGH YIELD

(Contd. of page 2)

- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

· Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials as well as heavy-metal compounds.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from humidity and water.

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure Controls/Personal Protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

### 1333-86-4 Carbon black (bound)

WEL Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³

· Additional Occupational Exposure Limit Values for possible hazards during processing:

USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous Silica: USA OSHA (TWA/PEL): 20mppcf 80 mg/m3, ACGIH (TWA/TLV): 10 mg/m3

TRGS 900 (Luftgrenzwert): 10 mg/m3 (Einatembare partikel)). 3 mg/m3 (Alveolengängige fraktion)

UK WEL: 10 mg/m3 (Respirable Dust) 5 mg/m3 (Inhalible Dust)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale dust / smoke / mist.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)





Printing date 15.08.2018 Revision: 17.07.2018

Trade name: QCONNECT® - LEXMARK® C540H2KG BLACK HIGH YIELD

· Eye protection: Safety glasses

(Contd. of page 3)

SECTION 9: Physical and Chem	SECTION 9: Physical and Chemical Properties				
· 9.1 Information on basic physical and o	chemical properties				
· General Information	K K X				
· Appearance:					
Form:	Powder				
Colour:	Black				
· Odour:	Characteristic				
· Odour threshold:	Not determined.				
· pH-value:	Not applicable.				
· Change in condition					
Melting point/freezing point:	>100-150 °C				
Initial boiling point and boiling range	e: Undetermined.				
· Flash point:	No data available.				
· Flammability (solid, gas):	Not determined.				
· Decomposition temperature:	Not determined.				
· Auto-ignition temperature:	Product is not selfigniting.				
· Explosive properties:	Product does not present an explosion hazard in its original state.				
· Explosion limits:					
Lower:	Not determined.				
Upper:	Not determined.				
· Vapour pressure:	No data available.				
· Density at 20 °C:	$1.3 \text{ g/cm}^3$				
	Not determined.				
· Relative density	Not determined.				
Vapour density	No data available.				
· Evaporation rate	No data available.				
· Solubility in / Miscibility with					
water:	Insoluble.				
· Partition coefficient: n-octanol/water:	Not determined.				
· Viscosity:					
Dynamic:	No data available.				
Kinematic:	No data available.				
· Solvent content:					
VOC (EC)	0.00 %				
Solids content:	100.0 %				





Printing date 15.08.2018 Revision: 17.07.2018

Trade name: QCONNECT® - LEXMARK® C540H2KG BLACK HIGH YIELD

(Contd. of page 4)

· 9.2 Other information

No further relevant information available.

## **SECTION 10: Stability and Reactivity**

- · 10.1 Reactivity Non reactive.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological Information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Other information (about experimental toxicology):
- Mutagenicity: Ames test Negative (According to the test result of similar composition.)
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological Information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 6)





Printing date 15.08.2018 Revision: 17.07.2018

Trade name: QCONNECT® - LEXMARK® C540H2KG BLACK HIGH YIELD

(Contd. of page 5)

• 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal Considerations**

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.
- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

<b>SECTION 14: Transport Information</b>	
· 14.1 UN-Number	Not a regulated material under the United States DOT, IMDG ADR, RID, or ICAO/IATA.
· ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name	Not a regulated material under the United States DOT, IMDO ADR, RID, or ICAO/IATA
· ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	Not a regulated material under the United States DOT, IMDO ADR, RID, or ICAO/IATA.
· ADR, ADN, IMDG, IATA	
· Class	Void
· 14.4 Packing group	Not a regulated material under the United States DOT, IMDO ADR, RID, or ICAO/IATA.
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II	of Marpol
and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

## **SECTION 15: Regulatory Information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.





Printing date 15.08.2018 Revision: 17.07.2018

Trade name: QCONNECT® - LEXMARK® C540H2KG BLACK HIGH YIELD

(Contd. of page 6)

### **SECTION 16: Other Information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of

Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

### \* Data compared to the previous version altered.

No changes to the Material Safety Data Sheet, all sections are current as the date of print seen above describes.

GB