

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

HP Color LaserJet Q7561A Cyan Print Cartridge

Use of the preparation

This product is a cyan toner preparation that is used in HP Color LaserJet 3000 series printers.

Revision Date

16-Jan-2008

Company identification

Hewlett-Packard, Ltd. Cain Road, Amen Corner

Bracknell, Berkshire, RG12 1HN

Emergency telephone number

Poison Information Center 0207771 5307

Hewlett-Packard health effects line

(Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199

General information telephone number

1 344 36-0000

(Toll-free within the US)

1-800-474-6836 1-208-323-2551

(Direct) Email

hpcustomerinquiries@hp.com

2. HAZARDS IDENTIFICATION

Acute health effects

Skin contact Unlikely to cause skin irritation.

Eye contact May cause transient slight irritation.

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust.

Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

Potential health effects

Routes of exposure Potential routes of exposure under normal use conditions are skin and eye contact; and

inhalation

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carcinogenicity None of the ingredients have been classified as carcinogens according to EU, IARC, MAK, NTP,

OSHA or ACGIH.

Physical hazardsNot classified as a physical hazard. **Health hazards**Not classified as a health hazard.

Environmental hazards Not classified as an environmental hazard.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive

1999/45/EC, as amended.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS number	% by weight	EU number	EU classification
Trade Secret	75 - 85		
Trade Secret	5 - 15		
	Trade Secret	weight Trade Secret 75 - 85	weight Trade Secret 75 - 85

Material name Q7561A SDS UK
Creation date 20-Oct-2005 Version number 3 1 / 6



Trade Secret Copper compound 1 - 5

Amorphous silica 7631-86-9 1 - 2418-260-2

4. FIRST AID MEASURES

Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.

Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure)

for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

5. FIRE-FIGHTING MEASURES

Flash point and method not applicable

Fire fighting

equipment/instructions

If fire occurs in the printer, treat as an electrical fire.

Suitable extinguishing media CO2, water, or dry chemical

Extinguishing media which must not be used for safety

reasons

None known.

Unusual fire & explosion

hazards

Like most organic material in powder form, toner can form explosive dust-air mixtures when

finely dispersed in air.

Hazardous combustion

products

Carbon monoxide and carbon dioxide.

Specific methods None established.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Minimize dust generation and accumulation.

Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

7. HANDLING AND STORAGE

Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Keep out of the reach of children. Store at room temperature in the original container. Keep Storage

the container tightly closed and dry. Store away from strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits

Germany

Components CAS# **TWA MAK** Ceiling 4 mg/m3 7631-86-9 Not established Amorphous silica 4 mg/m3

Switzerland

Amorphous silica

Components CAS# **TWA STEL** 7631-86-9 4 mg/m3 Not established

SDS UK Material name Q7561A Version number 3 Creation date 20-Oct-2005 2/6

United Kingdom

TWA STEL Components CAS# Amorphous silica 7631-86-9 6 mg/m3 18 mg/m3

Additional exposure data USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV):

10 mg/m3

UK WEL: 10 mg/m3 (Respirable Dust), 5 mg/m3 (Inhalable Dust)

United Kingdom - Workplace Exposure Limits (WELs) - STELs

Amorphous silica 7631-86-9 18 mg/m3 STEL (inhalable dust); 7.2 mg/m3 STEL (respirable dust)

United Kingdom - Workplace Exposure Limits (WELs) - TWAs

Amorphous silica 7631-86-9 6 mg/m3 TWA (inhalable dust); 2.4 mg/m3 TWA (respirable dust)

Personal protective equipment

General No personal respiratory protective equipment required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Fine powder **Appearance Physical state** Not available

Form solid Colour Cyan

Odour Slight plastic odor

Odour threshold Not available pН not applicable **Boiling point** not applicable Flash point not applicable Not available. **Flammability** Not available

Flammability limits in air, upper, % by volume

Flammability limits in air,

lower, % by volume

Not flammable

Vapour pressure not applicable Relative density Not available

Solubility in water Negligible in water. Partially soluble in toluene and xylene.

Partition coefficient (n-octanol/water)

Not available

Viscosity not applicable Vapour density not applicable **Evaporation rate** not applicable Not available Melting point Freezing point Not available



Auto-ignition temperature not applicable **Specific gravity** 1 - 1.2 (H2O = 1)

Softening point 100 - 150 °C (212 - 302 °F)

10. STABILITY AND REACTIVITY

Stability Stable under normal storage conditions.

Conditions to avoid Imaging Drum: Exposure to light

Materials to avoid Not available

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

Hazardous polymerisation

Will not occur.

11. TOXICOLOGICAL INFORMATION

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Amorphous silica 7631-86-9 Oral LD50 Rat: >5000 mg/kg; Dermal LD50 Rabbit: >2000 mg/kg

Inhalation toxicity No information available.

Not classified for Acute inhalation toxicity according to EU Directive 67/548/EEC and

1999/45/EC.

Oral toxicity LD50/oral/rat >2000mg/kg, (OECD 401), Not harmful.

Not classified for Acute oral toxicity according to EU Directive 67/548/EEC and 1999/45/EC.

Eye irritation Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

Chronic toxicity No information available.

SensitisationNot classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA

HCS (US).

Carcinogenicity Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA

Regulations (USA), EU Directive, or Proposition 65 (California).

Mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Reproductivity Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop.

65, and DFG (Germany).

Further information Complete toxicity data are not available for this specific formulation.

Refer to Section 3 for potential health effects and Section 4 for first aide measures.

12. ECOLOGICAL INFORMATION

Other adverse effects This product has not been tested for ecological effects.

13. DISPOSAL CONSIDERATIONS

Disposal instructions Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely

dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal,

state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if

this service is available in your location, please visit http://www.hp.com/recycle.

Material nameQ7561ASDS UKCreation date20-Oct-2005Version number34 / 6

Waste from residues / unused products

Not available

Contaminated packaging

Not available

14. TRANSPORT INFORMATION

ADR

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

General Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.

15. REGULATORY INFORMATION

International regulations All chemical substances in this HP product have been notified or are exempt from notification

under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

Labelling

Contains Amorphous silica, Copper compound, Styrene acrylate copolymer, Wax

16. OTHER INFORMATION

Manufacturer information Hewlett-Packard Company

11311 Chinden Boulevard Boise, ID 83714 USA

List of relevant R phrases

United Kingdom - Workplace Exposure Limits (WELs) - STELs

Amorphous silica 7631-86-9 18 mg/m3 STEL (inhalable dust); 7.2 mg/m3 STEL (respirable dust)

United Kingdom - Workplace Exposure Limits (WELs) - TWAs

Amorphous silica 7631-86-9 6 mg/m3 TWA (inhalable dust); 2.4 mg/m3 TWA (respirable dust)

Other information This MSDS was prepared in compliance with EU Directive 91/155/EEC as amended by

2001/58/EC.

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

Issue date 16-Jan-2008

Material nameQ7561ASDS UKCreation date20-Oct-2005Version number35 / 6

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible exposure limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds