INFORMATION SECURITY

INTIMUS 130
IN THE DEPARTMENT

- Low noise level
- Integrated Auto Reverse Function
- Illuminated indicators

PROFESSIONAL DATA SHREDDERS

– a Synthesis of Technology, Performance and Design. All intimus® shredders are built from durable, precision engineered, high-performance components, designed for a long life of high volume usage. The product range covers all requirements from day-to-day office use up to High Security Shredding machines in use for destruction of classified material in line with all current legal requirements such as DIN 66399 or NSA 02/01. intimus® shredders carry various features which make them unique in user-friendliness and operating efficiency.

FEATURES

- Low noise level
- Integrated Auto Reverse Function for easy removal of paper jams
- Illuminated indicators for stand-by, basket full, door open and paper jam
- Sealed dust-free design with robust wooden cabinet
- Mounted on rollers for flexible use



CPNI. Centre for the Protection of National Infrastructure

130 CP5

Ecologic

I-control®

DLS

SPECIFICATION			
Model	**130 SP2**	**130 CP4**	**130 CP5**
Shred size	3,8 mm	3,8 x 36 mm	1,9 x 15 mm
Bin siz	130	130	130
Suitable for	10+	10+	10+
Security level (DIN 66 399)	P-2 / T-2[+]	P-4 / F-1/ T-4[+]	P-5 / F-2 / T-5[+]
Shredding capacity*	23-25 (sheets) 70 g/m² 20-22 (sheets) 80 g/m²	23-25 (sheets) 70 g/m² 20-22 (sheets) 80 g/m²	14-16 (sheets) 70 g/m² 11-13 (sheets) 80 g/m²
Cutting speed	0,14 m/s	0,14 m/s	0,14 m/s
Throughput** (sheets/min)	707 (sheets/min) 70 g/m² 622 (sheets/min) 80 g/m²	622 (sheets/min) 70 g/m² 537 (sheets/min) 80 g/m²	453 (sheets/min) 70 g/m² 368 (sheets/min) 80 g/m²
Also shreds			
Dimensions (W/D/H)	66 x 43 x 102 cm	66 x 43 x 102 cm	66 x 43 x 102 cm
Weight	60 kg	60 kg	60 kg

[+]only floppy disks / ID cards

* based on 70 g/m2 A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

** theoretical average performance paper/min