WG7550F

IDEAL FOR SMBs, THIS RAPID-PRINTING A3 COLOUR MFP INKJET PRINTER DELIVERS HIGH-YIELDS WITH LOWER COSTS





- Achieve a high printing yield with exceptional print speeds of up to 80ppm (300 dpi draft)
- Create seamless wireless LAN connections and print with smartphones or tablets via Mopria (Android), Apple AirPrint or the Canon PRINT Business mobile app
- Transfer scans to and print direct from a USB
- Take advantage of high-speed copying and scanning with ADF functionality, which produces a 2-sided scan in just one pass
- Deliver clear document transfers with the printer's high-speed fax capability
- Maximise office space and efficiency with the MFP's compact space-saving design
- Maintain with ease and print faster with the static FINE Line Head, which reduces the number of replacement parts
- Cut unnecessary down time with a maximum paper supply of 2,250 sheets (including optional cassette) and high-yield XL ink cartridges (20,000 pages with dedicated XL black ink and 16,500 pages with the XL colour ink)
- Reduce reliance on service teams fewer replacement parts and smooth and easy recovery from paper jams allow easy user maintenance
- Enjoy easy operation thanks to the 5-inch colour touchscreen with on-screen keyboard
- Reduce costs with lower power consumption just TEC 1.4kwh in sleep mode
- Work towards sustainability goals thanks to the printer's design a portion of recycled plastic is used in each one

With high-speed copy, print, scan and fax capabilities, this A3 printer is ideal for demanding of-fices. Few replaceable parts, lower power usage and higher-yield consumables cut running costs and simplify maintenance while a small footprint makes it the perfect fit for an office tight on space.



PRODUCT RANGE



WG7550Z



WG7550F



WG7550



TECHNICAL SPECIFICATIONS

PRINTER MAXIMUM PRINTING RESOLUTION	1200 x 1200dpi		
PRINT HEAD/ INK			
Type	Line Head w/FINE Technology		
Ink Tank	Black/Cyan/Magenta/Yellow		
Ink Tank Series (EUR)	PGI-7500		
Estimated Page Yield	XL = 20,000 pages BK		
	XL - 16,500 pages C/M/Y		
PRINT SPEED Document: Col, B/W ⁻¹ Simplex, General Mode (600dpi), Cassette 1	Up to 50ppm		
Document : Col, B/W ⁻² Simplex, Office Document Mode (300dpi), Cassette 1	Up to 80ppm		
Document : Col, B/W *1 Duplex, General Mode (600dpi), Cassette 1	Up to 25 ppm		
Document : Col, B/W ' ³ FPOT Ready/simplex, Cassette 1	Approx. 6.5 sec		
Document : Col, B/W *3 FPOT Sleep/simplex, Cassette 1	Approx. 12.5 sec		
MAXIMUM MEDIA SIZE (WXL)			
Default setting of Long Paper is OFF * This is supported by firmware 1.0 or 1.1	Cassette : 297 x 431.8 mm (11.7"x17") Multi-Purpose Tray: 330.2 mm x 482.6 mm (13"x19") '4		
SUPPORTED MEDIA SIZE	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal,		
* Depending on regions, custom size specification may be different. Please refer to "Maximum Media Size".	1x17, 12x18, SRA3, 13x19, K8, K16, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, FA4, FS(Indian Legal), 4x6" 5x7", 8x10", 10x12", 13x19", COM10, Monarch, ISO-C5, DL, Custom size (Up to 330.2mm x 711.2mm or 330.2 mm x 482.6 mm)		
PRINTING MARGIN			
Bordered Printing	Top, Bottom, Left, Right: 4mm each '5		
Bordered Auto Duplex Printing			
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 1:			
Thin Paper (52-63g/m²)			
Plain Paper (64-105g/m²)			
Thick Paper (106-220g/m²)	A5, A4, B5, Statement, Executive, Letter, K16, G-Letter		
Colored Paper (64-82g/m²)			
Recycled Paper (64-105g/m²)			
Bond Paper (83-99g/m²)			
Envelope (75-105g/m²)	COM10, Monarch, ISO-C5, DL		
Canon Matte Photo Paper	Not Available		
Label (118-185g/m²)	Not Available		
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 2, 3:			
Thin Paper (52-63g/m²)			
Plain Paper (64-105g/m²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal,		
Thick Paper (106-220g/m²)	11×17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio,		
Colored Paper (64-82g/m²)	A-Oficio, F4A, FS(Indian Legal)		
Recycled Paper (64-105g/m²) Bond Paper (83-99g/m²)			
Envelope (75-105g/m²)	Not Available		
Canon Matte Photo Paper	Not Available		
Label (118-185g/m²)	Not Available		
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 4:			
* Cassette 2 & 3 support thick paper (106-220g/m²) but cassette 4 supports 106-163g/m² only	15.44.47.05.04.61.4.5		
Thin Paper (52-63g/m²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11×17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter,		
Plain Paper (64-105g/m²)	G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio,		
Thick Paper (106-163g/m²)	A-Oficio, F4A, FS(Indian Legal)		
Colored Paper (64-82g/m²) Recycled Paper (64-105g/m²)			
Rond Paper (83-99a/m²)			
Bond Paper (83-99g/m²) Envelope (75-105g/m²)	Not Available		
	Not Available Not Available		

SUPPORTED MEDIA TYPE AND SIZE -MULTI-PURPOSE TRAY:			
Thin Paper (60-63g/m²) Plain Paper (64-105g/m²) Thick Paper (106-256g/m²) Colored Paper (64-82g/m²) Recycled Paper (64-105g/m²) Bond Paper (83-99g/m²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11×17, 12×18, SRA3, 13×19, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4×6		
Envelope (75-105g/m²) Canon Matte Photo Paper Label (118-185g/m²)	COM10, Monarch, ISO-C5, DL 4x6", 5x7", 8x10", 10x12", A4/LTR, A3, 13×19" A4, B4, Letter		
PAPER CASSETTE CAPACITY (80G/M²) Cassette 1, 2, 3, 4 Multi-Purpose Tray	550 sheets each 50 sheets		
MAXIMUM OUTPUT TRAY CAPACITY (80G/M²)	A3: 100 sheets, A4/LTR:250 sheets		
SUPPORTED MEDIA TYPE FOR DOUBLE SIDE PRINTING			
Туре	Thin Paper, Thick Paper, Plain Paper, Colored Paper, Recycled Paper, Bond Paper		
Size/Weight	A5 - 12x18", 52-220g/m²		
PRINT HEAD ALIGNMENT	Automatic Adjustment		
SCAN '6 SCANNER TYPE SCANNER SENSOR DUPLEX SCANNING OPTICAL RESOLUTION '7 SELECTABLE RESOLUTION '8	Flatbed & ADF CIS×2 sensors Available (Single Pass) 600 x 600 dpi 9600 x 9600 dpi		
SCANNING BIT DEPTH (INPUT/OUTPUT) Grayscale	10bit/8bit		
Color SCANNING SPEED '9 Document(ADF): Simplex Col Document(ADF): Simplex B/W Document(ADF): Duplex Col Document(ADF): Duplex B/W	30bit/24bit (RGB10bit/8bit each) Approx. 40 ipm Approx. 40 ipm Approx. 65 ipm Approx. 65 ipm		
MAXIMUM PAPER CAPACITY (80G/M²)	100 sheets		
MAXIMUM DOCUMENT SIZE Flatbed ADF	A3/11"x17" A3/11"x17"		
COPY MAXIMUM DOCUMENT SIZE SUPPORTED MEDIA SIZE	A3/11"x17" A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11×17, 12×18, SRA3, 13×19, K8, K16, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, F5 (Indian Legal), 4x6", 5x7", 8x10", 10x12", 13x19", COM10, Monarch, ISO-C5, DL, Custom size (Up to 330.2mm x 711.2mm or 330.2 mm x 482.6 mm x		
COPY EXPOSURE	9 Levels		
COPY SPEED *10 Document (A4/LTR) Canon Oiginal Method/ Simplex	50 ppm (Col, B/W)		
FIRST-COPY-OUT TIME '11 Document : Color sFCOT/Simplex	Approx. 5.8 sec		
MAGNIFICATION	25-400% (1% Increments)		
MULTIPLE COPY	Up to 999 copies		
FAX APPLICABLE LINE MODEM SPEED TRANSMISSION SPEED B/W Color COMPRESSION METHOD '12 B/W	PSTN (Public Switched Telephone Network) Super G3 (Up to 33.6kbps) / G3 (Up to 14.4Kbps) Approx. 3 sec/page (33.6kbps) Not Available MH,MR,MMR,JBIG		
GRADATION Black Color	Not Available 256 Levels Not Available		

WG7550F



WG7550F

MEDIA SIZE Sending Receiving FAX MEMORY "13 AUTOMATIC DIALING One-touch Dialing Coded Dialing Group Dialing SEND COMMUNICATION PROTOCOL MAXIMUM DOCUMENT SIZE ADDRESS BOOK SEND RESOLUTION FILE FORMAT Single Page Multi-Pages NETWORK	8dots/mm × 3.85 lines/mm (Standard) 8dots/mm × 7.7 lines/mm (Fine) 8dots/mm × 15.4 lines/mm (Super Fine) 16dots/mm × 15.4 lines/mm (Super Fine) 16dots/mm × 15.4 lines/mm (Ultra Fine) 11 x 17, LGL, LTR, A3, B4, A4, B5*3, A5*4 11 x 17, LGL, LTR, A3, B4, A4, B5, A5, 8K, and 16K Up to 512 pages Up to 19 (Best Member) Up to 281 Up to 199 FTP (TCP/IP), SMB (TCP/IP), SMTP (Same as Copy function) 300 addresses 204dpi x 196 dpi, 300dpi x 300dpi TIFF (MMR), PDF, JPEG TIFF (MMR), PDF	For Phone For Phone Line For Phone Line Finishing OPTIONS OPERATING ENVIRONMENT "IS RECOMMENDED OPERATING ENVIRONMENT "IS POWER POWER CONSUMPTION Copy/Print *16 Ready *16 Sleep *15 Off *16 Maximum Power Consumption TEC (TYPICAL ELECTRICITY CONSUMPTION) "IT ENVIRONMENTAL REGULATION DUTY CYCLE RECOMMNEDED MONTLY PRINTING VOLUME DIMENSION (WXDXH) Standard Configuration (WXDXH)	Available - Temperature; 5 to 35C (41 to 96F) Humidity: 20 to 90% RH (w/o condensation) Temperature; 15 to 30C (59 to 86F) Humidity: 20 to 85% RH (w/o condensation) AC 100-240V 50/60Hz Approx. 110W Approx. 55W Approx. 1.9W Approx. 0.1W Approx. 300W Approx. 1.25kWh/week Energy Star*, Blue Angel*, Eco Mark*, EPEAT* 'To be officially announced 100,000 pages 1,000 to 5,000 pages 560mm(W) x 590mm(D) x 880mm(H) 22.1"(W) x 23.3"(D) x 34.7"(H)
WIRED LAN Network Type Data Rate WIRELESS LAN	1000 Base-T/100Base-TX/10Base-T 1Gbps(1000Mbps)/100Mbps/10Mbps	With Optional Pedestal (WxDxH) Maximum Space (WxDxH)	588mm(W) x 590mm(D) x 1,133mm(H) 23.2"(W) x 23.3"(D) x 44.7"(H) 925mm(W)×1,208mm(D) x 1,487mm(H) 36.5"(W) x 47.6"(D) x 58.6"(H) ("ADF is opened to 60")
WIRELESS LAN Network Type Frequency Band Range Security	IEEE 802.11 b/g/n 2.4 GHz Indoor 50m ⁻¹⁴ Infrastructure Mode; 128 (104)/ 64 (40) bit WEP, WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES) Access Point Mode; WPA2-PSK (AES-CCMP)	WEIGHT (INC. PRINT HEAD) (OPTIONAL) CASSETTE FEEDING UNIT CF10 (CASSETTE 3, 4)	Approx. 82.1 kg (Approx. 180.2lb)
DIRECT CONNECTION (WIRELESS LAN)	Available	MEDIA SIZE MEDIA WEIGHT	Refer to "Supported Media Type and Size per Cassette 3, 4: " above.
OPERATING SYSTEM		MEDIA CAPACITY POWER	Supplied from Main Unit
SYSTEMS	Windows 7 - Starter / Home Basic / Home Premium / Professional / Enterprise / Ultimate Windows 8.1 - 8.1 / Pro / Enterprise Windows 10 - Home / Pro / Enterprise Windows Server 2008	S60mm x 590mm x 253 mm (WxDxH) 22.1"(W) x 23.3"(D) x 10.0"(H), Approx. 19kg, Approx. 41.2lb FOOTNOTES Print Speed is based on ISO/IEC 24734. Measured in default mode (General Mode: 600dpi) and calculated by Canon original methodology. Print Speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc. Print Speed is based on ISO/IEC 24734. Measured in fast mode (Office Document Mode: 300dpi) and calculated by Canon original methodology. Print Speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc. Print Speed (FPOT) is based on ISO/IEC17629. Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.	
	- Standard (x86/x64) / Enterprise Edition (x86/x64) / Datacenter (x86/x64) / Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 R2 Windows Server 2016 Mac: V10.16.0: OS10.8 to 10.13 (incompatible with 10.14) V10.17.0: OS10.8 to 10.14 (incompatible with 10.15)	document, print mode, medi Print Speed is based on ISO/ 300dpi) and calculated by C Print speed varies dependin document, print mode, medi Print Speed (FPOT) is based configuration, interface, soft and used cassette etc.	/IEC 24734. Measured in fast mode (Office Document Mode: anon original methodology. g on system configuration, interface, software, content of la type, weight and used cassette etc. on ISO/IEC17629. Print speed varies depending on system ware, content of document, print mode, media type, weight
PRINTING SOLUTIONS CANON PRINT BUSINESS CANON PRINT SERVICE MOPRIA APPLE AIR PRINT GOOGLE CLOUD PRINT NFC MEDIA DIRECT PRINT (USB MEMORY)	Datacenter (x86/x64) Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 Windows Server 2012 R2 Windows Server 2016 Mac: V10.16.0: OS10.8 to 10.13 (incompatible with 10.14) V10.17.0: OS10.8 to 10.14 (incompatible with 10.15) Available Available Available Available Available Available 14 Available NOT Available	document, print mode, medi Print Speed is based on ISO/ 300dpi) and calculated by C Print speed varies depending document, print mode, medi Print Speed (FPOT) is based configuration, interface, soft and used cassette etc. With Custom setting, casset 2, 3 and 4 supports 139,7 x 2 Depending on the driver soft TWAIN driver (ScanGear) is Optical Resolution is based a scanning the original. When scanning in high resol When scanning in high resol Average copy time from ADI scanning button to output the	/IEC 24734. Measured in fast mode (Office Document Mode: Janon original methodology. g on system configuration, interface, software, content of la type, weight and used cassette etc. Ion ISO/IEC17629. Print speed varies depending on system tware, content of document, print mode, media type, weight te 1 supports 90.0 x 190.0 mm to 216.0 x 297.0 mm. cassette 10.0 mm to 297.0 x 431.8 mm tware, this margin varies. based on TWAIN Specifications V 1.6. on ISO/IEC 14473. This is the maximum sampling rate when ution, scanning area size may be limited. F. Set the original on ADF and measure time from pushing the te copied paper. ton original Method. With Canon original chart, execute the te copy pages per minute.
CANON PRINT BUSINESS CANON PRINT SERVICE MOPRIA APPLE AIR PRINT GOOGLE CLOUD PRINT NFC MEDIA DIRECT PRINT	Datacenter (x86/x64) Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 Windows Server 2012 R2 Windows Server 2016 Mac: V10.16.0: OS10.8 to 10.13 (incompatible with 10.14) V10.17.0: OS10.8 to 10.14 (incompatible with 10.15) Available Available Available Available Available Available Available Available 14 Available 14	document, print mode, medi Print Speed is based on ISO/ 300dpi) and calculated by C Print speed varies depending document, print mode, medi Print Speed (FPOT) is based configuration, interface, soft and used cassette etc. With Custom setting, casset 2, 3 and 4 supports 133.7 x 2 Depending on the driver soft of	/IEC 24734. Measured in fast mode (Office Document Mode: canon original methodology. g on system configuration, interface, software, content of la type, weight and used cassette etc. on ISO/IEC17629. Print speed varies depending on system ware, content of document, print mode, media type, weight te 1 supports 90.0 x 190.0 mm to 216.0 x 297.0 mm. cassette 10.0 mm to 297.0 x 431.8 mm tware, this margin varies. based on TWAIN Specifications V 1.6. on ISO/IEC 14473. This is the maximum sampling rate when ution, scanning area size may be limited. F. Set the original on ADF and measure time from pushing the te copied paper. ton original Method. With Canon original chart, execute the te copy pages per minute. d on ISO/IEC 29183. ured in default mode with Canon original FAX testing chart, ing on content of document, receiving settings at the

Canon Inc. canon.com

Canon Europe

canon-europe.com

English edition © Canon Europa N.V.,2019

