WG7540

HIGH-SPEED, LOW MAINTENANCE A3 INKJET MFP FOR SMBs

Low-maintenance, economical A3 inkjet printer for SMBs. This compact MFP delivers fast prints of up to 70ppm and high-speed scans and copies using ADF, which produces a 2-sided scan in just one pass. With few replaceable parts, maintenance can be easily carried out by the user to keep down running costs.





- Maximise office space with an A3 colour MFP with a small space-saving footprint
- Keep efficiency high with fast print speeds of up to 70ppm (300 dpi draft)
- Deliver scans at high speed with ADF functionality, which produces 2-sided scans in just one pass
- Keep printing and copying with a maximum paper supply of 2,250 sheets (including optional cassette) and high-yield XL ink cartridges (20,000 pages with dedicated XL black ink and 16,500 pages with the colour XL ink)
- Reduce reliance on service teams fewer replacement parts and smooth and easy recovery from paper jams allow easy user maintenance
- Transfer scans to and print direct from a USB
- Get working straightaway with an intuitive 5-inch colour touchscreen with on-screen key-board
- Save money and reduce power consumption sleep mode uses just TEC 1.4kwh
- Enjoy fast prints with low maintenance. FINE Line Head technology includes a stationary print head, a non-replaceable part, which spans the entire page width for faster printing
- Produce professional documents with sharp black pigment ink
- Add to your business' sustainability thanks to the WG7540's partial use of recycled plastic



PRODUCT RANGE



WG7550F



WG7550



WG7540

Canon

TECHNICAL SPECIFICATIONS

PRINTER		Envelope (75-105g/m²)	Not Available
MAXIMUM PRINTING RESOLUTION	1200 x 1200dpi	Canon Matte Photo Paper	Not Available
PRINT HEAD/ INK		Label (118-185g/m²)	Not Available
Type	Line Head w/FINE Technology	SUPPORTED MEDIA TYPE AND SIZE	
Ink Tank	Black/Cyan/Magenta/Yellow	-MULTI-PURPOSE TRAY:	
Ink Tank Series (EUR)	PGI-7500	Thin Paper (60-63g/m²)	
Estimated Page Yield	XL = 20,000 pages BK XL - 16,500 pages C/M/Y	Plain Paper (64-105g/m²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal,
PRINT SPEED	· · · · · · · · · · · · · · · · · · ·	Thick Paper (106-256g/m²)	11×17, 12×18, SRA3, 13×19K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio,
Document : Col, B/W *1	Up to 40ppm	Colored Paper (64-82g/m²)	M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4×6
Simplex, General Mode (600dpi), Cassette 1		Recycled Paper (64-105g/m²) Bond Paper (83-99g/m²)	
Document : Col, B/W '2	Up to 70ppm	Envelope (75-105g/m²)	COM10, Monarch, ISO-C5, DL
Simplex, Office Document Mode (300dpi), Cassette 1	ор со торрии	Canon Matte Photo Paper	4x6", 5x7", 8x10", 10x12", A4/LTR, A3, 13×19"
·		Label (118-185g/m²)	A4, B4, Letter
Document : Col, B/W ¹¹ Duplex, General Mode	Up to 20 ppm	PAPER CASSETTE CAPACITY	
(600dpi), Cassette 1		(80G/M²)	550
Document : Col, B/W '3 FPOT Ready/simplex,	Approx. 6.5 sec	Cassette 1, 2, 3, 4 Multi-Purpose Tray	550 sheets 50 sheets
Cassette 1		MAXIMUM OUTPUT TRAY	A3: 100 sheets, A4/LTR:250 sheets
Document : Col, B/W *3 FPOT Sleep/simplex,	Approx. 12.5 sec/TBC	CAPACITY (80G/M²)	A3. 100 streets, A47 ETK.230 streets
Cassette 1		SUPPORTED MEDIA TYPE FOR DOUBLE SIDE PRINTING	
MAXIMUM MEDIA SIZE (WXL)		Type	Thin Paper, Thick Paper, Plain Paper, Colored Paper,
Default setting of Long Paper is OFF	Cassette : 297 x 431.8 mm (11.7"x17") Multi-Purpose Tray: 330.2 mm x 482.6 mm (13"x19") ¹⁴		Recycled Paper, Bond Paper
* This is supported by firmware 1.0 or 1.1		Size/Weight	A5 - 12x18", 52-220g/m²
SUPPORTED MEDIA SIZE * Depending on regions, custom size	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11×17, 12×18, SRA3, 13×19, K8, K16, Foolscap/Folio, Oficio,	PRINT HEAD ALIGNMENT	Automatic Adjustment
specification may be different. Please refer to "Maximum Media Size".	G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4x6".	SCAN '6	
	5x7", 8x10", 10x12", 13×19", COM10, Monarch, ISO-C5, DL, Custom size (Up to 330.2mm x 711.2mm or 330.2 mm x	SCANNER TYPE	Flatbed & ADF
	482.6 mm)	SCANNER SENSOR	CIS×2 sensors
PRINTING MARGIN		DUPLEX SCANNING	Available (Single Pass)
Bordered Printing	Top, Bottom, Left, Right: 4mm each *5	OPTICAL RESOLUTION '7 SELECTABLE RESOLUTION '8	600 x 600 dpi 9600 x 9600 dpi
Bordered Auto Duplex Printing		SCANNING BIT DEPTH	5555 X 5555 Gp.
SUPPORTED MEDIA TYPE		(INPUT/OUTPUT)	
AND SIZE PER CASSETTE		Grayscale	10bit/8bit
-CASSETTE 1:		Color	30bit/24bit (RGB10bit/8bit each)
Thin Paper (52-63g/m²) Plain Paper (64-105g/m²)		SCANNING SPEED '9	A 40 i
Thick Paper (106-220g/m²)		Document(ADF): Simplex Col Document(ADF): Simplex B/W	Approx. 40 ipm Approx. 40 ipm
Colored Paper (64-82g/m²)	A5, A4, B5, Statement, Executive, Letter, K16, G-Letter	Document(ADF) : Duplex Col	Approx. 65 ipm
Recycled Paper (64-105g/m²)		Document(ADF) : Duplex B/W	Approx. 65 ipm
Bond Paper (83-99g/m²)		MAXIMUM PAPER CAPACITY	100 sheets
Envelope (75-105g/m²)	COM10, Monarch, ISO-C5, DL	(80G/M²) MAXIMUM DOCUMENT SIZE	
Canon Matte Photo Paper Label (118-185g/m²)	Not Available Not Available	Flatbed	A3/11"x17"
	Not Available	ADF	A3/ 11"x17"
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 2, 3:			
		COPY	A 7 / 11"17"
Thin Paper (52-63g/m²) Plain Paper (64-105g/m²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal,	MAXIMUM DOCUMENT SIZE SUPPORTED MEDIA SIZE	A3/ 11"x17" A5, A4, A3, B5, B4, Statement , Executive, Letter, Legal,
Thick Paper (106-220g/m²)	11×17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter,	OKTED TIEDIN OILL	11×17, 12×18, SRA3, 13×19, K8, K16, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio,
Colored Paper (64-82g/m²)	G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal)		M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4x6",
Recycled Paper (64-105g/m²)			5x7", 8x10", 10x12", 13×19", COM10, Monarch, ISO-C5, DL, Custom size (Up to 330.2mm x 711.2mm or 330.2 mm x
Bond Paper (83-99g/m²)			482.6 mm)
Envelope (75-105g/m²) Canon Matte Photo Paper	Not Available Not Available	COPY EXPOSURE	9 Levels
Label (118-185g/m²)	Not Available Not Available	COPY SPEED *10	40ppm (Col, B/W)
SUPPORTED MEDIA TYPE		Document (A4/LTR) Canon Oiginal Method/	70ppiii (Cui, u/ vv)
AND SIZE PER CASSETTE -CASSETTE 4:		Simplex	
* Cassette 2 & 3 support thick paper		FIRST-COPY-OUT TIME *11	
(106-220g/m²) but cassette 4 supports 106-163g/m² only		Document : Color sFCOT/Simplex	Approx. 5.8 sec
This Dance (F2 C7=/2)		MAGNIFICATION	25-400% (1% Increments)
Thin Paper (52-63g/m²)			
Plain Paper (64-105g/m²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11×17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter,		· · · · · · · · · · · · · · · · · · ·
Plain Paper (64-105g/m²) Thick Paper (106-163g/m²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11×17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal)	MULTIPLE COPY	Up to 999 copies
Plain Paper (64-105g/m²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11×17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal)		· · · · · · · · · · · · · · · · · · ·



TECHNICAL SPECIFICATIONS

SEND	
COMMUNICATION PROTOCOL	FTP (TCP/IP), SMB (TCP/IP), SMTP
MAXIMUM DOCUMENT SIZE	(Same as Copy function)
ADDRESS BOOK	300 addresses
SEND RESOLUTION	204dpi x 196 dpi, 300dpi x 300dpi
FILE FORMAT	
Single Page	TIFF (MMR), PDF, JPEG
Multi-Pages	TIFF (MMR), PDF
NETWORK	
WIRED LAN	
Network Type	1000 Base-T/ 100Base-TX/ 10Base-T
Data Rate	1Gbps(1000Mbps)/100Mbps/10Mbps
WIRELESS LAN	Not Available
Network Type Frequency Band	Not Available Not Available
Range	Not Available
Security	Not Available
DIRECT CONNECTION	Not Available
(WIRELESS LAN)	
OPERATING SYSTEM	
Supported Operating	Windows:
Systems	Windows 7
	- Starter / Home Basic / Home Premium / Professional /
	Enterprise / Ultimate Windows 8.1
	- 8.1 / Pro / Enterprise
	Windows 10
	- Home / Pro / Enterprise
	Windows Server 2008
	- Standard (x86/x64) / Enterprise Edition (x86/x64) / Datacenter (x86/x64)
	Windows Server 2008 R2
	Windows Server 2012
	Windows Server 2012 R2
	Windows Server 2016
	Mac:
	V10.16.0: OS10.8 to 10.13 (incompatible with 10.14) V10.17.0: OS10.8 to 10.14 (incompatible with 10.15)
PRINTING SOLUTIONS	
CANON PRINT BUSINESS	Available
CANON PRINT SERVICE	Available
MOPRIA	Available
APPLE AIR PRINT	Available *14
GOOGLE CLOUD PRINT NFC	Available *14
	NOT Available
MEDIA DIRECT PRINT (USB MEMORY)	
Compatible Format	USB 2.0 compatible
File Format	JPEG/TIFF/PDF
OTHERS	
OPERATION PANEL	
Display	LCD (5.0 inch/TFT color)
	35 Languages Selectable: Japanese/English/ German/
Language	French/Italian/Spanish/Dutch/Portuguese/Norwegian/
Language	French/Italian/Spanish/Dutch/Portuguese/Norwegian/ Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovana/Turkish/Grapk/Simplifiad Chipses/
Language	Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/
Language	Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/
Language INTERFACE	Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/ Lithuanian/Romanian/Bulgarian/Croatian/Catalan/
	Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/ Lithuanian/Romanian/Bulgarian/Croatian/Catalan/ Arabic/Malay/Basque/Thai/Vietnamese
INTERFACE USB Port for USB Memory USB Port for PC	Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/ Lithuanian/Romanian/Bulgarian/Croatian/Catalan/ Arabic/Malay/Basque/Thai/Vietnamese
INTERFACE USB Port for USB Memory USB Port for PC For Phone	Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/ Lithuanian/Romanian/Bulgarian/Croatian/Catalan/ Arabic/Malay/Basque/Thai/Vietnamese USB 2.0 Hi-Speed USB 2.0 Hi-Speed Available
INTERFACE USB Port for USB Memory USB Port for PC For Phone For Phone Line	Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/ Lithuanian/Romanian/Bulgarian/Croatian/Catalan/ Arabic/Malay/Basque/Thai/Vietnamese
INTERFACE USB Port for USB Memory USB Port for PC For Phone	Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/ Lithuanian/Romanian/Bulgarian/Croatian/Catalan/ Arabic/Malay/Basque/Thai/Vietnamese USB 2.0 Hi-Speed USB 2.0 Hi-Speed Available

	T	
RECOMMENDED OPERATING ENVIRONMENT *15	Temperature; 15 to 30C (59 to 86F) Humidity: 20 to 85% RH (w/o condensation)	
POWER	AC 100-240V 50/60Hz	
POWER CONSUMPTION		
Copy/Print *16	Approx. 110W	
Ready *16	Approx. 55W	
Sleep *16	Approx. 1.9W	
Off *16	Approx. 0.1W	
Maximum Power Consumption	Approx. 300W	
TEC (TYPICAL ELECTRICITY CONSUMPTION) 17	Approx. 1.25kWh/week	
ENVIRONMENTAL	Energy Star*, Blue Angel*, Eco Mark*, EPEAT*	
REGULATION	*To be officially announced	
DUTY CYCLE	100,000 pages	
RECOMMNEDED MONTLY PRINTING VOLUME	1,000 to 5,000 pagess	
DIMENSION (WXDXH)		
Standard Configuration (WxDxH)	560mm(W) x 590mm(D) x 880mm(H) 22.1"(W) x 23.3"(D) x 34.7"(H)	
With Optional Pedestal (WxDxH)	588mm(W) x 590mm(D) x 1,133mm(H) 23.2"(W) x 23.3"(D) x 44.7"(H)	
Maximum Space (WxDxH)	925mm(W)×1,208mm(D) x 1,487mm(H) 36.5"(W) x 47.6"(D) x 58.6"(H) (*ADF is opened to 60°)	
WEIGHT (INC. PRINT HEAD)	Approx. 81.5kg (Approx. 179.1lb)	
(OPTIONAL) CASSETTE FEEDING UNIT CF10 (CASSETTE 3, 4)		
MEDIA SIZE	Refer to "Supported Media Type and Size per Cassette 3,	
MEDIA WEIGHT	4: " above.	
MEDIA CAPACITY		
POWER	Supplied from Main Unit	
DIMENSION/WEIGHT	560mm x 590mm x 253 mm (WxDxH) 22.1"(W) x 23.3"(D) x 10.0"(H), Approx. 19kg, Approx. 41.2lb	

- Print Speed is based on ISO/IEC 24734. Measured in default mode (General Mode: 600dpi) and calculated by Canon original methodology.
- Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.

 Print Speed is based on ISO/IEC 24734. Measured in fast mode (Office Document Mode: 300dpi) and calculated by Canon original methodology.
- Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.
- Print Speed (FPOT) is based on ISO/IEC17629. Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.
- With Custom setting, cassette 1 supports 90.0 x 190.0 mm to 216.0 x 297.0 mm. cassette 2, 3 and 4 supports 139.7 x 210.0 mm to 297.0 x 431.8 mm
- Depending on the driver software, this margin varies.
- TWAIN driver (ScanGear) is based on TWAIN Specifications V 1.6.
- Optical Resolution is based on ISO/IEC 14473. This is the maximum sampling rate when scanning the original.
- When scanning in high resolution, scanning area size may be limited.
- Average copy time from ADF. Set the original on ADF and measure time from pushing the scanning button to output the copied paper.
- Copy Speed is based on Canon original Method. With Canon original chart, execute the continuous copy and calculate copy pages per minute.

 First-Copy-Out Time is based on ISO/IEC 29183.
- Data transfer speed is measured in default mode with Canon original FAX testing chart. Actual speed varies depending on content of document, receiving settings at the destination, transfer line status and etc.
- Fax memory is measured with Canon orighinal FAX testing chart. This number varies depending on the available memory size, content of document and etc.
- Some early stage units may require firmware update to make Air Print available.
- Print quality might be lower depending on the operating environment.
- Reference value measured by Canon original method based on operation modes in International ENERGY STAR Program. Depending on your environment, this may vary.
- Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.

Specifications may be changed without notice.

Canon Inc. canon.com

Canon Europe

canon-europe.com

English edition © Canon Europa N.V.,2019

