# Vigor 2927 series

The Ideal VPN Router for Small Business and Remote Working



### **Product Overview**

The DrayTek Vigor 2927 series Dual-WAN Load Balancing Firewall VPN routers allow you to make the most of FTTP Fibre Broadband with Gigabit WAN throughput, extensive Firewall, Content Filtering, VPN client/server and Quality of Service controls.

Along with model options for fast WiFi and integrated 4G/LTE modem to take advantage of mobile broadband, the Vigor 2927 series provides a reliable, flexible, and secure network solution, that's ideal for Small Business and Home Offices.

# **Key Features & Benefits**

# **Dual Gigabit WAN Load Balancer**

Make full use of Fibre Broadband with the Vigor 2927's Gigabit throughput per-WAN. Up to 1.8Gbps total combined throughput with Firewall, Content Filtering and Quality of Service.

Benefits: Unleash the full potential of Fibre broadband. High speed, Gigabit CPE with flexible application.

## **Dual-SIM 4G+ LTE Modem**

Provide ultra-reliable connectivity with an integrated 4G+/LTE modem on 'L' models. Get the best out of 4G Broadband with LTE Category 6. Handle Mobile network outages with Dual-SIM Failover.

Benefits: High speed Mobile Broadband. Ensure constant connectivity.

## **Packed with Features**

Take advantage of DrayTek's rich feature set and useful functionality such as Quality of Service, Route Policy, Hotspot Web Portal, VPN Matcher, DrayDDNS and more.

Benefits: Advanced DrayTek router functionality.

# **Ideal VPN Router for SMB**

Provide fast and secure VPN access, with up to 50 VPN tunnels. Enabling remote workers to access network resources and connecting remote sites. With DrayTek SSL VPN and OpenVPN support.

**Dray** Tek

Benefits: Provide secure, encrypted network access for remote workers.

# 5+1 Gigabit LAN Ports

Attach Computers, Servers and Network Attached Storage directly, with up to 6 Gigabit LAN ports. Use VLANs to supply Broadband & VPN connectivity to as many as 8 separate networks.

Benefits: Improve quality of service for private and guest data traffic. Mix fixed and virtual configurations.

# **Designed for Centralised Management**

Configure and manage the Vigor 2927 series remotely through the VigorACS central management platform.

Benefits: Save time and money. Easily provision, monitor and manage remote sites without on-site IT or dedicated staff.



# Compatible with VigorACS Centralised Management Platform



# **Key Specification**

- Dual-WAN Gigabit Ethernet WAN Router with Load Balancing & Failover
- Up to 950Mbps Throughput per WAN interface, 1800Mbps in total
- Up to 300Mbps IPsec VPN Throughput
- 50 LAN-to-LAN & Remote Teleworker VPN Tunnels
- 25 DrayTek SSL VPN or OpenVPN Tunnels
- 4G/LTE with dual-SIMs for second backup telco ('L' models)
- AC1300 11ac 'Wave 2' Dual Band Wireless ('ac' models)
- 8 LAN Subnets with VLANs (Port-based / 802.1g)
- SPI Firewall and Content Filtering
- Optional VigorCare Available
- Compatible with VigorACS central management platform



# **Technical Specification (UK Hardware Spec.)**

#### **Physical Interfaces**

- WAN Ports: 1x Gigabit Ethernet (1G/100M/10M), RJ-45 LAN Ports: 5x Gigabit Ethernet (1G/100M/10M), RJ-45
- WAN/LAN Switchable Port: 1x Gigabit Ethernet (1G/100M/10M), RJ-45 2x USB 2.0 Ports for 3G/4G Modem, thermometer or Printer
- or 1x USB 2.0 Port ('L' models)
- 2x Removable Wireless antennas (wireless models) 2x Removable 4G/LTE Wireless antennas ('L' models) Wireless On / Off / WPS button
- **Recessed Factory Reset button**

#### Performance

- NAT Performance:
  - 950 Mb/s NAT Throughput for Single WAN with Hardware Acceleration
  - 1.8Gb/s Total NAT Throughput for Dual WAN with
  - Hardware Acceleration
  - 800 Mb/s NAT Throughput per WAN 60,000 NAT Sessions
- VPN Performance

  - 300 Mb/s IPsec (AES256) VPN Performance 800 Mb/s Hardware Accelerated IPsec VPN Performance
    - (requires f/w 4.2.1) 120 Mb/s SSL VPN Performance
  - Max. 50 Concurrent VPN Tunnels Max. 25 Concurrent SSL VPN / OpenVPN Tunnels

#### WAN Interfaces

- WAN1: Gigabit Ethernet
- WAN2: Gigabit Ethernet WAN3: 2.4GHz Wireless WAN ('ac' models)

- WAN4: 5GHz Wireless WAN ('ac' models) WAN5: 4G/LTE USB Modem (not included) or Integrated 4G/LTE Category 6 Modem ('L' models only) WAN6: 4G/LTE USB Modem (not included) Internet connection
- Load Balancing: IP-based, Session-based
- Hardware Acceleration

- 802.1p/q Multi-VLAN Tagging Multi-VLAN/PVC 2.4GHz & 5GHz Simultaneous Wireless WAN ('ac' models only) WAN Active on Demand: Link Failure, Traffic Threshold
- Connection Detection: PPP, ARP Detect, Ping Detect
- WAN Data Budget
- Dynamic DNS
- DrayDDNS with automated LetsEncrypt Certificates New!
- Full Feature-set Hardware Acceleration (requires f/w 4.2.1): Hardware Accelerated Quality of Service
  - Multi-WAN Data Budget
  - Traffic Graph & Data Flow Monitor
  - Bandwidth Limit

- IPv4 Connection Types: PPPoE, DHCP, Static IP, PPTP/L2TP
- IPv6 Connection Types:
  Ethernet: PPP, DHCPv6, Static IPv6, TSPC, AICCU, 6rd, 6in4 Static Tunnel
  - 4G/LTE Modem & USB 4G/LTE Modem: TSPC, AICCU

# Integrated 4G LTE Modem Features ('L' models) Dual-SIM Failover

- 4G LTE Category 6 Modem with fallback to 3G / GPRS
- Unlocked to any network (BT, EE, 3, 02, Vodafone, Eircom)
- 4G LTE Max Data Rates:
  - 300Mbps Downlink (Category 6)
  - 50Mbps Uplink (Category 6) 4G LTE (FDD) Bands: 1, 3, 5, 7, 8, 20, 28, 32 4G LTE (TDD) Bands: 38, 40, 41
- 3G (WCDMA/HSPA+/UMTS) Bands: 1, 3, 5, 8
- 2x LTE Antennas included with 1m extension cables
- Per-SIM-Card WAN Data Budget
- 2x Standard-Size SIM-Card Slots

- Removable SIM slot cover SMS Inbox Send & Receive SMS text messages SMS Router Commands Status Report, Reboot via text message LTE Bridge - New!

#### Wireless Features ('ac' models)

- AC1300 11ac (Wave 2' Dual Band Wireless ('ac' models):
  802.11ac 2x2 wireless access point
  Compatible with 802.11a/b/g/n wireless
  Dual-band (2.4/5Gh2) simultaneous wireless
  Use the 266/March Wireless

- Up to 866Mbps PHY rate at 80MHz with 5GHz
- Up to 400Mbps PHY rate at 40MHz with 2.4GHz Channel Bandwidth: 20/40MHz for 2.4GHz, 20/40/80MHz
  - for 5GHz MU-MIMO
- Tx Beamforming
- Mesh Root support with DrayTek VigorAP Mesh Nodes New! (requires f/w 4.2.2)
- Up to 4 SSIDs per radio band
- Extended 5Ghz Band Channels 36-48, 52-64, 100-140 Wireless Optimisation: Airtime Fairness, AP-Assisted Mobility,
- Band Steering
- Bandwidth Management (Per Station / Per SSID) WMM (Wireless MultiMedia)
- WPS WiFi Protected Setup
- Station Control Time limited wireless connectivity per Station
- (e.g. 1 hour) EAPOL Key Retry Disable EAPOL Key Retry to protect unpatched

# **Dray** Tek

# **Technical Specification (UK Hardware Spec.) (cont.)**

### Wireless Features ('ac' models) (cont.)

- Wireless Security: WPA2
- .
- WPA3 **New!** (requires f/w 4.2.2) Pre-Shared Key authentication Enterprise 802.1x authentication

- WEP/WPA for Legacy Clients Access Control Blacklist / Whitelist client MAC addresses per SSID

- Firewall & Content Filtering
  IP-based or User-based Firewall Policy
  User-based Time Quota
- DoS Attack Defence
- Spoofing Defence
- Content Filtering:
  - Application Content Filter
  - URL Content Filter DNS Keyword Filter Web Features

  - Web Category Filter (requires GlobalView subscription)

#### **NAT Features**

- NAT Port Redirection Open Ports
- Port Triggering DMZ Host
- UPnP
- ALG (Application Layer Gateway): SIP, RTSP, FTP, H.323 VPN Pass-Through: PPTP, L2TP, IPsec

#### **NAT Features**

- Auto Configuration
- NAT Port Redirection
- Open Ports
- Port Triggering DMZ Host
- UPnP
- ALG (Application Layer Gateway): SIP, RTSP, FTP, H.323 VPN Pass-Through: PPTP, L2TP, IPsec

#### LAN Management

- 802.1q Tag-based, Port-based VLAN Up to 8 LAN Subnets (NAT or Routing mode selectable per LAN
- interface) Up to 16 VLANs
- DMZ Port
- DHCP Server:
- Multiple IP Subnet
  - Custom DHCP Options
  - Bind-IP-to-MAC
  - DHCP Pool Count up to 1022 addresses for LANs 1-3 DHCP Pool Count up to 253 addresses for LANs 4-8
- LAN IP Alias
- Wired 802.1x Port Authentication
- Port Mirroring Local DNS Server
- Conditional DNS Forwarding
- Hotspot Web Portal
- Hotspot Authentication: Click-Through, Social Login, SMS PIN, Voucher

#### **Networking Features**

- Policy-based Routing: Protocol, IP Address, Port, Domain/ Hostname, Country
- High Availability: Active-Standby, Hot-Standby
- DNS Security (DNSSEC)

Specifications, content and product availability are subject to Full specifications are available at https://www.draytek.co.u

Local RADIUS server

- SMB File Sharing (Requires external storage) Multicast: IGMP Proxy, IGMP Snooping & Fast Leave, Bonjour Routing Features: IPv4 & IPv6 Static Routing, Inter-VLAN Routing, .

### VPN

- Up to 50 active VPN tunnels including up to 25 SSL VPN or **OpenVPN** Tunnels
- Up to 16 Hardware Accelerated 800Mb/s IPsec tunnels New! (requires f/w 4.2.1)
- LAN-to-LAN Dial-In VPN Server & Dial-Out VPN Client
- LAN-to-LAN Dial-In VPN Server & Dial-Out VPN Client Teleworker-to-LAN Dial-In VPN Server User Authentication: Local, RADIUS, LDAP, TACACS+, mOTP IKE Authentication: Pre-Shared Key and Digital Signature (X.509) Encryption: MPPE, DES, 3DES, AES (128/192/256) Authentication: SHA-256, SHA-1 VPN Trunk (Redundancy): Load Balancing, Failover Dead Peer Detection (DPD) IPsec NAT-Traversal (NAT-T) Virtual IP Mapping Resolve VPN IP subnet/range conflicts DHCP over IPsec

- DrayTek VPN Matcher Connect to a VPN router that's behind NAT/CG-NAT - New! VPN Protocols:

  - IPsec IKEv1, IKEv2, IKEv2 EAP
    - IPsec-XAuth DrayTek SSL VPN
  - OpenVPN
  - GRE over IPsec
  - PPTP
  - L2TP, L2TP over IPsec

### **Bandwidth Management**

- IP-based Bandwidth Limit
- IP-based Session Limit User-based Data Quota
- QoS (Quality of Service):
  - Classify via TOS, DSCP, 802.1p, IP Address, Service Type
  - 4 Priority Queues

  - App QoS VoIP Prioritization

### **Operating Requirements**

- Rack Mountable (Optional Vigor RM1 mounting bracket required)
- Wall Mountable
- Temperature Operating: 0 °C ~ 45 °C Storage: -25 °C ~ 70 °C Humidity 10% ~ 90% (non-condensing)
- Power Consumption:

Warranty : Two (2) Years RTB Power Requirements : 220-240VAC

- 24 watts ('ac' model)
  - Operating Power: DĆ 12V (via external PSU, supplied)

Screws & wall plugs for wall mounting 2m Cat-5e RJ-45 Network Cable 2x Detachable Wireless LAN Antennas ('ac' models)

2x Detachable LTE Antennas ('L' models) 2x 1m LTE Extension Base ('L' models DC 12V Power Supply with UK Plug

**Box Contents** 

ge and may differ from country to country. Actual Performance may vary depending on applications, usage, environment and other fact

- Dimensions: 241mm Width
- 165mm Depth • 44mm Height Weight: 630g (ac model)

Quick Start Guide

Vigor 2927 series router



### Vigor 2927 series Router Models

UK Product code	EAN	Product name	Product description
V2927-K	4710484741288	Vigor 2927 UK/IE	Vigor 2927 wired router
V2927AC-K	4710484741486	Vigor 2927ac UK/IE	Vigor 2927ac router with 11ac AC1300 wireless
V2927LAC-K	4710484742018	Vigor 2927Lac UK/IE	Vigor 2927Lac router with 11ac AC1300 wireless and integrated 4G/LTE modem



Email: info@draytek.co.uk Telephone: +44 345 5570 007 Specifications, content and product availability are subject to ct Full specifications are available at https://www.draytek.co.uk