

All fires, fast.

firexo

FIREXO 6LTR EXTINGUISHER

Name	Firexo 6LTR Extinguisher
Model/Product number	809-765-347-876
Capacity (litres)	6
Cylinder Height (mm)	497
Outer Width (mm)	170
Cylinder Material	Steel
Pressurizing Gas	Nitrogen
Test Pressure (bar)	30 bar
Working Pressure at 20 °C	12 bar
Weight Full (kg)	10.76
Weight Empty (kg)	3.5
Spray Range (m)	1 – 4
Discharge Time at 20 °C (seconds)	30 – 40
Temperature Range (°C)	-18 / +60
Warranty	5yr
Fire Rating	34A/113B/C/D/E/75F
CE Approval	CE 0036



ALL FIRES.



METHOD OF USE

In the event of a fire hold extinguisher upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side.

Discharge entire contents onto the fire from a 1m-3m distance.

Replace or recharge after use.

Tested on electrical to 35 kV.

© FIREXO 2020

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.

firexo

firexo.com