



Integrated Auto Reverse Function for easy removal of jammed paper. User friendly thanks to i-control® function control. Silentec®: innovative sound dampening principle and EcoLogic for more energy efficiency. DLS - Dynamic Load Sensor for long-term, trouble-free use.

i-control® Absolute transparency of the work flow

Silentec® Innovative concept for noise insulation

EcoLogic Energy efficiency

DLS Dynamic Load Sensor - controlled performance

- ✓ Dustproof enclosed cabinet
- ✓ Mounted on rollers for flexible use
- ✓ Material: shock resistant plastic, wood

Technical data

Cutting size paper (mm)	0,8 x 4,5 mm
Security level DIN 32757-1	6 / NSA
Shredding capacity 70 g/m ² :	5-6 sheets
Cutting speed 70 g/m ² (m/Sec.):	0,08 m/sec.
Cutting speed 70 g/m ² (sheets/Min.):	90 sheets/min.
Shredding capacity 80 g/m ² :	4-5 sheets
Cutting speed 80 g/m ² (m/Sec.):	0,08 m/sec.
Cutting speed 80 g/m ² (sheets/Min.):	73 sheets/min.
Working width (mm):	260 mm
DIN paper size:	A4
Catchbasket volume (l):	60 l
Catchbasket volume (sheets):	2430 sheets
Power consumption (kW):	0,7 kW
Supply voltage (Volt):	230 Volt
Weight gross (kg):	43 kg
Weight net (kg):	36 kg
Warranty on machine (years):	2 years
Warranty on the fracture of cutting cylinders:	2 years
Width (cm):	45 cm
Depth (cm):	39 cm
Height (cm):	77 cm
Type of packaging:	2 Boxes
Packaging dimensions (L/W/H):	55/49/32 & 55/49/66 cm
Packing unit:	1

Accessories

- 999 77 PE bags
- 880 35 Shredder oil for cross-cut shredder
- 801 80 Shredder oil for cross-cut shredders (re-fill)

www.intimus.com/index.php?intimus_crypto_60_CC6_en