# **TP-LINK®**

# AV600 Powerline Starter Kit

## TL-PA4010 KIT

#### • Features:

- Data transfer rate up to 600Mbps over electrical wires, ideal for HD video streaming
- · Nano Size with a total new exterior
- No new wires or drilling required, just using existing electrical wires
- No setup required, simply plug and play
- Up to 300 meters range over the household power circuit for better performance through walls or across floors
- Power-Saving Mode automatically reduces power consumptionby up to 85%\*
- 128-bit AES encryption easily at a push of "Pair" Button
- QoS provides networking flexibility and stable IPTV streaming and online gaming
- A wide range of plug type including EU, UK and US
- \* Actual data will vary because of the network conditions and environment factors.



### • Description:


TP-LINK's 600Mbps Powerline Starter Kit, TL-PA4010 KIT turns your existing Powerline into a high speed network with no need for new wire or drilling. No configuration required, simply plug your adapters into your power sockets and you can establish networking infrastructure in a flash. With a speed of up to 600Mbps, TL-PA4010 KIT is a great choice for an easy to build multimedia entertainment network.

## Specifications:

| Hardware Features       |   |
|-------------------------|---|
| Standards and Protocols | HomePlug AV, IEEE802.3, IEEE802.3u            |
| Interface               | 1* 10/100Mbps Ethernet Port                   |
| Plug Type               | UK  |
| Button                  | Pair Button                                   |
| LED Indicator           | PWR, PLC, ETH                                 |
| Dimensions (W x D x H)  | 2.6 x 2.0 x 1.1in. (65 × 52 × 28.5mm)         |
| Power Consumption       | < 2.0 W                                       |
| Range                   | 300M in house                                 |
| Software Features       |   |
| Modulation Technology   | OFDM  |
| Encryption              | 128-bit AES Encryption                        |
| Others                  |   |
| Certifications          | CE, FCC, RoHS                                 |
| System Requirements     | Windows 8/7/Vista/XP/2000, Mac, Linux*        |
| Environment             | Operating Temperature: 0°C~40°C (32°F~104°F)  |
|                         | Storage Temperature: -40°C~70°C (-40°F~158°F) |
|                         | Operating Humidity: 10%~90% non-condensing    |
|                         | Storage Humidity: 5%~90% non-condensing       |
|                         | J ,   |

<sup>\*</sup> Utility supports Windows 7/Vista/XP/2000 operating system for the present.

## • Diagram:



### Package:

- AV600 Powerline Adapter TL-PA4010 \*2
- 2-meter RJ-45 Ethernet Cable \*2
- Quick Installation Guide

<sup>\*</sup> Powerline adapters should be deployed on the same circuit and in set of two or more. The first, connected to the router and others located elsewhere to enable connectivity in those locations.