

Data Sheet

4 Port VGA Video Audio Switch with RS232 control

Product ID: VS410RVGAA



The VS410RVGAA 4 Port VGA Video Audio Switch with RS232 control lets you switch between four separate VGA signals, as well as the corresponding audio, for output to a single display or projector at resolutions up to 1920x1200 (PC) or 1080p (HDTV).

An ideal solution for situations where VGA and audio input ports are scarce, the VGA switch eliminates the hassle of having to swap out connections to your display and audio receiver, while letting you select the video source quickly and easily at the push of a button.

The VGA switch also features convenient remote switching capabilities through either RS232 serial remote control, or the included IR remote control - allowing you to switch between VGA input signals from a distance and in turn providing a convenient addition to presentation displays, trade shows, security environments and more.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.



Data Sheet

Certifications, Reports and Compatibility











Applications

- Perfect for use in boardroom settings to let visitors connect to your display or projector
- Great for use in presentations, trade shows, conferences, retail, and entertainment applications
- Excellent solution for connecting and switching between multiple PC/HDTV's to one display

Features

- Supports resolutions up to 1920x1200 (1080p)
- Supports VGA Video bandwidth of 650 MHz
- Includes an easy-to-use remote control for easy switching between devices
- RS232 interface provides you with remote/off-site control
- Front panel push-buttons
- 3.5mm audio connections



Hard-to-find made easy*

Data Sheet

	Warranty	2 Years
Hardware	Audio	Yes
	AV Input	3.5 mm Audio
		VGA
	AV Output	3.5 mm Audio
		VGA
	Ports	4
Performance	Bandwidth	650 MHz (-3dB) max
	Maximum Analog Resolutions	1920x1200 (PC), and 1080p (HDTV)
Connector(s)	Connector A	4 - 3.5 mm Mini-Jack (3 Position) Female
		4 - VGA (15 pin, High Density D-Sub) Female
	Connector B	1 - 3.5 mm Mini-Jack (3 Position) Female
		1 - VGA (15 pin, High Density D-Sub) Female
Power	Center Tip Polarity	Positive
	Input Current	0.6A
	Input Voltage	110V-240V AC
	Output Current	2.6A
	Output Voltage	5 DC
	Power Consumption (In Watts)	5
	Power Source	AC Adapter Included
Physical Characteristics	Color	Black
	Enclosure Type	Aluminum
	Product Height	40 mm [1.6 in]
	Product Length	165 mm [6.5 in]
	Product Weight	1.5 kg [3.3 lb]
	Product Width	287 mm [11.3 in]
Packaging Information	Shipping (Package) Weight	2.1 kg [4.7 lb]
What's in the Box	Included in Package	1 - IR Remote Control
		1 - 4x1 VGA Switch
		1 - 3ft. VGA Cable



Data Sheet

1 - Universal Power Adapter (US/UK/EU/AU)

Product appearance and specifications are subject to change without notice.