

Serial DB9 RS232 Extender over Cat 5 - Up to 3300 ft (1000 meters)

Product ID: RS232EXTC1GB



The RS232EXTC1GB Serial over Cat 5 Extender allows you to increase the distance of your RS232 Serial connection by up to 1000 meters (3300 feet), giving you the ability to connect serial peripheral devices up to a kilometer away from your system - an incredible 65x greater than normal RS232 serial cable length restrictions would permit.

The Extender is a cost-effective serial extension solution and completely hardware-based, eliminating the need to install additional software, allowing for a completely plug and play installation. The hardware can be setup in minutes, using existing or new Cat 5 or better Ethernet cabling.

Perfect for use in industrial monitoring and control, POS, security, medical, and traffic flow applications, the RS232 Serial over Cat 5 extender maintains the RS232 standard with support for data transfer rates of up to 230 Kbps.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Industrial applications include controlling CNC machinery, polling bar code scanner data, administering process control equipment, weigh stations, and other manufacturing applications
- Monitor and control medical equipment, security keypads/card scanners, point of sale equipment and remote sensor data, and various other healthcare related serial communications
- Extend connectivity to Point of Sale card swipe devices, bar code scanners, scales, receipt printers or cash register displays
- Remotely poll data from access keypads, card scanners, camera installations or home security systems
- Remote sensor monitoring for traffic flow management (air traffic control, expressway flow)

Features

- Extend RS232 up to 1000m / 3300ft
- Data transfer rates of up to 230 Kbps
- Compatible with all RS232 communications
- Employ existing Cat5, 5e, 6 or better Ethernet infrastructure to remotely connect serial devices
- Supports full-duplex data communication
- Compact design
- No driver software required for easy Plug-and-Play installation

Hardware	Warranty	2 Years
	Cabling	Cat 5 UTP
	Ports	1
Performance	Maximum Data Transfer Rate	115.2Kbps
Connector(s)	Local Unit Connectors	1 - DB-9 (9 pin, D-Sub) Female
		1 - RJ-45 Female
	Remote Unit Connectors	1 - DB-9 (9 pin, D-Sub) Male
		1 - RJ-45 Female
Software	OS Compatibility	OS independent
Special Notes / Requirements	System and Cable Requirements	Cat5 RJ45 cabling required
Power	Center Tip Polarity	Positive
	Input Current	55mA
	Input Voltage	240V AC
	Output Current	0.3A
	Output Voltage	9 DC
	Plug Type	M
	Power Consumption (In Watts)	2.7
	Power Source	2 AC Adapters Included
Environmental	Humidity	0% to 95%
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	0°C to 85°C (32°F to 185°F)
Physical Characteristics	Color	Silver
	Enclosure Type	Steel
	Product Height	22 mm [0.9 in]
	Product Length	92 mm [3.6 in]
	Product Weight	65 g [2.3 oz]
	Product Width	34 mm [1.3 in]
Packaging Information	Shipping (Package) Weight	1 kg [2.2 lb]
What's in the Box	Included in Package	1 - RS232 Extender Local Unit
		1 - RS232 Extender Remote Unit

- 1 - 20cm Null Modem cable (DB-9 Male to Male)
- 2 - Power Adapter
- 1 - User Manual

Product appearance and specifications are subject to change without notice.