

3 m (10 ft.) USB-C to HDMI Cable - 4K at 60Hz - Black

Product ID: CDP2HD3MBNL



This USB-CTM to HDMI® adapter cable offers a convenient solution for directly connecting your DisplayPort over USB Type-CTM device to your HDMI monitor, television, or projector. The adapter offers a connection distance of up to 3 m (10 ft.) and works with USB-C devices that support DP Alt Mode, such as the MacBook, Chromebook PixelTM and DellTM XPSTM models 15 and 13. It's also compatible with ThunderboltTM 3 ports.

Clutter-free installation

At 3 m (10 ft.) in length, this adapter cable delivers a direct connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation.

For shorter installations, StarTech.com also offers a 1 m (3 ft.) USB-C to HDMI cable (CDP2HD1MBNL) and 2 m (6 ft.) USB-C to HDMI cable (CDP2HD2MBNL), enabling you to choose the right cable length for your custom installation needs.





Astonishing picture quality

At four times the resolution of high-definition 1080p, you'll be amazed at the picture quality of a 4K 60Hz monitor or television. This adapter cable lets you harness the video capabilities that are built into your USB Type-C connection, to deliver the astonishing quality of Ultra HD to your 4K display.

Plus, the adapter is still compatible with lower display resolutions, such as 1080p, which makes it a great accessory for your current home, office or other HD work environment, while future-proofing for 4K 60Hz implementation.

The CDP2HD3MBNL is backed by a 2-year StarTech.com warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Connect a USB Type-C computer to an HDMI projector or display in your classroom, auditorium or boardroom
- Install at your home workstation or office hot desk to make your USB-C computer compatible with your HDMI display

Features

- Position your devices as needed throughout your workspace, with reduced cable clutter
- 3 m (10 ft.) all-in-one solution with a combined cable and adapter
- Hassle-free connection with the reversible USB-C connector
- Astonishing video quality with support for resolutions up to 4K at 60Hz



Data Sheet

	Warranty	2 Years
Hardware	Adapter Style	Cable Adapters
	AV Input	USB Type-C
	AV Output	HDMI
	Chipset ID	VIA/VLI - VL100 Parade - PS176
	Ports	1
Performance	Audio Specifications	7.1 surround sound
	Maximum Digital Resolutions	3840x2160 @ 60 Hz
	Supported Resolutions	1024×768 1280×720 (High-definition 720p) 1920×1080 (High-definition 1080p) 1920×1200 2560×1440 2560×1600 3840×2160 (Ultra HD 4K)
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
	Connector B	1 - HDMI (19 pin) Male Output
Special Notes / Requirements	Connector B Note	1 - HDMI (19 pin) Male Output Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
_		Your USB-C port must support DisplayPort over USB-C (DP
Requirements	Note	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
Requirements	Note Humidity	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation)
Requirements	Note Humidity Operating Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F)
Requirements Environmental Physical	Note Humidity Operating Temperature Storage Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F)
Requirements Environmental Physical	Note Humidity Operating Temperature Storage Temperature Cable Length	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3 m [9.8 ft]
Requirements Environmental Physical	Note Humidity Operating Temperature Storage Temperature Cable Length Color	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3 m [9.8 ft] Black
Requirements Environmental Physical	Note Humidity Operating Temperature Storage Temperature Cable Length Color Product Height	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3 m [9.8 ft] Black 12 mm [0.5 in]
Requirements Environmental Physical	Note Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3 m [9.8 ft] Black 12 mm [0.5 in] 3000 mm [118.1 in]
Requirements Environmental Physical	Note Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Weight	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3 m [9.8 ft] Black 12 mm [0.5 in] 3000 mm [118.1 in] 80 g [2.8 oz]
Requirements Environmental Physical Characteristics Packaging	Note Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Weight Product Width	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3 m [9.8 ft] Black 12 mm [0.5 in] 3000 mm [118.1 in] 80 g [2.8 oz] 20 mm [0.8 in]

Product appearance and specifications are subject to change without notice.