

The Perfect Balance of Superb Performance, Compelling Features, and Compact Form Factor.

The Quadro P2000 is the perfect balance of performance, compelling features, and compact form factor delivering incredible creative experience and productivity across a variety of professional 3D applications. It features a Pascal GPU with 1024 CUDA cores, large 5 GB GDDR5 on-board memory, and the power to drive up to four 5K (5120x2880 @ 60Hz) displays natively. This makes it an excellent choice for accelerating product development and content creation workflows that demand fluid interactivity with large, complex 3D models and scenes.

Quadro cards are certified with a broad range of sophisticated professional applications, tested by leading workstation manufacturers, and backed by a global team of support specialists. This gives you the peace of mind to focus on doing your best work. Whether you're developing revolutionary products or telling spectacularly vivid visual stories, Quadro gives you the performance to do it brilliantly.

THE PNY ADVANTAGE

PNY provides unsurpassed service and commitment to its professional graphics customers. In addition, PNY delivers a complete solution including the appropriate adapters, cables, brackets, driver software installation disc and documentation to ensure a quick and successful install.

FEATURES

- > Four DisplayPort 1.4 Connectors1
- DisplayPort with Audio
- > NVIDIÁ nView™ Desktop Management Software
- > HDCP 2.2 Support
- > NVIDIA Mosaic²
- > NVIDIA Iray and MentalRay Support

PACKAGE CONTENTS

- > NVIDIA® Quadro® P2000 Professional Graphics Board
- Software Installation Disc.
- > Printed Quick Start Guide
- Four DisplayPort to DVI SL Adapter

WARRANTY AND SUPPORT

- > 3-Year Warranty
- > Pre- and Post-Sales
- Technical Support
- > Dedicated Field Application Engineers
- > Direct Tech Support Hot Lines



PNY PART NUMBER	VCQP2000-PB
SPECIFICATIONS	
GPU Memory	5 GB GDDR5
Memory Interface	160-bit
Memory Bandwidth	Up to 140 GB/s
NVIDIA CUDA® Cores	1024
System Interface	PCI Express 3.0 x16
Max Power Consumption	75 W
Thermal Solution	Active
Form Factor	4.4" H x 7.9" L, Single Slot
Display Connectors	4x DP 1.4
Max Simultaneous Displays	4 direct, 4 DP 1.4 Multi-Stream
Display Resolution	4x 4096x2160 @ 120Hz 4x 5120x2880 @ 60Hz
Graphics APIs	Shader Model 5.1, OpenGL 4.5³, DirectX 12.0⁴, Vulkan 1.0³
Compute APIs	CUDA, DirectCompute, OpenCL™

^{© 2017} NVIDIA Corporation and PNY. All rights reserved. NVIDIA, the NVIDIA logo, Quadro, nView, CUDA, NVIDIA Pascal, and 3D Vision are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. The PNY logotype is a registered trademark of PNY Technologies. OpenCL is a trademark of Apple Inc. used under license to the Khronos Group Inc. All Other trademarks and copyrights are the property of their respective owners. FEB17



VGA/DVI/HDMI support via adapter/connector | 2 Windows 7, 8, 8.1, 10 | ³ Product is based on a published Khronos Specification and is expected to pass the Khronos Conformance Testing Process when available. Current conformanc status can be found at www.khronos. org/conformance | ⁴ GPU supports DX 12 API Hardware Feature Level 12_1