

S334e

Bright projection









- Bright SVGA projector 3800 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project bright vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the S334e boasts amazing colour, long lamp life and energy-saving features to provide you with a low overall cost of ownership.



Specifications

Display/image Display technology DIP

Resolution SVGA (800x600) Brightness 3,800 lumens Contrast ratio 22,000:1 Native aspect ratio 4:3 Aspect ratio - compatible 16:9 Keystone correction -+/-40°

vertical

Horizontal scan rate 15.38 ~ 91.15Khz Vertical scan rate 50 ~ 85(120 for 3D)Hz

Uniformity 75%

0.71m ~ 7.73m (27.78" ~ 304.4") (diagonal) Screen size

Lamp info Light source type Lamp Lamp watts 203

Lamp life (hours) 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

Optical

1.94:1 - 2.16:1 Throw ratio Projection distance (m) 1m - 12m Zoom 1.1 Zoom type Manual Focal length (mm) 21.85 ~ 24 Native offset

Connectivity

Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A

General

Noise level (typical)

FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,

4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages

Arabic, Ozech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian,

(simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Remote control Card style Speaker count Watts per speaker 10W AC power cord In the box Remote control

Battery Basic user manual

Power Power supply 100 ~ 240V, 50 ~ 60Hz

Power consumption 0.5W

(standby)

Power consumption (min) 187W Power consumption (max) 225W

Weight and dimensions

Net weight 3kg

Dimensions (W x D x H) 316 x 244 x 108 mm



