optomaeurope.com



WU334 High resolution, versatile and powerful



- Bright WUXGA projector 3600 ANSI lumens
- Easy connectivity 2x HDMI, MHL, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Beam bright, eye catching content with the high definition, WUXGA WU334 projector. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts easy connectivity with multiple inputs including two HDMI, MHL, VGA and a built in 10W speaker. You can even use the USB Power to connect and power HDMI dongles such as the Google Chromecast.



Specifications

		_
Display/image		
Display technology	DLP	
Resolution	WUXGA (1920x1200)	(D) (reese)
Brightness	3,600 lumens	
Contrast ratio	20,000:1	
Native aspect ratio	16:10	
Aspect ratio - compatible	4:3,16:9	
Keystone correction - vertical	+/-40°	(100) (200)
Horizontal scan rate	15.38 ~ 91.15Khz	
Vertical scan rate	50 ~ 85(120 for 3D)Hz	Optomo
Uniformity	70%	
Screen size	0.74m ~ 7.62m (29" ~ 300") (diagonal)	
Lamp info		-
Light source type	Lamp	
Lamp watts	240	
Lamp life (hours)	3500 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)	
Optical		
Throw ratio	1.47:1 - 1.62:1	
Projection distance (m)	1m - 9.5m	
Zoom	1.1	
Zoom type	Manual	
Focal length (mm)	15.59 ~ 17.14	
Native offset	110%	
Connectivity		-
Connections	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232	
General		-
Noise level (typical)	27dB	
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac	
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,	
2D compatibility	11100 W/0, 0.000 III 2, 4.400 II 2 / 12 D/0/17/0/10/10/10	
	4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)	
3D compatibility	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:	
	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60	
3D	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D	
3D Security	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface	
3D Security	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages:	ian,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Germ (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese	ıan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gern (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m	an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Germ (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese	an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
Operating conditions Remote control Speaker count	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gern (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1	an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Germ (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W	an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gern (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1	an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Germ (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord, remote control, Battery, basic user manual	ıan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Germ (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W	ıan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (standby)	 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Germ (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 	an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Power Power Power consumption (standby) Power consumption (min)	 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, Gern (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 205W 	an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power consumption (standby) Power consumption (min) Power consumption (max)	 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Germ (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 	nan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar,Kensington Lock,Password protected interface 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Germ (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 205W 295W 	an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,
3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power consumption (standby) Power consumption (min) Power consumption (max)	 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, Gern (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 205W 	ıan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,

Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 03052019120008