

## EH345

Full HD 1080p, bright and powerful









- Bright 1080p projector 3200 ANSI lumens
- Installation flexibility 1.3x zoom
- Amazing colour Accurate sRGB colour space
- Easy connectivity HDMI, VGA, USB Power, 10W speaker

Make your presentations count regardless of the ambient light level using the Full HD 1080p EH345. Designed for education and business environments this powerful projector is perfect for installation. It is also has long lamp life and energy-saving features to provide you with a low overall cost of ownership.

Easy to connect to with multiple inputs including two HDMI, MHL, VGA and a built-in 10W speaker. You can even present wirelessly using the HDCast Pro (sold separately) or use the USB Power to connect and power HDMI dongles such as the Google Chromecast.



## **Specifications**

Display/image Display technology

Resolution 1080p Full HD (1920x1080)

Brightness 3,200 lumens Contrast ratio 22,000:1 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Keystone correction -+/-40°

vertical

Horizontal scan rate 15.3 ~ 91.1Khz Vertical scan rate 24 ~ 85(120 for 3D)Hz

75% 1.01m ~ 7.62m (39.92" ~ 299.81") (diagonal) Screen size

DIP

Lamp info Light source type Lamp Lamp watts 195

Lamp life (hours) 5000 (Bright), 7000 (Dynamic), 6000 (Eco), 8000 (Eco+),

10000 (Education) 10,000 hours

Lamp life (education)

Ontical 1.13:1 - 1.47:1 Throw ratio Projection distance (m) 1.3m - 9.76m Zoom 1.3 Zoom type Manual Focal length (mm) 16.91 ~ 21.6 116%

Native offset Connectivity

Uniformity

Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB),

1 x Composite video, 1 x Audio 3.5mm, 1 x HDMI 1.4a 3D

support + MHL

Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x

USB-A power 1A Control 1 x RS232

General

3D compatibility

Noise level (typical) 29dB

WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, PC compatibility

Mac

NTSC M/J. 3.58MHz. 4.43MHz PAL B/D/G/H/I/M/N. 2D compatibility

4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

25 language OSD / display languages

Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Polish, Portuguese, Romanian, Arabio, Czech, Polish, Pol

(simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Remote control Data remote with laser and mouse function

Speaker count Watts per speaker 10W AC power cord In the box Remote control 2x AAA batteries Basic user manual

Power Power supply 100 ~ 240V, 50 ~ 60Hz

Power consumption 0.5W (standby)

Power consumption (min) 192W Power consumption (max) 232W

Weight and dimensions

2.47kg Net weight Dimensions (W x D x H) 298 x 230 x 96

mm



