MultiSync® EA245WMi-2 LCD 24" Commercial Display

Datasheet





NEC MultiSync® EA245WMi-2 Ultra-Thin Bezel - The Office benchmark, combining sleek and elegant design with health-conscious performance

The 24" ultra-thin bezel display targeting ultimate office productivity, performance and quality, fulfils the demand for future-ready design. With its full height adjustability from 0 to 150 mm and 170° swivel functionality this display ensures perfect individual ergonomic set-up supporting best productivity. Ensuring the well-being of the user, built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates the effect of flickering. The users' eyes are protected whilst ensuring a true-to-life display colour performance from all viewing angles. The LED backlight panel with AH-IPS technology supports a high display brightness of 300 cd/m² and in parallel lowers power consumption.

The ultra-narrow bezel display reduces the display footprint without compromising on screen size and gives an office a fresh professional interior with its sleek and elegant design.

Benefits

Ergonomic Office – full height adjustability (150 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Protecting your eyes from strain and damage – Built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, thus protecting your eyes against cataracts and macular degeneration without compromise to true-to-life display colour performance.

Highest Productivity and efficient Multi-Tasking – reduce the number of PCs and Daisy-Chain multiple displays using DisplayPort (out) and benefit from Uniformity Control for a consistent visualisation in a trading floor setup.

Auto-Adjust Power Consumption – to minimize unnecessary power usage, the Human and Ambient Light Sensors adjust the display brightness according to user presence and room lighting conditions.

Future-Ready Design – best in form and function design with 3-sided ultra-narrow bezel gives an office a fresh professional interior.

Business Class Image Quality – Advanced High-Performance IPS (AH-IPS) panel provides the very best viewing angles as well as noticeably better colour reproduction.

Product Information

Product Name	MultiSync® EA245WMi-2	
Product Group	LCD 24" Commercial Display	
Order Code	60004486 (BK), 60004488 (WH)	

Display

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	24 / 61
Screen Aspect Ratio	16:10
Pixel Pitch [mm]	0.270
Brightness (typ.) [cd/m²]	300
Contrast Ratio (typ.)	1000:1 (5000:1 dynamic contrast ratio)
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	5
Colours [Mio.]	16.77

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 95
Vertical Frequency [Hz]	56 - 75

Resolution

Optimum Resolution	1920 x 1200 at 60 Hz			
Supported	1920 x 1200;	1440 x 900;	1280 x 1024;	1024 x 768;
	1920 x 1080;	1400 x 1050;	1280 x 960;	800 x 600;
	1680 x 1050;	1366 x 768;	1280 x 768;	640 x 480
	1600 x 1200;	1360 x 768;	1280 x 720;	

Connectivity

Digital	1 x DisplayPort; 1 x DisplayPort out; 1 x DVI-D; 1 x HDMI; USB ver. 3.0 (3 down / 1 up)
Analog	1 x D-sub 15 pin

Electrical

Power Consumption on Mode [W]	18 (Eco Mode 2); 22 (typ.); 50 (max.)
Power Savings Mode [W]	0.3
Power Supply	internal power supply

Environmental Conditions

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80

Ergonomics

Height adjustable stand [mm]	150
Screen Tilt / Swivel [°]	-5 to +35; -170 to +170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

Mechanical

Bezel Width [mm]	0.8 (left/right/top)
Dimensions (W x H x D) [mm]	With stand: 531.5 x 515.4 x 250

Weight [kg]	6.7	
VESA Mounting [mm]	100 x 100	
Additional Features		
Special Characteristics	Ambient light sensor for optimized brightness levels; Carbon Footprint Meter; Carbon Savings Meter; ControlSync $^{\otimes}$; Customize Setting; DICOM preset; DICOM Simulation; EcoModes; Human Sensor; LED Backlight Technology; NaViSet Administrator 2; Quick release Stand and Handle; sRGB Support; Touch Sensor Keys; USB ver. 3.0 (3 down / 1 up)	
Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet	
Cable Management	yes	
Kensington security slot	yes	
Plug and Play	VESA DDC2B; VESA DDCi	
Audio	Headphone Jack; Integrated Speakers (1 W + 1 W)	
Adjust Functions	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; One Touch Recovery; Power-Off Timer; sRG	
Shipping Content	Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Setup Guide; USB Cable	
Safety and Ergonomics	CE; EnergyStar 7.0; Flicker-free; Low Blue Light; TCO 7.0	
Warranty	3 years warranty incl. backlight; optional 4th to 5th year warranty extension	
Green Features		
Energy Efficiency	Ambient light sensor; Annual energy consumption: 31 kWh (based on 4 operating hours per day); Energy efficiency class: A+; Human sensor; Intelligent Power Management	



Ecological Materials

Ecological Standards

This document is $\ensuremath{\text{@}}$ 2019 NEC Display Solutions Europe GmbH.

Downloadable manuals

Energy Star 7.0; TCO 7.0

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 15.04.2019