\Orchestrating a brighter world

MultiSync[®] EA245WMi LCD 24" Commercial Display

Datasheet





NEC MultiSync® EA245WMi-SV2 Ultra-Thin Bezel - The Office benchmark, combining sleek and elegant design with health-conscious performance

The 24" ultra-thin bezel display targeting ultimate office productivity, performance and quality, fulfils demand for future-ready design. Outstanding productivity requires high attention to healthcare. Ensuring the well-being of the user, built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates the effect of flickering. The users' eyes are protected whilst ensuring a true-to-life display colour performance from all viewing angles. The LED backlight panel with AH-IPS technology supports a high display brightness of 300 cd/m² and in parallel lowers power consumption.

The ultra-narrow bezel display reduces the display footprint without compromising on screen size and gives an office a fresh professional interior with its sleek and elegant design.

Benefits

Future-Ready Design - best in form and function design with 3-sided 0.8 mm ultra-thin bezel gives an office a fresh professional interior.

Protecting your eyes from strain and damage – Built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, thus protecting your eyes against cataracts and macular degeneration without compromise to true-to-life display colour performance.

Highest Productivity and efficient Multi-Tasking – reduce the number of PCs and Daisy-Chain multiple displays using DisplayPort (out) and benefit from Uniformity Control for a consistent visualisation in a trading floor setup.

Ergonomic Office - full height adjustability (100 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Auto-Adjust Power Consumption – to minimize unnecessary power, Human and Ambient Light Sensor adjusts the display brightness when a user leaves his desk.

Business Class Image Quality – Advanced High-Performance IPS (AH-IPS) panel provides the very best viewing angles as well as noticeably better colour reproduction.

Product Information

Product Name	MultiSync [®] EA245WMi
Product Group	LCD 24" Commercial Display
Order Code	60003811 (BK), 60003812 (WH)

Display

Panel TechnologyIPS TFT with W-LED backlightScreen Size [inch/cm]24 / 61Screen Aspect Ratio16:10Pixel Pitch [mm]0.270Brightness (typ.) [cd/m²]300Contrast Ratio (typ.)1000:1 (5000:1 dynamic contrast ratio)Viewing Angle [°]178 horizontal / 178 vertical (typ. at contrast ratio 10:1)Response Time (typ.) [ms]6Colours [Mio.]16.77		
Screen Aspect Ratio16:10Pixel Pitch [mm]0.270Brightness (typ.) [cd/m²]300Contrast Ratio (typ.)1000:1 (5000:1 dynamic contrast ratio)Viewing Angle [°]178 horizontal / 178 vertical (typ. at contrast ratio 10:1)Response Time (typ.) [ms]6	Panel Technology	IPS TFT with W-LED backlight
Pixel Pitch [mm]0.270Brightness (typ.) [cd/m²]300Contrast Ratio (typ.)1000:1 (5000:1 dynamic contrast ratio)Viewing Angle [°]178 horizontal / 178 vertical (typ. at contrast ratio 10:1)Response Time (typ.) [ms]6	Screen Size [inch/cm]	24 / 61
Brightness (typ.) [cd/m²] 300 Contrast Ratio (typ.) 1000:1 (5000:1 dynamic contrast ratio) Viewing Angle [°] 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) Response Time (typ.) [ms] 6	Screen Aspect Ratio	16:10
Contrast Ratio (typ.)1000:1 (5000:1 dynamic contrast ratio)Viewing Angle [°]178 horizontal / 178 vertical (typ. at contrast ratio 10:1)Response Time (typ.) [ms]6	Pixel Pitch [mm]	0.270
Viewing Angle [°] 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) Response Time (typ.) [ms] 6	Brightness (typ.) [cd/m ²]	300
Response Time (typ.) [ms] 6	Contrast Ratio (typ.)	1000:1 (5000:1 dynamic contrast ratio)
	Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colours [Mio.] 16.77	Response Time (typ.) [ms]	6
	Colours [Mio.]	16.77

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 95
Vertical Frequency [Hz]	56 - 75

Resolution

Optimum Resolution	1920 x 1200 at 60 Hz
Supported	1920 x 1200; 1920 x 1080; 1680 x 1050; 1600 x 1200; 1440 x 900; 1400 x 1050; 1366 x 768; 1360 x 768;
	1280 x 1024; 1280 x 960; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 640 x 480

Connectivity

Digital	1 x DisplayPort; 1 x DisplayPort out; 1 x DVI-D; 1 x HDMI; USB ver. 3.0 (3 down / 1 up)
Analog	1 x D-sub 15 pin

Electrical

Power Consumption on Mode [W]	22 (Eco Mode); 22 (typ.); 28 (max.)
Power Savings Mode [W]	0.3
Power Supply	internal power supply

Environmental Conditions

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80

Ergonomics

Height adjustable stand [mm]	100
Screen Tilt / Swivel [°]	-5 to +30; -170 to +170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

Mechanical

Dimensions (W x H x D) [mm]	531.5 x 397.6 x 204.3
Weight [kg]	6
VESA Mounting [mm]	100 x 100

Additional Features

Special Characteristics	Ambient light sensor for optimized brightness levels; Carbon Footprint Meter; Carbon Savings Meter; ControlSync [®] ; Customize Setting; DICOM preset; EcoModes; Human Sensor; LED Backlight Technology; NaViSet Administrator 2; sRGB Support; Touch Sensor Keys; USB ver. 3.0 (3 down / 1 up)
Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	VESA DDC2B; VESA DDCi
Audio	Headphone Jack; Integrated Speakers (1 W + 1 W)
Adjust Functions	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock- out; One Touch Recovery; Power-Off Timer; sRGB
Shipping Content	Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Setup Guide; USB Cable
Safety and Ergonomics	CE; EAC; EnergyStar 7.0; FCC Class B; Flicker-free; GEEA/Energy Label; ISO 9241-307 (pixel failure class I); Low Blue Light; RoHS; TCO 7.0; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA
Warranty	3 years warranty incl. backlight; optional 4th to 5th year warranty extension

Green Features

Energy Efficiency	Ambient light sensor; Annual energy consumption: 31 kWh (based on 4 operating hours per day); Energy efficiency class: A+; Human sensor; Intelligent Power Management
Ecological Materials	Downloadable manuals
Ecological Standards	Energy Star 7.0; TCO 7.0



This document is © 2018 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.03.2018