MultiSync® E224Wi LCD 22" Commercial Display

# **Datasheet**





The MultiSync <sup>®</sup> E224Wi is a high class 21.5" 16:9 format monitor with best IPS panel and latest energy saving LED backlight technology. It offers the latest DisplayPort connectivity and ergonomic adjustability for professional office users. Low power consumption and low operating costs make the display perfect for use in the professional office environment. Outstanding ergonomic comfort make it very user-friendly and help to increase productivity.

The ideal display for high performance office with compact space requirement.

#### **Benefits**

Ergonomic Office - full height adjustability (110 mm), tilt and flat mode ensures perfect individual ergonomic set-up.

Highly flexible connectivity - - display can be used with two digital (DVI-D, DisplayPort) and one analogue input.

Image display - 21.5inch 16:9 IPS with LED backlight.

Vesa Mount (100 mm) – allows to install the monitor via various mounting solutions.

Cost Saving Device Management - save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Droduct	I £	-4!

Product Name	MultiSync <sup>®</sup> E224Wi
Product Group	LCD 22" Commercial Display
Order Code	60003584 (BK), 60003583 (WH)

# Display

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	22 / 55
Pixel Pitch [mm]	0.248
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	6 (grey-to-grey)
Colours [Mio.]	16.7

# **Synchronisation Rate**

Horizontal Frequency [kHz]	31.5 - 81.1
Vertical Frequency [Hz]	56 - 76

#### Resolution

Optimum Resolution	1920 x 1080 at 60 Hz
Supported	1680 x 1050; 1440 x 900; 1400 x 1050; 1366 x 768; 1360 x 768; 1280 x 1024; 1280 x 960; 1152 x 870; 1152
	x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480

### Connectivity

Digital	1 x DisplayPort; 1 x DVI-D (with HDCP)
Analog	1 x mini D-sub 15 pin

### **Electrical**

Power Consumption on Mode [W]	16 (Eco Mode); 22 (typ.); 25 (max.)
Power Savings Mode [W]	0.4
Power Supply	0.45 A/0.25 A; 100-120 V/220-240 V; integrated power supply

### **Environmental Conditions**

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80

# **Ergonomics**

Height adjustable stand [mm]	110
Screen Tilt / Swivel [°]	-5 to +20; -45 to +45
Screen Rotate [°]	0 to 90 (landscape to portrait mode)

#### Mechanical

Bezel Width [mm]	14.7 (left and right); 15.8 (top and bottom)
Dimensions (W x H x D) [mm]	507.4 x 364.5 x 213.9; Without stand: 507.4 x 301.1 x 58.5
Weight [kg]	5.9
VESA Mounting [mm]	100 x 100

### **Additional Features**

Special Characteristics	21.5" (16:9) Highly efficient IPS panel with LED backlight saves more than 30 % energy; Carbon Footprint Meter; Carbon Savings Meter; EcoModes; ErgoDesign <sup>®</sup> : Height adjustable stand (110 mm) with 90° Pivot features; NaViSet Administrator 2; sRGB Support; TORO™ Design; Windows 7 compatible; Windows 8
	compatible
Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	VESA DDC2B
Adjust Functions	Auto Adjust; Brightness; Carbon Footprint Meter / Carbon Savings Meter; Contrast; DV Mode; EcoMode;
	Language Select
Shipping Content	Monitor; Power Cable; Setup Guide
	Signal Cable: [value1] x DVI-D; VGA - VGA
Safety and Ergonomics	CE; EnergyStar 6.0; FCC Class B; MPR III; PSB; RoHS; TCO 6.0; TÜV Ergonomics; TÜV GS
Warranty	3 years warranty incl. backlight

#### **Green Features**

Energy Efficiency	Annual energy consumption: 32 kWh (based on 4 operating hours per day); Carbon Footprint Meter / Carbon Savings Meter; ECOMode; Energy efficiency class: B; LED backlight technology
Ecological Materials	Downloadable manuals
Ecological Standards	Energy Star 6.0; ErP compliant; RoHS compliant; TCO 6.0







FCC Class B



MPR III





TÜVRheinland
CERTIFIED
TÜV

TCO 6.0 Ergonomics



TÜV GS

This document is @ 2018 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.03.2018