

MSDS No.: ICP-069Q

Page:1/6

Product Name: YELLOW TONER CARTRIDGE

Prepared date: 25-Oct-2002 Revised Date: 18-Feb-2003

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: YELLOW TONER CARTRIDGE

used for: magicolor 7300

Supplier Identification:

Minolta Co., Ltd.

3-13, 2-Chome, Azuchi-Machi, Chuo-Ku, Osaka 541-8556 JAPAN Telephone: +81-6-6271-2251 Facsimile: +81-6-6266-1010

Contact Point:

Minolta Co., Ltd. (Quality & Ecology Division)

3-91, Daisennishimachi, Sakai, Osaka 590-8551 Japan

Facsimile: +81-72-241-3427

2. COMPOSITION / INFORMATION ON INGREDIENTS

Substance [] Preparation [X]

Major Ingredients:

[Generic Name]	[CAS No.]	[%]
Styrene acrylic resin	+++	80-90
Wax	+++	10-20
Organic pigment	+++	1-10
Amorphous silica	7631-86-9	1-10
Titanium compound	+++	1-10

+++: Supplier's confidential information

Hazardous Ingredients:

None present



MSDS No.: ICP-069Q

Page:2/6

Product Name: YELLOW TONER CARTRIDGE

Prepared date: 25-Oct-2002 Revised Date: 18-Feb-2003

3. HAZARDS IDENTIFICATION

Classification: Not classified as dangerous. (1999/45/EC)

Most Important Hazards and Effects of the Products

For Human Health: This toner is not classified as a human carcinogen.

No symptoms expected with intended use.

For the Environment: No data are available on the adverse effects of

this product on the environment.

For Others: None

Specific Hazards: Dust explosion (likemost finely divided organic powders)

4. FIRST-AID MEASURES

Symptoms of Overexposure: No symptoms expected with intended use.

Routes of Entry: Eye contact, inhalation, ingestion

Information

Inhalation: If symptoms are experienced, remove source of contamination or move victim to fresh air and obtain medical advice.

Skin Contact: Flush with gently flowing water (preferably lukewarm) and soap for 15 minutes or until particle is removed. If irritation does occur, obtain medical advice.

Eye Contact: Donotallowvictimtorubeye(s). Flushwithgentlyflowing water (preferably lukewarm) for 15 minutes or until particle is removed. Have victim look right and left, and, then up and down. If irritation does occur, obtain medical attention. DO NOT attempt to manually remove anything stuck to the eye(s).

Ingestion: If irritation or discomfort occurs, obtain medical attention immediately.

Note to Physician: None

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: CO2, water spray, foam and dry chemical Extinguishing Media to Avoid: Full water jet

Special Firefighting Procedures: None

Fire and Explosion Hazards: Ifdispersedinair, likemostfinelydivided organic powders, may form an explosive mixture.

Protection of Firefighters: Use self-contained breathing apparatus (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: None Environmental Precautions: None

Methods for Cleaning Up: Wipe off with paper or cloth.

DO NOT use vacuum cleaner when a large amount is released. It, like most finely divided organic powders, may create a dust explosion.



MSDS No.: ICP-069Q

Page:3/6

Product Name: YELLOW TONER CARTRIDGE

Prepared date: 25-Oct-2002 Revised Date: 18-Feb-2003

7. HANDLING AND STORAGE

Handling

Technical Measures: None Precautions: None

Safe Handling Advice: Try not to disperse the particles.

Storage

Technical Measures: None

Storage Conditions: Keep container closed.

Store in a cool and dry place. Keep out of reach of children.

Incompatible Products: None

Packaging Materials: Bottles or Cartridge designated by Minolta.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures

Ventilation: None required with intended use.

Control Parameters (As total dust)

OSHA-PEL(USA): 15mg/m3 ACGIH-TLV(USA): 10mg/m3

DFG-MAK(GER): 4mg/m3 Worksafe-TWA(Austl.): 10mg/m3

Personal Protective Equipment

None required when used as intended in Minolta equipment.

Other: For use other than normal customer-operating procedures (such as in bulk toner processing facilities), goggles and respirators

may be required.

Hygiene Measures: Wash hands after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical State: Solid Form: Powder Color: Yellow

Odor: Slight mild odor

Particle Size(µm): 5-10

pH: Not applicable
Boiling Point: Not applicable
Melting Point(°C): No data available

Softening Point(°C): 125

Flash Point: Not applicable
Ignition Temperature(°C): No data available
Explosion Properties: No data available
Vapor Pressure: Not applicable

Density(g/cm^3): 1.2

Solubility in water: Negligible

Oxidizing Properties: No data available Partition Coefficient, n-Octanol/Water: Not applicable



MSDS No.: ICP-069Q

Page:4/6

Product Name: YELLOW TONER CARTRIDGE

Prepared date: 25-Oct-2002 Revised Date: 18-Feb-2003

10. STABILITY AND REACTIVITY

Stability: Stable [X] Unstable []

Hazardous Reactions: Dust explosion, like most finely divided organic

powders.

Conditions to avoid: Electric discharge, throwing into fire.

Materials to Avoid: Oxidizing materials. Hazardous Decomposition Products: CO, CO2

11. TOXICOLOGICAL INFORMATION

Health Effects from Exposure: No symptoms expected with intended use. Toxicological Data

Acute Toxicity:

Inhalation, LC50(mg/1): >4.80 (Rat,4hour) *

(This was the highest attainable concentration.)

Ingestion(oral), LD50(mg/kg): >2000 (Rat) *

Dermal, LD50(mg/kg): No data available

Eye irritation: Minimal irritant (Rabbit) *

Skin irritation: Mild irritant (Rabbit) *

Skin sensitizer: Non sensitizer (Guinea pig) *
Mutagenicity: Negative * (AMES test)

(*= Based on data for other Minolta Products with similar ingredients)

Local Effects: see Chronic Toxicity or Long term Toxicity

Chronic Toxicity or Long Term Toxicity:

Prolonged inhalation of excessive dust may cause lung damage. It is attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged interval. Use of this product, as intended, does not result in inhalation of excessive dust.

In a study in rats by chronic inhalation exposure to a typical toner, a mild to moderate degree of lung fibrosis was observed in 92% of rats in the high concentration(16mg/m^3) exposure group, and a minimal to mild degree of fibrosis was noted in 22% of the animals in the middle(4mg/m^3) exposure group. But no pulmonary change was reported in the lowest(1mg/m^3) exposure group, the most relevant level to potential human exposures.

Carcinogenicity

IARC Monographs: Not listed NTP(USA): Not listed OSHA Regulated(USA): Not listed



MSDS No.: ICP-069Q

Page:5/6

Product Name: YELLOW TONER CARTRIDGE

Prepared date: 25-Oct-2002 Revised Date: 18-Feb-2003

12. ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment.

13. DISPOSAL CONSIDERATION

Appropriate Methods of Disposal

Preparation(community provisions):

Waste may be disposed or incinerated under conditions which meet all federal, state and local environmental regulations.

Contaminated Packaging:

Waste may be disposed or incinerated under conditions which meet all federal, state and local environmental regulations.

Precautions:

Do not throw the toner cartridge or toner into an open flame. The hot toner may scatter and cause burns or other damage.

14. TRANSPORT INFORMATION

Special Precautions: None

Information on Code and Classifications According to

International Regulations UN Classification: None

15. REGULATORY INFORMATION

US Information

Information on the label: Not required

TSCA(Toxic Substances Control Act):

All chemical substances in this product comply with all applicable rules or order under TSCA.

SARA(Superfund Amendments and Reauthorization Act) Title III

302 Extreme Hazardous Substance: None

311/312 Hazard Categories: None

313 Reportable Ingredients: None

California Proposition 65:

This product contains no chemical substances subject to California Proposition 65.

EU Information

Information on the label (1999/45/EC and 67/548/EEC):

Symbol & Indication: Not required

R-Phrase: Not required S-Phrase: Not required

76/769/EEC:

All chemical substances in this product comply with all applicable rules or order under 76/769/EEC.

Article 14(2.1) of Directive 1999/45/EC is not applicable to this product.



MSDS No.: ICP-069Q

Page:6/6

Product Name: YELLOW TONER CARTRIDGE

Prepared date: 25-Oct-2002 Revised Date: 18-Feb-2003

16. OTHER INFORMATION

NFPA Hazard Rating: The National Fire Protection Agency(USA):

Health: 1 Flammability: 1 Reactivity: 0

HMIS Rating: The National Paint and Coating Association(USA):

Health: 1 Flammability: 1 Reactivity: 0

Recommended Uses:

Toner for Printer magicolor 7300

Restrictions:

Information on this data sheet represents our current data and the best opinion as to the proper use in handling of this product under normal conditions specified in our User's Manual. However, neither Minolta Co.,Ltd. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we do not guarantee that these are the only hazards which exist.

Literature References:

ANSI Z400.1-1993

ISO 11014-1

Commission Directive 91/155/EEC

H.Muhle, B.Bellmann, O.Creutzenberg, C.Dasenbrock, H.Ernst, R.Kilpper, J.C.MacKenzie, P.Morrow, U.Mohr, S.Takenaka, and R.Mermelstein(1991) Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats. Fundamental and Applied Toxicology 17, pp.280-299.