

# ThinkVision T22v-10 MONITOR

## BEST-IN-CLASS VoIP MONITOR.



Lenovo™

### EASY CONFERENCING. EASY MANAGEMENT. EASY CHOICE.

This outstanding 21.5" professional monitor is built for collaboration and conferencing with an integrated webcam, microphone and speakers. But there's no sacrificing display performance with bright, rich color and near-edgeless In-Plane Switching panel to ensure optimized visual experience. This best-in-class VoIP solution features a full range of connectivity options and full-function stand to suit any environment.

#### WHY YOU SHOULD BUY THE LENOVO™ THINKVISION® T22v-10 MONITOR




##### Easy conferencing

Conference calls are a breeze with integrated webcam with privacy lock, speakers and microphone.



##### Easy sign-in

With Windows Hello supported devices such as smartwatches, smart bracelets or smartphones, you'll get enhanced security without having to type in a password.



##### Easy on the eyes

The near-edgeless 21.5" In-Plane Switching screen provides exceptional visuals across wide-viewing angles.

#### THE LENOVO THINKVISION T22v-10 MONITOR IS BEST SUITED FOR

1

Highly-collaborative users who do a lot of web conferencing and need a simple solution with integrated features.

2

Organizations that want a best-in-class VoIP monitor with professional performance.

3

Organizations that value low energy consumption and minimum environmental impact.



# ThinkVision T22v-10 MONITOR

## SPECIFICATIONS

DISPLAY		ENVIRONMENTAL	
Panel Size	21.5"	Temperature	
Panel Type	In-Plane Switching	Operating	0°C – 40°C
Backlight	WLED	Non-Operating	-20°C – 60°C
Resolution	1920 x 1080	Humidity	
Aspect Ratio	16:9	Operating	10% – 80%
Anti-Glare	Yes	Non-Operating	5% – 95%
Screen Dimensions (W x H) (mm)	476.06 x 267.79	Altitude	
Maximum Brightness (Typical)	250 cd/m <sup>2</sup>	Operating	0 m – 8000 m
Viewing Angle (H/V at CR 10:1)	178°/178°	Non-Operating	0 ft – 40,000 ft
Contrast Ratio (Typical)	1000:1	Arsenic-Free Glass	Yes
Dynamic Contrast Ratio	3M:1	PVC-Free	Yes
Pixel Pitch (W x H) (mm)	0.25 x 0.25	Mercury-Free	Yes
Dot/Pixel Per Inch (DP/PPI)	102	PCC % of Plastic Resins	>85%
Color Gamut (CIE 1931)	72% sRGB		
Response Time (Extreme/Typical/Off)	4/6/14 ms (G-to-G)		
POWER CONSUMPTION		DIMENSIONS (W x D x H)	
Typical	18 W	Size Packed	
Maximum	43 W	(mm)	554 x 365 x 187
Sleep-Mode	<0.5 W	(inches)	21.81" x 14.37" x 7.36"
Switch Off-Mode	<0.3 W	Size Unpacked with Stand	
Power Supply	Internal	Lowest Position	
Power Voltage	90 VAC – 264 VAC	(mm)	489.7 x 251.9 x 375.8
Voltage Dynamic Frequency	47 Hz – 63 Hz	(inches)	19.28" x 9.92" x 14.79"
		Highest Position	
		(mm)	489.7 x 251.9 x 485.8
		(inches)	19.28" x 9.92" x 19.13"
		Size Unpacked without Stand	
		(Monitor Head Only)	
		(mm)	489.7 x 43.5 x 315.1
		(inches)	19.28" x 1.71" x 12.41"
		Distance from Table to Panel	
		Lowest Pixel at Bottom of Screen	
		(mm / inches)	82.1 / 3.23"
		Highest Pixel at Top of Screen	
		(mm / inches)	192.1 / 7.56"
		Stand Base Footprint Area	
		(mm / inches)	232 x 203.6 / 9.13" x 8.02"
		Weight	
		Packed	Starting at 14.46 lbs (6.56 kg)
		Unpacked	Starting at 10.16 lbs (4.61 kg)
		Monitor Head Only	Starting at 6.48 lbs (2.94 kg)
SIGNAL INPUT		COMPLIANCE	
Video Input Signals	HDMI™ 1.4 + DisplayPort™ 1.2 + VGA	EPEAT™	Gold
Video Cables Supplied	HDMI™ (ROW) + DisplayPort™ + VGA + USB 3.0	ENERGY STAR® Rating	7.0
Video Cable Length	1.8 m	ULE	Gold
USB Hub	Yes	TCO	TCO Display 7.0 / TCO Edge 2.0
USB Cable Supplied	Yes	RoHS (EU 2002/95/EC)	Yes
Audio-Out	Yes (3.5 mm)	Windows Certification	Windows 7 / Windows 10
		China Energy Efficiency Standard	Grade 2
SIGNAL INTERFACE / PERFORMANCE		WARRANTY AND AVAILABILITY	
Horizontal Frequency	30 kHz – 81 kHz	Warranty	
Vertical Frequency	50 Hz – 75 Hz	ROW	3 Years
Native Resolution	1920 x 1080	PRC	18 Months
Maximum Pixel Clock Speed/	VGA : 205 MHz	Geography Availability	WW
Bandwidth	HDMI™ : 165 MHz		
	DisplayPort™ : 165 MHz		
Default Color Temperature	6500K		
Preset/User Modes	24/20		
OSD Buttons	5+2 Buttons		
OSD Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian		
MECHANICAL			
Tilt Angle (Front / Back)	-5° / 30°		
Swivel Angle (Left / Right)	+/-45°		
Lift (mm)	Yes (110)		
Pivot	+/-90°		
VESA® Mount (mm)	Yes (100 x 100)		
Kensington® Lock Slot	Yes		
Cable Management	Yes		
Bezel Color	Raven Black		
Bezel Width			
Top (mm / inches)	2 / 0.08"		
Bottom (mm / inches)	21.4 / 0.84"		
Sides (mm / inches)	2 / 0.08"		



WWW.LENOVO.COM

Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic or typographic errors. All images are for illustration purposes only. For full Lenovo product, service and warranty specifications visit [www.lenovo.com](http://www.lenovo.com). Lenovo makes no representations or warranties regarding third party products or services. **Trademarks:** The following are trademarks or registered trademarks of Lenovo: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkServer, ThinkVantage and ThinkVision. Microsoft, Windows and Vista are registered trademarks of Microsoft Corporation. Ultrabook, Celeron, Celeron Inside, Core Inside, Intel, Intel Logo, Intel Atom, Intel Atom Inside, Intel Core, Intel Inside, Intel Inside Logo, Intel vPro, Itanium, Itanium Inside, Pentium, Pentium Inside, vPro Inside, Xeon, Xeon Phi, and Xeon Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product and service names may be trademarks or service marks of others. Battery life (and recharge times) will vary based on many factors including system settings and usage. Visit [www.lenovo.com/lenovo/us/en/safecomp/](http://www.lenovo.com/lenovo/us/en/safecomp/) periodically for the latest information on safe and effective computing. ©2017 Lenovo. All rights reserved.

Lenovo™