Fujitsu recommends Windows 10 Pro.



Data Sheet FUJITSU Desktop ESPRIMO G558

Mini, Mighty | Takes up your challenges, not your space

The FUJITSU ESPRIMO G558 offers advanced desktop PC functionality in an ultra-compact, space-saving design. With the latest 8th Gen Intel® Core™ processors, PCI Express® SSD, USB Type-C interface and dual-display support, the ESPRIMO G558 provides the performance to meet your daily office needs. Its small size and wide range of interfaces make this PC a great choice for space-constrained workplaces.

An ultra-compact design

Small footprint; energy and space-saving device for clean, clutter-free desk

■ Desktop performance in an ultra-small design (~ 0.86 liters)

Superb usability

Flexible mounting options and wide range of usage scenarios

 VESA mount compatible - mount at the back of a display, wall mount or mount under the desk, horizontal/vertical usage, easy-to-service design for convenient hardware customization/upgrades

Small yet grand

High performance in a small mini PC design

■ Latest 8th Gen Intel® Core™ processors, dual display support, USB Type C (optional), DDR4 2666 MHz memory, M.2 support, SSD PCI Express® NVMe, advanced security features (embedded TPM, Kensington Lock support, optional EraseDisk)

Perfect fit for modern offices and workplaces of tomorrow

Modular design that can transform your workplace

■ Create your own All-in-One (AiO) PC setup; support for up to two displays

Outstanding quality and reliability

Quality you can trust; based on German production standards

 Designed, developed and tested in our own factory in Augsburg to meet Fujitsu standards and exceed industry requirements











Page 1 / 8 www.fujitsu.com/fts/ESPRIMO

Components

| perating systems | |
|--|---|
| Operating system pre-installed | Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home |
| Processor | Intel® Core™ i7-8700T processor (6 Cores / 12 Threads, 2.40 GHz, up to 4.0 GHz, 12 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-9400T processor (6 Cores / 6 Threads, 1.80 GHz, up to 3.4 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-8500T processor (6 Cores / 6 Threads, 2.10 GHz, up to 3.5 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-8400T processor (6 Cores / 6 Threads, 1.70 GHz, up to 3.3 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i3-8100T processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i5-9500T processor (6 Cores / 6 Threads, 2.20 GHz, up to 3.7 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, 9 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i5-8400 processor (6 Cores / 6 Threads, 2.80 GHz, 9 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i3-9100 processor (4 Cores / 4 Threads, 3.60 GHz, up to 4.2 GHz, 6 MB, Intel® HD Graphics 630) * |
| | Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) |
| | Intel® Pentium® processor G5400T processor (2 Cores / 4 Threads, 3.10 GHz, 4 MB, Intel® UHD Graphics 610) |
| | Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610) |
| | Intel® Celeron® processor G4930 (2 Cores / 2 Threads, 3.20 GHz, 2 MB, Intel® UHD Graphics 610) |
| | Intel® Celeron® processor G4900 (2 Cores / 2 Threads, 3.10 GHz, 2 MB, Intel® UHD Graphics 610) |
| | *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) |
| emory modules | 4 GB (1 module(s) 4 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM |
| | 8 GB (1 module(s) 8 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM |
| | 16 GB (1 module(s) 16 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM |
| ard disk drives (internal) | SSD PCIe, 1024 GB M.2 NVMe module |
| | SSD PCIe, 512 GB M.2 NVMe module |
| | SSD PCIe, 256 GB M.2 NVMe module |
| | SSD PCIe, 1024 GB M.2 NVMe module, SED |
| | SSD PCIe, 512 GB M.2 NVMe module, SED |
| | SSD PCIe, 256 GB M.2 NVMe module, SED |
| | SSD SATA III, 1024 GB, 2.5-inch |
| | SSD SATA III, 512 GB, 2.5-inch |
| | SSD SATA III, 256 GB, 2.5-inch |
| | SSD SATA III, 128 GB, 2.5-inch |
| | SSD SATA III, 64 GB, 2.5-inch |
| | HDD SATA III, 7,200 rpm, 500 GB, 2.5-inch |
| | HDD SATA II, 5,400 rpm, 1,000 GB, 2.5-inch* |
| | HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch |
| Hard disk notes | SSD (Solid State Disk) |
| | SED (Self-Encrypting Drive) |
| | 2.5-inch bay for devices with 7mm height |
| raphics | DP to DVI-D (single link) Adapter Cable |
| | |
| nterface add on cards/components optional) | |

Page 2 / 8 www.fujitsu.com/fts/ESPRIMO

Base unit

| Base unit | ESPRIMO G558 |
|---|--|
| Mainboard | |
| Mainboard type | D3654 |
| Formfactor | proprietary |
| Chipset | Intel® H310 |
| Processor socket | LGA 1151 |
| Processor guantity maximum | 1 |
| Supported capacity RAM (max.) | 32 GB |
| Memory slots | 2 DIMM (DDR4) |
| Memory frequency | 2,666 MT/s |
| Memory notes | Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. |
| | 2666 MHz may be clocked down to 2400 MHz depending on processor and memory configuration |
| LAN | 10/100/1,000 MBit/s Realtek RTL8111G |
| Integrated WLAN | 1 (optional with Bluetooth together) |
| BIOS version | AMI Aptio V UEFI Specification 2.6 |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology |
| Audio type | On board |
| Audio codec | Realtek ALC671 |
| Audio features | Internal speaker supports audio playback (optional), High Definition audio |
| I/O controller on board | |
| Serial ATA total | 1 |
| thereof SATA III | 1 |
| Controller functions | Serial ATA III (6 Gbit) NCQ AHCI |
| | |
| Front audio: headphone | 1 |
| USB 2.0 total | 3 |
| USB 3.1 Gen1 (USB 3.0) total | 277 |
| | 3 (4 optional) |
| | 3 (4 optional) 1x USB 2.0; 1x USB 3.0 |
| USB front | 1x USB 2.0; 1x USB 3.0 |
| USB front USB rear | |
| USB front USB rear VGA | 1x USB 2.0; 1x USB 3.0 2x USB 2.0, 2x USB 3.0, optional 1x USB 3.0 Type-C |
| USB front USB rear VGA DisplayPort | 1x USB 2.0; 1x USB 3.0 2x USB 2.0, 2x USB 3.0, optional 1x USB 3.0 Type-C |
| USB front USB rear VGA DisplayPort HDMI | 1x USB 2.0; 1x USB 3.0 2x USB 2.0, 2x USB 3.0, optional 1x USB 3.0 Type-C optional: via external active adapter cable 1 |
| USB front USB rear VGA DisplayPort HDMI Ethernet (RJ-45) | 1x USB 2.0; 1x USB 3.0 2x USB 2.0, 2x USB 3.0, optional 1x USB 3.0 Type-C optional: via external active adapter cable 1 1 |
| USB front USB rear VGA DisplayPort HDMI Ethernet (RJ-45) Interface Module notes | 1x USB 2.0; 1x USB 3.0 2x USB 2.0, 2x USB 3.0, optional 1x USB 3.0 Type-C optional: via external active adapter cable 1 1 Anytime USB charge functionality, Optional Type-C port supports DisplayPort 1.2 and Power Delivery (PD) e.g. from |
| USB front USB rear VGA DisplayPort HDMI Ethernet (RJ-45) Interface Module notes | 1x USB 2.0; 1x USB 3.0 2x USB 2.0, 2x USB 3.0, optional 1x USB 3.0 Type-C optional: via external active adapter cable 1 1 Anytime USB charge functionality, Optional Type-C port supports DisplayPort 1.2 and Power Delivery (PD) e.g. from |
| USB front USB rear VGA DisplayPort HDMI Ethernet (RJ-45) | 1x USB 2.0; 1x USB 3.0 2x USB 2.0, 2x USB 3.0, optional 1x USB 3.0 Type-C optional: via external active adapter cable 1 1 Anytime USB charge functionality, Optional Type-C port supports DisplayPort 1.2 and Power Delivery (PD) e.g. from Display Keyboard Mouse KBPC PX ECO |

| B: 1 | |
|------------------------------------|--|
| Drive bays | 1 |
| 2.5-inch internal bays | 1 |
| M.2-2280 | 1 x on mainboard for SSD NVMe (PCIe 2.0 x4; up to 20Gbit/s) |
| Mini PCI slots | |
| M.2-2230 | on mainboard for WLAN module |
| Graphics on board | |
| Graphics brand name | Intel® UHD Graphics 610, Intel® UHD Graphics 630 |
| Shared video memory | Up to half size of total system memory |
| TFT resolution (DisplayPort) | 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel |
| TFT resolution (HDMI) | 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,640 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel |
| Graphics features | Dual display support DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.5 DisplayPort interface supports Ver. 1.2 incl. Multi-Stream |
| Graphics notes | up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz |
| Electrical values | |
| Power efficiency note | power supply efficiency at 115/230V: 88% average efficiency |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Operating voltage range | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz |
| Max. output of single power supply | 65 W external AC adapter (optional) |
| Power consumption | |
| Power consumption note | See white paper Energy Consumption |
| Link to Energy White Paper | http://docs.ts.fujitsu.com/dl.aspx?id=04df0757-cf02-4048-846f-907c4ff4dad7 |
| Heat dissipation | |
| Heat dissipation notes | See white paper Energy Consumption |

Page 4 / 8 www.fujitsu.com/fts/ESPRIMO

| Noise emission | L. 18 C. TH. 7 07007 |
|--|---|
| Related Processors for noise | Intel® Core™ i7 8700T |
| Standard noise emission | 2x4 GB, SSD, Windows According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| Standard noise operation mode: CPU 50% load | 3.2 B / 18 dB(A) Bystander; 20 dB(A) Operator position |
| Standard noise operation mode: HDD load | 3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position |
| Standard noise operation mode: Idle mode | 3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position |
| Standard noise operation mode: Office applications 2.0 | 3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position |
| Dimensions / Weight / Environmental | |
| Dimensions (W x D x H) | 146.9 x 164.5 x 36 mm |
| , | 5.78 x 6.48 x 1.42 inch |
| Operating position | horizontal / vertical (optional, feet needed) |
| VESA mount | optional mounting kit |
| Weight | 0.8 kg |
| Weight (lbs) | 1.76 lbs |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 ℃ (50 - 95 °F) |
| Operating relative humidity | 5 - 85 % (relative humidity) |
| Compliance | · · · · · · · · · · · · · · · · · · · |
| Product | ESPRIMO G558 |
| Model | TCS4 |
| Germany | TÜV GS |
| Еигоре | (E |
| USA/Canada | FCC Class B cTUVus |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 7.1 EPEAT® Gold (dedicated regions) |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Additional Software | |
| Additional software (preinstalled) | Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.) |
| | |
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) |
| Manageability software | DeskView Client DeskView Instant BIOS Management |

Page 5 / 8 www.fujitsu.com/fts/ESPRIMO

| Manageability | |
|----------------------------------|--|
| DeskView components | BIOS Management incl. Security Inventory Management Driver Management Alarm Management |
| Supported standards | DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model) |
| Manageability link | http://www.fujitsu.com/fts/manageability |
| Physical Security | Kensington Lock support |
| System and BIOS Security | Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces |
| User Security | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Workplace Protect (secure authentication solution) |
| Workplace Embedded Tools | Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection |
| Miscellaneous | |
| | Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards Keyboard on with any key (USB) Thermal management Low Power Active Mode Extended lifetime |
| Accessories information | Further helpful options |
| | Desktop Accessories: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/ Stands and Mounting kits: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf |
| Packaging information | |
| Packaging dimension (mm) | 395 x 198 x 284 mm |
| Packaging dimension (inch) | 15.55 x 7.8 x 11.18 inch |
| Material - Weight (g) Carton | 670 g |
| Material - Weight (lbs) Carton | 1.48 lbs |
| Material - Weight (g) EPS / PS | 10 g |
| Material - Weight (lbs) EPS / PS | 0.02 lbs |
| Material - Weight (g) PE | 125 g |
| Material - Weight (lbs) PE | 0.28 lbs |
| Packaging notes | If keyboard is inlcuded in packaging: 1.) packaging dimension is increasing to: $500 \times 208 \times 290 \text{mm}$ / (19.69 x 8.19 x 11.42 inch); 2.) material weight of carton will increase to 880g; 3.) max. quantity/pallet = 56; printed user documentation is bleached in chlorin free process; |

Page 6 / 8 www.fujitsu.com/fts/ESPRIMO

| Warranty | |
|--|---|
| Warranty period | 1 year (for countries in EMEIA) |
| Warranty type | Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions Product Support Services - the performance | http://support.ts.fujitsu.com/warranty rect extension |
| Recommended Service | 9x5, Onsite Response Time: Next Business Day |
| Spare Parts availability | 5 years after end of product life |
| | 5 years |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

Recommended Accessories

USB Type-C to DisplayPort Adapter



The FUJITSU USB Type-C to DP Adapter offers a fast and easy way to connect Order Code: a DisplayPort-display to your mobile system, or desktop PC, using the USB Type-C port via plug-and-play functionality

S26391-F6058-L201

USB Type-C to VGA Adapter



The FUJITSU USB Type-C to VGA Adapter offers a fast and easy way to connect an analog VGA-display or projector to your mobile system, or desktop PC, using the USB Type-C port via plug-and-play functionality

Order Code: S26391-F6058-L203

Mounting Kit for Height Adjustable FUJITSU Displays



The FUJITSU Mounting Kit for Height Adjustable FUJITSU Displays has been specifically designed for use with ESPRIMO Q/G mini PCs, FUTRO Thin Clients S26361-F2542-L452 and FUJITSU Displays. By mounting an ESPRIMO mini PC or a FUTRO Thin Client behind a display, you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Order Code:

Display P24-9 TE



The FUJITSU Display P24-9 TE is a widescreen, ultra-thin bezel display that combines future workplace concepts with advanced ergonomics. The monitor has an intelligent USB Type C hub ideal for a AiO-type use in addition to one cable connectivity for notebooks used by an on-the-move flexible workforce that needs shared workspaces.

Order Code: S26361-K1646-V141

Wireless Mouse Touch WI910



The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code: S26381-K465-L100

Keyboard KB950 Phone

The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

S26381-F950-L4** (**: Country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO G558, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO G558, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/qlobal/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html

Copyright 2019 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2019-06-01 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright 2019 Fujitsu Technology Solutions GmbH