Fujitsu recommends Windows 10 Pro.

# Data Sheet FUJITSU Desktop ESPRIMO D538

# New small form factor PC in a more compact and space-saving design

The new FUJITSU ESPRIMO D538 Desktop PC provides superior expandability features in a smaller chassis design. The latest 8th Gen Intel<sup>®</sup> Core<sup>™</sup> processors (with up to 6 cores and 12 threads) and improved connectivity options in front provide the much-needed performance to meet your daily office needs. Optional security functions, such as the integrated cabinet lock, EraseDisk and SmartCard reader help secure your valuable business data and hardware components. You can easily and freely configure each PC to meet your specific hardware needs as well as customize each PC to satisfy even more complex project requirements. With the ENERGY STAR<sup>®</sup> certification and up to 94%-efficient power supply option, ESPRIMO D538 helps reduce your carbon footprint and energy bill.

### New SFF system with 8l housing and superior expandability

Powerful and cost-effective small form factor PC that enables more space saving

Improved connectivity options that include USB 3.1 gen1, optional SD card and SmartCard reader and VGA connector

### Best energy efficiency coupled with performance

Low power consumption combined with highest levels of performance

■ 8th generation Intel<sup>®</sup> Core<sup>™</sup> processor family, a switched monitor outlet and a power supply with 94% efficiency (optional)

### Manageability and Ease of Use

- "Plug & work" PC that ensures smooth system administration
- Easy to integrate into existing IT landscapes and reliable DeskView manageability tools

#### Advanced security

Designed to protect your data and system's hardware components

 Optional EraseDisk, integrated cabinet lock and smartcard reader for greater physical and datalevel security

#### Serviceability

Accessing and servicing the system is very easy and convenient due to tool-less chassis design

Tool-less access to housing memory, connectors, ODD and HDD drives and all other components are easily accessible; optional external dust filter for the front panel for harsh, dusty environments













# Components

		ESPRIMO D538/E94+	
Processor			
Operating systems			
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	
Operating system notes	Certified for SUSE Enterprise Desktop Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual- Channel Support" at http://support.ts.fujitsu.com.	Certified for SUSE Enterprise Desktop Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual- Channel Support" at http://support.ts.fujitsu.com.	
	ESPRIMO D538/E85+	ESPRIMO D538/E94+	
Memory modules	MHz, UDIMM	<ul> <li>5 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM</li> <li>5 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM</li> <li>16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM</li> </ul>	
	ESPRIMO D538/E85+	ESPRIMO D538/E94+	
Graphics	Entry 3D: NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3x miniDP Entry 3D: AMD® Radeon R7 340, 2 GB, 1x Dual Link DVI-I, 1x DisplayPort Others: VGA Extension Card Others: DP to DVI-D (single link) Adapter Cable	Entry 3D: NVIDIA <sup>®</sup> Quadro <sup>®</sup> P400, 2 GB, PCIe x16, 3x miniDP Entry 3D: AMD <sup>®</sup> Radeon R7 340, 2 GB, 1x Dual Link DVI-I, 1x DisplayPort Others: VGA Extension Card Others: DP to DVI-D (single link) Adapter Cable	
	ESPRIMO D538/E85+	ESPRIMO D538/E94+	
rd disk driveHDD SATA II, 5,400 rpm, 500 GB, 2.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch SSD PCIe, 1024 GB M.2 NVMe module SSD PCIe, 1024 GB M.2 NVMe module, SED SSD PCIe, 256 GB M.2 NVMe module, SED SSD PCIe, 512 GB M.2 NVMe module, SED SSD SATA III, 1024 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 512 GB, 2.5-inch		HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch SSD PCIe, 1024 GB M.2 NVMe module SSD PCIe, 1024 GB M.2 NVMe module SSD PCIe, 256 GB M.2 NVMe module SSD PCIe, 256 GB M.2 NVMe module SSD PCIe, 256 GB M.2 NVMe module SSD PCIe, 512 GB M.2 NVMe module SSD SATA III, 1024 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 512 GB, 2.5-inch	
Hard disk notes	SSD (Solid State Disk) SED (Self-Encrypting Drive)		

only) only) WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only) Gigabit Ethernet PCIe x1 eSATA Interface Dual serial card PCIe x1 ESPRIMO D538/E85+ ESPRIMO D538/E94+ Mainboard Mainboard type D3600 Formfactor proprietary Chipset Intel® H310 Processor socket LGA 1151 Processor quantity maximum 1 Supported capacity RAM (max.) 32 GB Memory slots 2 DIMM (DDR4) Memory frequency 2,666 MHz Memory frequency 2,666 MHz Memory notes Dual channel support For dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 or 2133 depending on used processor LAN 10/100/1,000 MBit/s Realtek RTL8111G		ESPRIMO D538/E85+	ESPRIMO D538/E94+	
Interfaces add on cards / components WUM 1002.11ac (2x2) PCIe x1 and B1 5 (declicated regions only) only) WIM 1002.11ac (2x2) PCIe x1 (declicated regions only) Gapabit Ethernet PCIe x1 Gapabit Eth	Optical drive	DVD Super Multi ultra slim (tray), SATA	DVD Super Multi ultra slim (tray), SATA	
only Qiagbit Elbernet POE x1           Base unit         ESPRIMO DS38E85+         ESPRIMO DS38E94+           Mainboard         only         only           Forecasor socket         DG600         only           Processor quantity maximum         only         only           1         only         only           Processor quantity maximum         only         only           1         only         only           Processor quantity maximum         only         only           1         only         only           Supported capacity RAM (max)         37 CB         only           Processor quantity maximum         only         only           1         only         only         only           Supported capacity RAM (max)         37 CB         only         only           Processor quantity maximum         only         only         only         only           Supported Capacity RAM (max)         37 CB         only         only         only           Bios for quantity maximum         only         only         only		ESPRIMO D538/E85+	ESPRIMO D538/E94+	
Wainboard           Wainboard type         D3600           Formfactor         proprietary           Chipset         Intel® #310           Processor socket         LGA 1151           Processor quantly maximum         1           Suppriet clagazify RAM (max)         32 GB           Memory slots         2 DIMM (DDR4)           Memory notes         Dual channel support           Fordual channel performance.         Z memory modules have to be ordered. Capacity per channel has to be the same.           2666 MHz         Dual channel support           Fordual channel performance.         Z memory modules have to be ordered. Capacity per channel has to be the same.           2666 MHz         Dual channel support           Fordual channel performance.         Z memory modules have to be ordered. Capacity per channel has to be the same.           2666 MHz         Diritori. D color           BIOS features         BIOS Hash. FROM update by software           Recovery BIOS         United Exensible Firmware Interface (UEFI)           Support for Compatibility Support Adule (CSM) is no longer possible on systems with Bth Generation Intel® Core® i technology           Audio codec         Realtex ALC671           Audio features         Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound           <	Interfaces add on cards / components	only) WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only) Gigabit Ethernet PCIe x1 eSATA Interface	WLAN 802.11ac (2x2) PCIe x1 and BT 5 (dedicated regions only) WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only) Gigabit Ethernet PCIe x1 eSATA Interface	
Mainboard type         D3600           Formfactor         proprietary           Chipset         Intel <sup>®</sup> H310           Processor socket         LGA 1151           Processor guantity maximum         1           Supported capacity RAM (max.)         32 G6           Memory soft         20MM (DDRA)           Bio Sersion         20/time constraints, constraint	Base unit	ESPRIMO D538/E85+	ESPRIMO D538/E94+	
Formfactor         proprietary           Chipset         Inde <sup>14</sup> H310           Processor socket         LGA 1151           Processor socket         LGA 1151           Supported capacity RAM (max.)         32 GB           Supported capacity RAM (max.)         32 GB           Wemory foquency         2 G66 M1/2           Stop Soft Soft Soft Soft Soft Soft Soft Soft	Mainboard			
Chipset         Intel® H310           Processor socket         LCA 1151           Processor socket         LCA 1151           Processor socket         LCA 1151           Processor socket         S2 CB           Supported capacity RAM (max)         32 CB           Memory lots         20 WM (D0R4)           Memory notes         Dual channel support           For dual channel support         For dual channel support           Addor y be clocked down to 2400 or 2133 depending on used processor         LCA N           BIOS Features         BIOS Features LT Specification 2.6           BIOS Features         BIOS Features PROVE DROW Update by software           Recovery BIOS         Unified Txcensible Firmware Interface (UEFI)           Support for Compability Support Module (ISM) is no longer possible on systems with 8th Generation Intel® Core® II           Audio codec         Realtek ALC671           Audio features         Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound           IVO controller on board         Serial ATA III (6 Cbit)           NCO         Audio cimeneut           Serial ATA III (6 Cbit)         NCO           NCO         Audio: Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound           Interfaces	Mainboard type	D3600		
Chipset         Intel® H310           Processor socket         ICA 1151           Processor socket         ICA 1151           Processor socket         32 CB           Remory slots         32 CB           Memory slots         20MM (D0R4)           Memory notes         20mont (D0R4)           Memory notes         Dual channel support Fordual channel support           Fordual Channel Support         2666 MHz           Statistic Marchen Support         2666 MHz           Dual channel Support         2666 MHz           Statistic Marchen Support         2666 MHz           Statistic Marchen Support         2666 MHz           Dual channel Support         2666 MHz           Statistic Marchen Support         2666 MHz           Dask Statistic Marchen Support         2666 MHz           Statistic Marchen Support for Outo 2400 or 2133 depending on used processor           LAN         10/100/1000 MBits Realek R11511G           BIOS Fish EPROM update by software Recovery BIOS         Statistic Marchen Support for Compability Support Module (ISM) is no longer possible on systems with 8th Generation Intel® Core®i ( Audio tope           Audio tope         On board         Statistic Marchen Support for Compability Support Module (ISM) is no longer possible on systems with 8th Generation Intel® Core®i ( Audio tope <t< td=""><td>Formfactor</td><td>proprietary</td><td></td></t<>	Formfactor	proprietary		
Processor socketLGA 115 1Processor quantity maximum1Supported capacity RAM (max)3 2G BMemory side quancity RAM (max)3 2G BMemory side quancity RAM (max)3 2G BMemory side quancity RAM (max)2,666 MHzMemory notesFor dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 or 2133 depending on used processorLAN001001,000 MBibX Realtek RTLB111GBIOS versionMIA /ptio V UEFI Specification 2.6BIOS featuresBIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (SM) is no longer possible on systems with 8th Generation Intel® Core® i technology.Audio codecMalter Alt State Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (SM) is no longer possible on systems with 8th Generation Intel® Core® i technology.Audio todecMalter Alt State Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® i technology.For dual is factored to and terende State IIII I I I I IIII (G Dicit) IIII	Chipset			
Processor quantity maximum1Supported capacity RAM (max.)32 GBMemory forquency2,666 MHzMemory frequency2,666 MHzMemory forquency2,666 MHzMemory forquency2,666 MHzMemory forguency2,666 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,669 MHzMaxima Capacity Per channel has to be the same. 2,	•			
Supported capacity RAM (max.)32 GBMemory slots2 DIMM (DDR4)Memory frequency2 666 MHzMemory notesDial channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2 666 MHz may be clocked down to 2400 or 2133 depending on used processorLAN1071001,000 MBit/s Relatek R11.8111GBIOS versionWIL Aptio V UIFI Specification 2.6BIOS featuresBIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® 1 technologyAudio topeOn boardAudio topeNo boardVO controller on board1 Support is compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® 1 Support is compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® 1 Support is compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® 1 Support is compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® 1 Support audio playback (optional), High Definition audio, 5.1 surround soundIV controller on board1 Support Surround SoundInternal speaker supports audio playback (optional), High Definition audio, 5.1 surround SoundInternal Speaker Support Sudio playback (optional), High Definition audio, 5.1 surround SoundInternal Speaker Support Sudio playback (optional), High Definition audio, 5.1 surround SoundInternal Speaker Support Sudio playback (optional), High Definition audio, 5.1 surround Sound				
Memory stots         2 DIMM (DDR4)           Memory frequency         2.666 MHz           Memory notes         Dual channel support           For dual channel support         For dual channel support           For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.         2666 MHz may be clocked down to 2400 or 2133 depending on used processor           LAN         10/1007.000 MB/US Realtek RTL8111G         BIOS Flash EPROM update by software           Recovery BIOS         UEFI Specification 2.6         BIOS Flash EPROM update by software           Recovery BIOS         Unified Extensible Firmware Interface (UEFI)         Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology           Audio rodec         Realtek ALC671         Audio codec         Realtek ALC671           Audio codec         Realtek ALC671         Audio codec         Realtek ALC671           Or controller on board         J         J         J           Or controller on board         Serial ATA total         3         J           Controller functions         Serial ATA III (6 Gbit)         Audio codec         Serial ATA III (6 Gbit) <td></td> <td></td> <td></td>				
Memory frequency         2,666 MHz           Memory notes         Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 or 2133 depending on used processor           LAN         10/10/1,000 MBit/s Realtek RTL8111G           BIOS version         AMI Aptio V           UEF Specification 2.6         BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® i technology           Audio tope         On board           Audio tope         Realtek ALC671           Audio features         Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound           I/O controller on board         S           I/O controller on board<				
Memory notes         Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 or 2133 depending on used processor           LAN         10/10/1,000 MBit/s Realtek RTL8111G           BIOS resion         With Aptio V UEFI Specification 2.6           BIOS features         BIOS Fash EPRON update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compability Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core <sup>™</sup> i technology           Audio codec         Realtek ALC671           Audio codec         Realtek ALC671           Audio path         Support for Compability Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core <sup>™</sup> i technology           Vocantroller on board         Serial ATA total         3           Serial ATA total         3         Controller controller for Compatibility Support Audio playback (optional), High Definition audio, 5.1 surround sound           Interfaces         Controller controller functions         Serial ATA III (6 Gbit) NCO AHCI         1           State formation: interphone         1         1         1           State formation: interphone         1         1           State formation: interphone         1         1           State formation: interphone         1         1           State formation	•			
For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.           2666 MHz may be clocked down to 2400 or 2133 depending on used processor           LAN         10/100/1,000 MBit/s Realtek RTL8111G           BIOS version         AMI Aptio V           UEFI Specification 2.6         BIOS Flash EPROM update by software           Recovery BIOS         Unified Extensible Firmware Interface (UEFI)           Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® is technology           Audio type         On board           Audio features         Internal speaker supports audio playback (optional), High Definition audio, S.1 surround sound           I/O controller on board         Serial ATA total           Serial ATA total         3           Controller functions         Serial ATA III (6 Gbit)           NCQ         NCQ           Audio: line-in         1           Audio: line-in         1           Serial ATA III (6 Gbit)         NCQ           NCQ         NCQ           Audio: line-in         1           Ister Southole         1           Fort audio: microphone         1           Ister Southole         6           Southole         6           USB 2.0 total <td><i>i i i</i></td> <td colspan="3"></td>	<i>i i i</i>			
BIOS version       AMI Aptio V UEFI Specification 2.6         BIOS features       BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® i technology         Audio type       On board         Audio type       On board         Audio features       Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound         I/O controller on board       3         I/O controller on board       Serial ATA total         Serial ATA total       3         Serial ATA total       Serial ATA III (6 Gbit) NCO AHCI         NCO Audio: line-in       1         Audio: line-in       1         Audio: line-in       1         Audio: line-in       1         Stotal (S B.JO) total       4         Stotal (S B.JO) total       4         Stotal (S B.JO) total       4	wemory notes	For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.		
UEFI Specification 2.6         BIOS Features       BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core® i technology         Audio type       On board         Audio type       Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound         IV controller on board       Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound         IV controller on board       3         IV controller on board       Serial ATA total         Serial ATA total       3         Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound         IV controller on board       Serial ATA III (6 Gbit) NCO Audio Stata III         Serial ATA III (6 Gbit) NCO Audio: line-in       NCO Audio: line-in         Audio: line-in       1         Audio: line-in       1         Audio: line-in       1         Subs 2.0 total       6         USB 2.0 total       6         USB 2.0 total       1         Subs 2.0 total       1         Subs 3.1 Gen2 total       1         Subs 3.1 Gen2 total       1	LAN	10/100/1,000 MBit/s Realtek RTL8111G		
Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology           Audio type         On board           Audio codec         Realtek ALC671           Audio features         Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound           I/O controller on board         Serial ATA total           Serial ATA total         3           Serial ATA total         Serial ATA III (6 Gbit) NCQ AHCI           Serial FATA III (6 Gbit) NCQ AHCI         Serial ATA III (6 Gbit) NCQ AHCI           Interfaces         I           Seriot andio: microphone         1           Ifort audio: ine-out         1           Seriot and Compatibility Support         Seriot ATA III (6 Gbit) NCQ AHCI           Seriot and Compatibility Support         1           Seriot Support         1           Seriot Supporting Compatibility Support         1 </td <td>BIOS version</td> <td colspan="3"></td>	BIOS version			
Audio codecRealtek ALC671Audio featuresInternal speaker supports audio playback (optional), High Definition audio, 5.1 surround soundI/O controller on board3Serial ATA total3Serial ATA total3thereof SATA III3Controller functionsSerial ATA III (6 Gbit) NCQ AHCIInterfaces1Audio: line-in1Audio: line-out1Front audio: microphone1Front audio: headphone1USB 2.0 total6USB 3.1 Gen1 (USB 3.0) total4USB 3.1 Gen2 total1 optional via add on cardUSB front2 x USB 2.0; 2x USB 3.0	BIOS features	Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i		
Audio codecRealtek ALC671Audio featuresInternal speaker supports audio playback (optional), High Definition audio, 5.1 surround soundI/O controller on board3Serial ATA total3Serial ATA total3thereof SATA III3Controller functionsSerial ATA III (6 Gbit) NCQ AHCIInterfaces1Audio: line-in1Audio: line-out1Front audio: microphone1Front audio: headphone1USB 2.0 total6USB 3.1 Gen1 (USB 3.0) total4USB 3.1 Gen2 total1 optional via add on cardUSB front2 x USB 2.0; 2x USB 3.0	Audio type	On board		
Audio featuresInternal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound//O controller on board//O controller on boardSerial ATA total3sthereof SATA III3Controller functionsSerial ATA III (6 Gbit) NCQ AHCIStrefaces				
Serial ATA total3thereof SATA III3thereof SATA1Controller functionsSerial ATA III (6 Gbit) NCQ AHCIInterfaces1Audio: line-in1Audio: line-out1Front audio: microphone1Interfaces1Serial ATA III (S Gbit) NCQ AHCISerial ATA III (S Gbit) NCQ AHCISerial ATA III (S Gbit) NCQ AHCISerial ATA III (S Gbit) NCQ AHCIInterfacesSerial ATA III (S Gbit) NCQ AHCISerial ATA III (S Gbit) Serial ATA III (S Gbit) Ser				
Serial ATA total3thereof SATA III3thereof SATA1Controller functionsSerial ATA III (6 Gbit) NCQ AHCIInterfaces1Audio: line-in1Audio: line-out1Front audio: microphone1Interfaces1Serial ATA III (S Gbit) NCQ AHCISerial ATA III (S Gbit) NCQ AHCISerial ATA III (S Gbit) NCQ AHCISerial ATA III (S Gbit) NCQ AHCIInterfacesSerial ATA III (S Gbit) NCQ AHCISerial ATA III (S Gbit) Serial ATA III (S Gbit) Ser	I/O controller on board			
thereof SATA III3thereof eSATA1Controller functionsSerial ATA III (6 Gbit) NCQ AHCIInterfaces1Audio: line-in1Audio: line-out1Front audio: microphone1Front audio: headphone1USB 2.0 total6USB 3.1 Gen1 (USB 3.0) total4USB 5.1 Gen2 total1 optional via add on cardUSB front2x USB 2.0; 2x USB 3.0	Serial ATA total	3		
thereof eSATA1Controller functionsSerial ATA III (6 Gbit) NCQ AHCIInterfacesAudio: line-in1Audio: line-out1Front audio: microphone1InterfacesFront audio: headphone1JSB 2.0 total6USB 3.1 Gen1 (USB 3.0) total4USB 3.1 Gen2 total1 optional via add on cardUSB front2x USB 2.0; 2x USB 3.0				
Controller functionsSerial ATA III (6 Gbit) NCQ AHCIInterfacesAudio: line-in1Audio: line-out1Front audio: microphone1InterfacesStront audio: headphone1InterfacesUSB 2.0 total6USB 3.1 Gen1 (USB 3.0) total4USB 3.1 Gen2 total1 optional via add on cardUSB front2x USB 2.0; 2x USB 3.0				
Audio: line-in1Audio: line-out1Front audio: microphone1Front audio: headphone1USB 2.0 total6USB 3.1 Gen1 (USB 3.0) total4USB 3.1 Gen2 total1 optional via add on cardUSB front2x USB 2.0; 2x USB 3.0		Serial ATA III (6 Gbit) NCQ		
Audio: line-out1Front audio: microphone1Front audio: headphone1USB 2.0 total6USB 3.1 Gen1 (USB 3.0) total4USB 3.1 Gen2 total1 optional via add on cardUSB front2x USB 2.0; 2x USB 3.0	Interfaces			
Front audio: microphone1Front audio: headphone1JSB 2.0 total6JSB 3.1 Gen1 (USB 3.0) total4JSB 3.1 Gen2 total1 optional via add on cardJSB front2x USB 2.0; 2x USB 3.0	Audio: line-in	1		
Front audio: headphone         1           JSB 2.0 total         6           JSB 3.1 Gen1 (USB 3.0) total         4           JSB 3.1 Gen2 total         1 optional via add on card           JSB front         2x USB 2.0; 2x USB 3.0	Audio: line-out	1		
Front audio: headphone         1           JSB 2.0 total         6           JSB 3.1 Gen1 (USB 3.0) total         4           JSB 3.1 Gen2 total         1 optional via add on card           JSB front         2x USB 2.0; 2x USB 3.0	ront audio: microphone	1		
JSB 2.0 total         6           JSB 3.1 Gen1 (USB 3.0) total         4           JSB 3.1 Gen2 total         1 optional via add on card           JSB front         2x USB 2.0; 2x USB 3.0		1		
USB 3.1 Gen1 (USB 3.0) total         4           USB 3.1 Gen2 total         1 optional via add on card           USB front         2x USB 2.0; 2x USB 3.0	•	6		
USB 3.1 Gen2 total         1 optional via add on card           USB front         2x USB 2.0; 2x USB 3.0				
<b>USB front</b> 2x USB 2.0; 2x USB 3.0				

Interfaces	
USB internal	2x USB 2.0
VGA	optional: via adapter card
DisplayPort	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality
Input device / components	
Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
Drive bays	
2.5-inch bays	1
3.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	5,25" bay: for slim optical disc drive only; 3.5" bay for 1x 3.5" drive (screwless) or optional via adapter for 1x or 2x 2.5" drives (screwless); 2.5" bay for 1x 2.5" drive (screws)
M.2-2280	1 x on mainboard for SSD NVMe (PCIe 2.0 x2; up to 10Gbit/s)
Slots	
PCI-Express 3.0 x16	1 x (174 mm / 6.85 inch) Low profile
PCI-Express 2.0 x4 (mech. x16)	1 x (174 mm / 6.85 inch) Low profile
Graphics on board	
Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel

Graphics on board			
Graphics features	Dual display support		
	DirectX <sup>®</sup> 12		
	HDCP support		
	OpenCL <sup>™</sup> 2.0 (requires Intel <sup>®</sup> Core <sup>™</sup> i3, i5 or i7 processors)		
	OpenGL <sup>®</sup> 4.4 For multi monitoring mode, graphics card and integrated g	ranhics run in narallel	
	DisplayPort interface supports Ver. 1.2 incl. Multi-Stream		
	DVI-D interface supports audio output and higher resolution	ns up to 4096 x 2160 pixel (at 30Hz refresh rate) if connected	
	to the HDMI interface of a display via suitable adapter cables (not included)		
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz		
Base unit	ESPRIMO D538/E85+	ESPRIMO D538/E94+	
Electrical values			
Power efficiency note	power supply efficiency at 10% / 20% / 50% / 100% load for	power supply efficiency at 10% / 20% / 50% / 100% load for	
	230V: 80% / 85% /88% / 87%; for 115V: 79%/ 84%/ 87%/ 84%	230V: 87% / 91% / 94% / 93%; for 115V: 86%/ 90%/ 92%/ 90%	
Rated voltage range	100 V - 240 V	100 V - 240 V	
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz	
Operating voltage range	90 V - 264 V	90 V - 264 V	
Operating line frequency range	47 Hz - 63 Hz	47 Hz - 63 Hz	
Max. output of single power supply	210 W	280 W	
Power factor correction/active power	active		
Monitor outlet	No	Switched	
Base unit	ESPRIMO D538/E85+	ESPRIMO D538/E94+	
Power consumption			
Power consumption note	See white paper Energy Consumption	See white paper Energy Consumption	
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=aadc7d0a-1289-477c- 81e2-17b490da661f	http://docs.ts.fujitsu.com/dl.aspx?id=216fd5ef-967b-4c68- bd3b-8f74d3aba0a8	
Noise emission			
Related Processors for noise	Intel® Core™ i7 8700	Intel® Core™ i7 8700	
Standard noise emission	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74	
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))	
Standard noise operation mode: CPU 50% load	3.5 B / 22 dB(A) Bystander; 24 dB(A) Operator position	3.5 B / 21 dB(A) Bystander; 23 dB(A) Operator position	
Standard noise operation mode: HDD load	3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position	3.5 B / 21 dB(A) Bystander; 24 dB(A) Operator position	
Standard noise operation mode: Idle mode	3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position	3.4 B / 20 dB(A) Bystander; 21 dB(A) Operator position	
Standard noise operation mode: ODD load	4.5 B / 32 dB(A) Bystander; 36 dB(A) Operator position	4.5 B / 31 dB(A) Bystander; 36 dB(A) Operator position	
Standard noise operation mode: Office applications 2.0	3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position	3.4 B / 21 dB(A) Bystander; 22 dB(A) Operator position	
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	313 x 286 x 89 mm		
	12.32 x 11.26 x 3.51 inch		
Operating position	horizontal / vertical (optional, feet needed)		
Weight	5 kg		
Weight (lbs)	11.03 lbs		

Dimensions / Weight / Environmental				
Weight notes	Actual weight may vary depending on configuration			
Operating ambient temperature	10 - 35 °C (50 - 95 °F)			
Operating relative humidity	5 - 85 % (relative humidity)			
Compliance				
Product	ESPRIMO D538/E85+ ESPRIMO D538/E94+			
Model	DTL			
Germany	TÜV GS			
Еигоре	CE			
USA/Canada	FCC Class B cTUVus			
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 7.1 EPEAT® Gold (dedicated regions)			
China	CCC (planned) CCC (depending on configuration) CEL (Chinese energy label) TPM 2.0 for China (optional)			
Compliance link	https://sp.ts.fujitsu.com/sites/certificates			
Additional Software				
Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)			
Additional software (optional)	Recovery DVD for Windows <sup>®</sup> Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft <sup>®</sup> Office Professional 2019 Microsoft <sup>®</sup> Office Home and Business 2019 (A Microsoft Account is required to activate each copy of the which it was acquired.)	™) ese products. For purchase and activation only in the region i		
Base unit	ESPRIMO D538/E85+	ESPRIMO D538/E94+		
Security				
Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)		
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1709) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces	Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1709) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces		
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)			
Auto BIOS Update via customer server Auto BIOS Update		Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection		

Manageability				
Manageability technology	DeskUpdate Driver management			
	PXE 2.1 Boot code Wake up from S5 (off mode)			
	Intrusion switch (optional)			
	WoL (Wake on LAN)			
Manageability software	DeskView Client			
	DeskView Instant BIOS Management			
DeskView components	BIOS Management incl. Security Inventory Management			
	Driver Management			
	Alarm Management			
Supported standards	DMI (Desktop Management Interface)			
	SMBIOS (System Management BIOS) PXE (Preboot Execution Environment)			
	WMI (Windows Management Instrumentation)			
	WBEM (Web Based Enterprise Management)			
	CIM (Common Information Model)			
Manageability link	http://www.fujitsu.com/fts/manageability			
Miscellaneous				
	Keyboard on (Special Fujitsu keyboard required)	Keyboard on (Special Fujitsu keyboard required)		
	Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special	Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special		
	USB keyboards USB keyboards			
	Keyboard on with any key (USB)	Keyboard on with any key (USB)		
	Thermal management	Thermal management		
Packaging information				
Packaging dimension (mm)	467 x 265 x 540 mm	467 x 265 x 540 mm		
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch	18.39 x 10.43 x 21.26 inch		
Max. quantity / pallet	24	24		
Material - Weight (g) Carton	1180 g	1180 g		
Material - Weight (lbs) Carton	2.6 lbs	2.6 lbs		
Material - Weight (g) EPS / PS	230 g	230 g		
Material - Weight (lbs) EPS / PS	0.51 lbs	0.51 lbs		
Material - Weight (g) PE	60 g	60 g		
Material - Weight (lbs) PE	0.13 lbs	0.13 lbs		
Packaging notes	printed user documentation is bleached in chlorine free process	printed user documentation is bleached in chlorine free process		
Warranty				
Warranty period	1 year (for countries in EMEIA)			
Warranty type	Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations)			
Warranty Terms & Conditions Product Related Services - the perfect	http://support.ts.fujitsu.com/warranty			
Recommended Service	9x5, Onsite Response Time: Next Business Day			
Spare Parts availability	5 years after end of product life			
Service Weblink	http://www.fujitsu.com/fts/services/support			

# **Recommended Accessories**

Display B24W-7 LED	The FUJITSU B24W-7 LED Display with excellent ergonomics makes intensive office work extremely comfortable. This highly reliable display offers superb usability and power-saving features to help reduce your labor as well as energy costs. With wide viewing angle technology, flexible connectivity, and easy manageability, the FUJITSU B24W-7 LED Display can help you improve productivity.	
Blue LED Mouse GL9000	Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.	Order Code: S26381-K438-L100
SOUNDSYSTEM DS E2000 Air	The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.	Order Code: S26391-F7128-L600
Keyboard KB950 Phone	The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.	S26381-F950-L4** (**: Country specific variation)

# More information

#### Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO D538, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### **Computing Products**

www.fujitsu.com/global/products/computing/

#### Software

www.fujitsu.com/software/

#### More information

Learn more about FUJITSU Desktop ESPRIMO D538, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/ESPRIMO

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http:// www.fujitsu.com/fts/resources/navigation/ terms-of-use.html

Copyright 2019 Fujitsu Technology Solutions GmbH

#### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2019-01-18 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html Copyright 2019 Fujitsu Technology Solutions GmbH