# i-SENSYS LBP212dw \ LBP214dw \ LBP215x

# SINGLE-FUNCTION BLACK & WHITE PRINTER OFFERING RELIABILITY AND GREATER COST CONTROL.

The i-SENSYS LBP210 series are fast, double sided, A4 black and white printers engineered to enhance work flow and productivity, and cut costs. Delivering improved, high-quality results, they are ideal for SMEs.



Санон



LBP212dw

LBP214dw

LBP215x

- Save time with fast print speeds of up to 38ppm (LBP214dw/ LBP215x)
- High quality 1200 x 1200 dpi print resolution
- Easy operation with large colour touchscreen on LBP215x
- Compatible with AirPrint and Mopria for mobile connectivity
- Large storage with 1GB internal memory
- Secure PIN printing from mobile devices (LBP214dw/ LBP215x)
- Improved flexibility with varied media support; A4, A5, A6
- Quick and simple mobile connectivity via QR code (LBP215x)
- Application Library allowing automation, added shortcuts and a customised interface(LBP215x)
- Universal Login Manager function and uniFLOW ready (LBP215x)



## **OPTIONAL ACCESSORIES**

### **Cassette Feeding Module AH1**

• Additional 550 sheet paper cassette, 1unit can be added to main unit.

#### Barcode Print Kit- E1E (Available on LBP215x)

• Installs bar code fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation.

# TECHNICAL SPECIFICATIONS

PRINTER ENGINE		Dimensions (W x D x H)	LBP215x: 438 mm x 373 mm x 312 mm
Print speed	LBP214dw, LBP215x		LBP214dw/LBP212dw: 401 mm x 373 mm x 250 mm
	Single sided : Up to 38 ppm (A4) Up to 63.1 ppm(A5-Landscape)	Weight	LBP215x: Approx. 9.9 Kg LBP214dw/LBP212dw: Approx. 9.5 Kg
	Double sided : Up to 30.3 ipm (A4) LBP212dw	Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)
	Single sided : Up to 33 ppm (A4) Up to 52.5 ppm(A5-Landscape) Double sided : Up to 26.4 ipm (A4)	Control panel	LBP215x: 12.7 cm LCD Colour Touch Screen LBP214dw/LBP212dw: 5 Line LCD, 3 LED (Job, Error,
Printing method	Monochrome laser beam printing		Energy saver), Buttons, 10-key numeric keypad
Print quality	Up to 1200 x 1200 dpi	CONTROLLER	
Print resolution	600 x 600 dpi	Processor Speed	800MHz x 2
Warm-up time	Approx. 14 seconds or less from power on	Memory	1GB
First Page Out Time	Approx: 5.5 seconds or less	Printer Languages	LBP215x/LBP214dw: UFRII, PCL 5e <sup>4</sup> , PCL6, Adobe*
Recommended Monthly Print Volume	750 - 4,000 pages per month		PostScript LBP212dw: UFRII, PCL 5e <sup>4</sup> , PCL6
Duty cycle	80,000 pages	Fonts	LBP215x: 93 PCL fonts, 136 PS fonts
Print margins	5 mm-top, bottom, left and right		LBP214dw/LBP212dw: 45 PCL fonts, 136 PS fonts
Advanced printing features	Secure Print (LBP214dw, LBP215x only) Print from USB memory key (JPEG/TIFF/PDF) Barcode Print <sup>1</sup> (LBP215x only)	Interface and connectivity	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
	Barcode Print "(LBP2Isx only) Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app	Software and Printer Management	Remote User Interface (RUI), Department ID Management, Toner Status Tool, IW Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote
MEDIA HANDLING			eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.
Paper input (Standard)	250-sheet cassette 100-sheet multi-purpose tray		Universal Log-in Manager (LBP215x only) uniFLOW online (LBP215x only)
Paper input (Option)	550-sheet cassette		uniFLOW online Express (LBP215x only) uniFLOW Compatibility with embedded uniFLOW Login
Paper output	150-sheet		Device Client (LBP215x only)
Media types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope	Operating Systems Compatibility	Windows* 10 / Windows* 8.1 / Windows* 7 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server*
Media sizes	Cassette (Standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Custom sizes: Min. 105 x 148 mm Max. 215.9 x 355.6 mm.	CONSUMABLES	2008 Mac OS X version 10.8.5 & up Linux <sup>5</sup>
	Multi-purpose tray:	All-in-One cartridges	Cartridge 052 (3,100 pages <sup>6</sup> ) <sup>7</sup>
	A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COMI0, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 215.9 x 355.6 mm.	ACCESSORIES/ OPTIONS	Cartridge 052H (9,200 pages <sup>6</sup> ) <sup>7</sup>
Media weights	Cassette (standard and optional): 52 to 120 g/m <sup>2</sup>	Items	Cassette Feeding Module-AH1
Double sided printing	multi-purpose tray: 52 to 163 g/m² A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscap		MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) (LBP215x only) Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW) (LBP215x only)
	Custom size - Min. 210 x 279.4 mm Max. 215.9 x 355.6 mm 60 to 120 g/m <sup>2</sup>		MiCard Attachment kit-BI (LBP215x only) Barcode Printing Kit-EIE (LBP215x only)
GENERAL FEATURES		Notes:	
Power requirements	220-240V(±10%) 50/60Hz (±2Hz)	<sup>11</sup> Accessory - Barcode Printing Kit-E1E - is required	
Power consumption	Maximum: Approx. 1,300 W Standby: Approx. 10 W	<sup>[2]</sup> Declared noise emission in accordance with ISO 9296	
	Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC):	<sup>[3]</sup> Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779	
LBP215x/214dw 1.2 kWh/week (230V) LBP212dw 1.1 kWh/week(230V)		<sup>(4)</sup> A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.	
	For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx	<sup>(5)</sup> Web distribution only Available from December 2018.	
Noise level	Sound Pressure <sup>2</sup> :	<sup>[6]</sup> Based on ISO/IEC 19752	
	Active: 56 dB Standby: Inaudible <sup>3</sup>	<sup>[7]</sup> Printer ships with starter cartridge (Black: 1,600pages)	
	Sound Power <sup>2</sup> : Active: 72.2 dB Standby: Inaudible <sup>3</sup>		

### Canon (UK) Ltd

Woodhatch Reigate Surrey RH2 8BF Telephone No: 01737 220000 Facsimile No: 01737 220022 canon.co.uk Canon Inc. Canon.com

Canon Europe canon-europe.com

UK English Edition © Canon Europa N.V., 2018



# SINGLE-FUNCTION BLACK & WHITE PRINTER OFFERING RELIABILITY AND GREATER COST CONTROL.

The i-SENSYS LBP210 series are fast, double sided, A4 black and white printers engineered to enhance work flow and productivity, and cut costs. Delivering improved, high-quality results, they are ideal for SMEs.

### Sales Start Date: April 2018

## i-SENSYS LBP212dw \ LBP214dw \ LBP215x



#### PRODUCT DETAILS:

Product name	Mercury code	EAN Code
i-SENSYS LBP212dw GB	2221C019AA	8714574656656
i-SENSYS LBP214dw GB	2221C017AA	8714574656632
i-SENSYS LBP215x GB	2221C015AA	8714574656618

#### ACCESSORIES:

Product name	Mercury code	EAN Code
Cassette Feeding Module-AH1	0732A033AA	4549292092769
 MiCard Attachment kit-B1	5146B002AA	4549292027235
Barcode Printing Kit-E1E	5143B002AA	N/A (e-delivery)

#### CONSUMABLES:

Product name	Mercury code	EAN Code
Cartridge 052	2199C002AA	4549292089400
Cartridge 052 H	2200C002AA	4549292089424

#### EASY SERVICE PLAN:

Product Name	Mercury Code	EAN Code
Installation service	7950A546AA	4960999794426
3-year on-site next day service-Pack A (LBP212dw & LBP214dw)	7950A525AA	4960999793290
3-year on-site next day service-Pack B (LBP215x)	7950A526AA	4960999793306

