

TeraStation[™] 5010

Network Attached Storage

NAS with native 10GbE connectivity.

Scalable high performance network storage for businesses.

Buffalo's TeraStation[™] 5010 series has been built for small and medium sized businesses seeking an easy and cost-effective 10GbE platform. The TS5010 is a network attached storage (NAS) solution with iSCSI protocol designed to move SMB data at enterprise level speeds and eliminate the bottlenecks that can occur on slower networks.

Thanks to its powerful hardware the TS5010 series can run multiple concurrent services seamlessly with minimal performance degradation, and is ideal for organizations looking to add an affordable virtualized storage to their business network. Branch offices no longer need full-scale server infrastructure for simple tasks such as file sharing and backup. Cloud backup is also supported with Microsoft Azure and OneDrive, Dropbox/Dropbox Business and Amazon S3. In combination with Buffalo's 10GbE business switches the quad core processor featuring TS5010 reaches faster than ever data transfer speeds. The series comes populated with NAS- or enterprise nearline (TS51210RH) grade HDD and is available in 2-,4- or 8-bay desktop and 4- or 12-bay rackmount configurations.

The 4-, 8- and 12-bay versions come fully populated or partially populated, thus giving companies the flexibility to start with a smaller initial investment and increase the total capacity when the need arises in the future. The 2-bay TS5210DF is equipped with SSDs and therefore highly shock-/vibration-proof and extremely fast.

Features and Benefits

- High-speed native 10GbE connection (1 or 2 (TS51210RH only) 10GbE ports)
- 2.5/5Gbps compatible, compliant with NBASE-T (IEEE 802.3bz) standard
- Powered by the high performance Annapurna Labs[®] Quad-Core processor with 4GB/8GB (TS51210RH) DDR3 ECC RAM
- Available in 2-bay, 4-bay and 8-bay desktop models or 4-bay and 12-bay rackmount
- Simultaneous NAS and iSCSI target functionality
- Advanced NTFS Permissions (Windows ACL)
- VMware readv
- Rapid RAID mode change
- RAID Mode Manager

- TRIM Command for increased SSD life time (TS5210DF)
- AES 256bit data encryption
- Boot Authentication ensures the device is only accessible on authorized networks
- Integrated cloud backup with Microsoft Azure and OneDrive, Dropbox and Amazon S3
- Remote access through WebAccess
- NovaBACKUP[®] backup software (11 licences for NovaBACKUP[®] Buffalo Edition)
- Duplex System Firmware Boot
- Active Directory (up to 10.000 supported users/groups imported from the domain)
- 3 year standard warranty (5 years for TS51210RH) including 24-hour HDD replacement; warranty extensions available separately (not for TS51210RH)

About **BUFFALO**

BUFFALO is a leading global provider of award-winning storage, networking and multimedia solutions for the home and small business environments as well as for system builders and integrators. With more than four decades of networking and computer peripheral experience, BUFFALO has proven its commitment to delivering innovative solutions that have put the company at the forefront of infrastructure technology.

Specifications

Models	TS5210DF (2-bay)	TS5210DN (2-bay)	TS5410DN (4-bay)	TS5410RN (4-bay)	TS5810DN (8-bay)	TS51210RH (12-bay)	
Part Numbers	TS5210DF00502-EU TS5210DF0202-EU	TS5210DN0402-EU TS5210DN0602-EU TS5210DN0802-EU TS5210DN1202-EU TS5210DN1602-EU	TS5410DN0804-EU TS5410DN1204-EU TS5410DN1604-EU TS5410DN12404-EU TS5410DN3204-EU	TS5410RN0804-EU TS5410RN1204-EU TS5410RN1604-EU TS5410RN2404-EU TS5410RN3204-EU	TS5810DN3208-EU TS5810DN6408-EU Partially populated TS5810DN1604-EU TS5810DN3204-EU	TS51210RH2412-EU TS51210RH4812-EU TS51210RH9612-EU TS51210RH9612-EU TS51210RH12012EU TS51210RH14412EU	
			Partially populated TS5410DN0802-EU TS5410DN1602-EU	Partially populated TS5410RN1602-EU	155010213204-20	Partially populated TS51210RH0804-EU TS51210RH1604-EU TS51210RH3204-EU TS51210RH4004-EU TS51210RH4804-EU	
Configuration Total Capacities	Desktop 512 GB, 2 TB	Desktop 4, 6, 8, 12, 16 TB	Desktop 8, 12, 16	Rackmount 19" 1U 6, 24, 32 TB	Desktop 16, 32, 64 TB	Rackmount 19" 2U 8, 16, 24, 32, 40, 44, 48 96, 120, 144 TB	
Anti-Vibration	10-150Hz 6G					00, 120, 11110	
nternal Hard Drives							
ӯре	SSD		NA	S HDD		Nearline HDD	
Number of Drives	2	2	4 (fully populated) 2 (partially populated)	4 (fully populated) 2 (partially populated)	8 (fully populated) 4 (partially populated)	12 (fully populated) 4 (partially populated)	
Capacities Drive Interface	256 GB, 1 TB		2, 3, 4, 6, 8 TB	C Ohne	4, 8 TB	2, 4, 8, 10, 12 TB	
Supported RAID	JBOD/0/1 JBOD/0/1/5/6/10						
JSB Interface							
Standard Compliance			USP	3 2.0/3.0			
Connector Type	A type						
Number of Ports	2 x USB 3.0 3 x USB 3.0					2 x USB 2.0, 2 x USB 3	
Data Transfer Rates		2 X USB 3.0 3 X USB 3.0 2 X USB 2.0, 2 X USB					
System/Performance							
CPU		Anr	napurna Labs® Alpine-Proze	essor AL314 (1.7 GHz Quad	d-Core)		
RAM			4 GB DDR3 with ECC			8 GB DDR3 with ECC	
nvironmental & Power							
ower Unit	1	1	1	1	1	1 (2nd optional)	
ower Consumption	Max. 85 W; average active: 30 W; average idle: 15 W; standby: 0.8 W	Max. 85 W; average active: 45 W; average idle: 32 W; standby: 0.8 W	Max. 85 W; average active: 56 W; average idle: 45 W; standby: 0.8 W	Max. 100 W; average active: 60 W; average idle: 46 W; standby: 0.7 W	Max. 150 W; average active: 108 W; average idle: 87 W; standby: 4.5 W	Max. 500 W; average active: 122 W; average idle: 100 W; standby: 3.9 W	
Power Supply	Internal AC 100-240 V, Universal 50/60 Hz						
Operating Temperature	0° - 40°C						
Dperating Humidity	10 - 85 % non-condensing						
Dimensions/Weight							
Dimensions (WxHxD)	170 x 170 x 230 mm	170 x 170 x 230 mm	170 x 215 x 230 mm	430 x 44,3 x 430 mm	300 × 215 × 230 mm	481 x 88 x 736.9 mm	
Veight	3.5 kg	4.8 kg	7 kg	8.4 kg	12.5 kg	20 kg (main unit with 4 HDDs) 25 kg (main unit with 12 HDDs)	
LAN Interface							
Standards Compliance Number of Ports	(10BASE-T) IEEE802.3, (100BASE-TX) IEEE802.3u, (1000BASE-T) IEEE802.3ab, (10GBASE-T) IEEE802.3an, (NBASE-T 1 (10GBASE-T), 2 (1GBASE-T)) IEEE802.3bz 2 x 10GBASE-T, 2 x 1GBASE-T	
Data Transfer Rates Supported Protocols	2.5/5/10 Gbps / 10/100/1000 Mbps TCP/IP						
Network File Services	CIFS/SMB, AFP, FTP, SFTP, NFS, SNMP						
Connector Type	RJ-45						
Other Client OS Support	Windows® 10, Windows® 8.1, Windows® 7, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012,						
ncluded Software	Windows Server® 2008, Mac® OS® X 10.9 or later NAS Navigator 2, NovaBACKUP® Buffalo Edition (one server and ten workstation licenses)						
Box Contents	TeraStation™, Quick Setup Guide, Cat 6a Ethernet Cable, AC Cable, Front Panel Key or Rail Kit with Mounting Brackets and Screws and Warranty Statemen						
Accessories	OB SSD3560						
Compatible Hard Drives	OP-SSD256G, OP-SSD1.0	OP-HD2.0N, OP-HD3.0N, OP-HD4.0N, OP-HD6.0N, OP-HD8.0N OP-HD4.0N, OP-HD8.0				N OP-HD2.0H2U-5Y OP-HD4.0H2U-5Y OP-HD8.0H2U-5Y OP-HD10.0H2HU-5Y OP-HD12.0H2HU-5Y	
Redundant Power Unit						OP-PU-10R2U-EU	
	5year WARRANTY SERVICE	24/7 NAS		ASTOR 😵 Dro	opbox 🔥 Az		
3 year warranty on all products,	including option of +1 / +2 year w			arranty extension.	a On	eDrive BUFFAL	
, jean manancy on an producto,			.,, isi reore form, without we				
						web acc	

© Buffalo Inc. 2019.

BUFFALD logo, TeraStation, LinkStation, DriveStation and MiniStation are either trademarks or registered trademarks of Melco Holdings Inc. or Buffalo Inc. Microsoft Windows and Microsoft logo are either registered trademarks or trademarks of Melco Holdings Inc. or Buffalo Inc. Microsoft Windows and Microsoft logo are either registered trademarks or trademarks of Melco Holdings Inc. or Buffalo Inc. Microsoft Windows and Microsoft logo are either registered trademarks or trademarks of Melco Holdings Inc. or Buffalo Inc. Microsoft Windows and Microsoft logo are either registered trademarks or trademarks of Melco Holdings Inc. or Buffalo Inc. Microsoft Corporation in United States and/or other countries. The names and logos of other companies mentioned herein belong to their respective owners. The information within this datasheet is subject to change without notice. All rights reserved. E & 0E.