

## **Gripfoot**



- Abrasive grit tape with self-adhesive backing to reduce slipping
- Gives additional grip to smooth surfaces
- Hard-wearing and easy to install
- 'Clear' version for decorative tiled floors
- Suitable for ladder/stair treads, ramps, walkways, entrances, loading docks, machinery and plant equipment, vehicles and boats

## **Technical Specifications:**

Conforms to Slip Resistance Test EN 13552 Category R13

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
25mm x 18.3m	0.40	15 x 16 x 2.5	Jiffy Bag	1	27	Black	GF010001
50mm x 18.3m	0.85	20 x 26 x 6	Jiffy Bag	1	27	Yellow	GF070002
						Red	GF030002
						Green	GF040002
						White	GF130002
						Blue	GF020002
						Black	GF010002
						Clear	GF120002
102mm x 18.3m	1.55	20 x 33 x 11	Jiffy Bag	1	27	Black	GF010003
152mm x 18.3m	2.35	20 x 20 x 16	Jiffy Bag	1	27	Black	GF010004
152mm x 610mm	0.15	18 x 20 x 1.5	Jiffy Bag	10	N/A	Black	GF010006
						Clear	GF120006
140mm x 140mm	0.75	18 x 66 x 1.5	Jiffy Bag	10	N/A	Black	GF010005
						Clear	GF120005

Material: Abrasive grit consisting of aluminium oxide bonded to a polymer substrate. Solvent based acrylic

emulsion adhesive backing. Product supplied with a moisture resistant release liner.

Typical Applications: Suitable for stairs, ladders, ramps, walkways, vehicles and boats.

Surface Finish: Grit Grit size: 46 grit

Thickness:  $1.0+ \pm 0.05$ mm

Resistance to Chemicals: N/A

Environmental Resistance: Suitable for indoor and outdoor environments

UV Resistance: Yes

Installation Method: Pressure sensitive self-adhesive tape

Product Performance: Conforms to slip resistance test EN13552 Category R13

Continued on next page

## Product **Datasheet**



**Adhesion Properties** 

Rolling Ball Tack 20cm

Shear Resistance 24 hrs (1" X 1"@ 1 kg)

Safe Temperature Range -10 °c to +60 °c Adhesive Type Acrylic Adhesive

## **Web Properties**

Property	Grit Carrier Substrate	Release Liner
Web Type	PVC Film	Release Liner
Basic Weight	181 g/m²	120 g/m²
Thickness	0.15 mm	0.185 mm
Tensile Strength	MD: 4.2 kg/15mm	MD: 8.7 kg/25mm
	CD: 3.1 kg/15mm	CD: 5.7 kg/25mm
Color	Black	Brown
Smoothness	Good	Good
Elongation	200±25%	
Die Cutting	Good	Good

Country of Origin: Taiwan