

PRODUCT DATASHEET



Bubblemat

Nitrile and natural rubber options

- Effective anti-fatigue mat available in two options :-
- 1. Bubblemat (100% natural rubber)
- 2. Bubblemat Nitrile (75% natural rubber / 25 % nitrile)
- The addition of nitrile provides excellent resistance to oils and chemicals.
- Both options feature a raised bubbled surface to stimulate blood circulation.
- Available as complete mats or interlocking sections for longer runs.

Product height: 14mm

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
0.9 x 1.2m (edged all round)	10	17.5 x 17.5 x 105	Boxed	1	30	Black	BF010002
0.6 x 0.9 (end piece)	5	17.5 x 17.5 x 75	Boxed	1	42	Black	BF010003
0.6 x 0.9 (middle)	5	17.5 x 17.5 x 75	Boxed	1	42	Black	BF010004
0.6 x 0.9 (edged all round)		17.5 x 17.5 x 75	Boxed	1		Black	BF010001N
0.9 x 1.2m (edged all round)		17.5 x 17.5 x 105	Boxed	1		Black	BF010002N
0.6 x 0.9 (end piece)		17.5 x 17.5 x 75	Boxed	1		Black	BF010003N
0.6 x 0.9 (middle)		17.5 x 17.5 x 75	Boxed	1		Black	BF010004N

Material: Bubblemat (100% natural rubber).

Bubblemat Nitrile (75% Natural Rubber, 25% Nitrile Rubber)

Surface Finish:

Product Height:

Operating Temperature:

Bubble shaped

18mm nominal

-30° to +50°

Resistance to Chemicals: Resistant to water and most mild acids Environmental Resistance: Use predominantly in dry areas.

UV Resistance: N/A

Typical Applications: Ideal for manufacturing production areas where employees are standing in static positions.

Bubble surface constantly stimulates blood circulation to reduce fatigue.

Installation Method: Individual components that lock together to cover any desired length or individual mats complete

with bevel edge all round

Cleaning method: Hose down or pressure wash using a mild detergent.

Product Performance: Fatigue:

Slip Resistance: $\bullet \bullet \bullet \bullet$ Wear: $\bullet \bullet \bullet$ Low ‡ High $\bullet \bullet \bullet$ N/A $\bullet \to \bullet \bullet \bullet \bullet$

Country of Origin: Sri Lanka

Other: Silicone is used in the production process of the mats and a residue will possibly be left on the product.

End of document

United Kingdom

Flame Retardancy:

COBA Europe Ltd Marlborough Drive Fleckney, Leicestershire LE8 8UR

+44 (0)116 240 1088

sales@cobaeurope.com

www.cobaeurope.com

Germany

COBA Europe GmbH Pullenweg 1 - 3 41352 Korschenbroich

+49 (2161) 2945-0

verkauf@cobaeurope.de
 verkauf@c

Slovakia

COBA Europe s.r.o. Terchová - Vyšné Kamence 11 SK-013 06

/* +421 41 507 11 12

image: sales@cobaeurope.sk
/* www.cobaeurope.sk

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.