



Safety Deckplate

Durable Deckplate provides comfort and grip

- Hardwearing PVC soil resistant diamond pattern surface.
- Self-extinguishing top surface provides resilience to many industrial chemicals.
- Comfortable foam 'cushion' backing for fatigue relief.
- Available as **Safety Deckplate** with bright yellow borders.
- Supplied with ramped edges.

Product height: 14mm

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
0.6 x 0.9	4	750 x 175 x 175	Boxed	1	42	Black/ Yellow	SD010701
0.9 x 1.5	8	1050 x 175 x 175	Boxed	1	30	Black/ Yellow	SD010702
0.9 x 3	16	25 x 25 x 94	Boxed	1	25	Black/ Yellow	SD010703
0.9 x 6	32	50 x 50 x 100	Boxed	1	6	Black/ Yellow	SD010704
0.9 x per linear metre						Black/ Yellow	SD010707C

Material: Vinyl top surface with p.v.c foam backing fusion bonded (not glued)
 Surface Finish: Diamond pattern.
 Product Height: 14mm nominal

Operating Temperature: 0° to +60° C
 Resistance to Chemicals: PVC is resistant to many different chemicals, alkalis and general industrial chemicals. Please contact the sales office for more specific details.

Environmental Resistance: Dry indoor environments.
 UV Resistance: N/A

Typical Applications: Packing stations, assembly areas, production lines where regular turning occurs.

Installation Method: Loose lay.
 Cleaning Method: Mop the top surface

Product Performance:

Continued on next page

United Kingdom

COBA Europe Ltd
 Marlborough Drive
 Fleckney, Leicestershire
 LE8 8UR

+44 (0)116 240 1088
 sales@cobaeeurope.com
 www.cobaeeurope.com

Germany

COBA Europe GmbH
 Pullenweg 1 - 3
 41352 Korschenbroich

+49 (2161) 2945-0
 verkauf@cobaeeurope.de
 www.cobaeeurope.de

Slovakia

COBA Europe s.r.o.
 Terchová - Vyšné Kamence 11
 SK-013 06

+421 41 507 11 12
 sales@cobaeeurope.sk
 www.cobaeeurope.sk

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.

Fatigue: ●●●●●
Slip Resistance: ●●●●●
Wear: ●●●●●
Low † High ● → ●●●●●

Flame Retardancy: Will not burn after the ignition source is removed. When 'forced' to burn, Carbon Monoxide, Carbon Dioxide and Hydrogen Chloride fumes are emitted. Meets or exceeds Consumer Products Safety Commission FF1-70

Country of Origin: China

End of document

United Kingdom

COBA Europe Ltd
Marlborough Drive
Fleckney, Leicestershire
LE8 8UR

☎ +44 (0)116 240 1088
✉ sales@cobaurope.com
🌐 www.cobaurope.com

Germany

COBA Europe GmbH
Pullenweg 1 - 3
41352 Korschenbroich

☎ +49 (2161) 2945-0
✉ verkauf@cobaurope.de
🌐 www.cobaurope.de

Slovakia

COBA Europe s.r.o.
Terchová - Vyšné Kamenec 11
SK-013 06

☎ +421 41 507 11 12
✉ sales@cobaurope.sk
🌐 www.cobaurope.sk

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.