

PRODUCT DATASHEET



COBArib

Anti-slip fluted rubber matting

- Durable, manufactured from hardwearing natural rubber.
- Fine ribbed surface has effective slip-resistance.
- Provides insulation from cold concrete floors.
- Has some noise insulation properties.
- Can also be used on workbenches.
- Available in a chunky **COBArib Wide** option.

Product height: 3mm or 6mm

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
0.9 x 10 (3mm)	30	20 x 20 x 90	Roll	1	20	Black	RR010010
0.9 x per linear metre (3mm)	3	2 x 2 x 90	Roll	1	N/A	Black	RR010010C
1.2 x 10 (3mm)	40	20 x 20 x 120	Roll	1	20	Black	RR010020
1.2 x per linear metre (3mm)	4	2 x 2 x 120	Roll	1	N/A	Black	RR010020C
0.9 x 10 (6mm)	73	28 x 28 x 90	Roll	1	9	Black	RR010030
0.9 x per linear metre (6mm)	6	28 x 28 x 90	Roll	1	N/A	Black	RR010030C
1.2 x 10 (6mm)	8	28 x 28 x 120	Roll	1	9	Black	RR010040
1.2 x per linear metre (6mm)	8	28 x 28 x 120	Roll	1	N/A	Black	RR010040C

Material:	Natural rubber
Surface Finish:	Fine fluted ribbed surface
Product Height:	3 mm and 6 mm nominal
Operating Temperature:	-20° to 80° C
Resistance to Chemicals:	Resistant to water and most mild acids
Environmental Resistance:	Use in wet or dry areas.
UV Resistance:	Yes
Typical Applications:	Industrial uses around benches, workstations and walkways. Also suitable for use as a covering for bench work surfaces.
Installation Method:	Loose lay
Cleaning method:	Hose down or pressure wash using a mild detergent.

United Kingdom

COBA Europe Ltd Marlborough Drive Fleckney, Leicestershire LE8 8UR

ℓ +44 (0)116 240 1088
⊠ sales@cobaeurope.com
𝔅¹ www.cobaeurope.com

Germany COBA Europe GmbH Pullenweg 1 - 3 41352 Korschenbroich

ℓ +49 (2161) 2945-0
i verkauf@cobaeurope.de
o¹ www.cobaeurope.de

Slovakia COBA Europe s.r.o. Terchová - Vyšné Kamence 11 SK-013 06

+ +421 41 507 11 12

⊠ sales@cobaeurope.sk

♂ www.cobaeurope.sk

Continued on next page

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.





Product Performance:	Fatigue: Slip Resistance: Wear: Low ‡ High	$\begin{array}{c}\bullet\\\bullet\bullet\bullet\\\bullet\bullet\bullet\\\bullet\bullet\bullet\\\bullet\bullet\bullet\\\bullet\bullet\bullet\bullet\\\bullet\bullet\bullet\\\bullet\bullet\bullet\\\bullet\bullet\bullet\\\bullet\bullet\bullet$
Flame Retardancy:	N/A	
Country of Origin:	China	

Chemical Data

Major components: Styrene-Butadiene Rubber (SBR) Carbon black Minor components:Zinc Oxide ,Sulfur, Accelerators / Activators (< 1 %),Antioxidant / Stabilizers (< 1 %)

United Kingdom

COBA Europe Ltd Marlborough Drive Fleckney, Leicestershire LE8 8UR

ℓ +44 (0)116 240 1088 ⊠ sales@cobaeurope.com 𝔅¹ www.cobaeurope.com

Germany

COBA Europe GmbH Pullenweg 1 - 3 41352 Korschenbroich

ℓ +49 (2161) 2945-0
i verkauf@cobaeurope.de
𝔅¹ www.cobaeurope.de

Slovakia

COBA Europe s.r.o. Terchová - Vyšné Kamence 11 SK-013 06

ℓ +421 41 507 11 12
⊠ sales@cobaeurope.sk
𝔅 www.cobaeurope.sk

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.

End of document