1U 19" Rack Mount Light Panel - Dimmable LED - Flexible Gooseneck Arms - Server Cabinet Light - Data Center/IT Network Enclosure Rackmount Lighting Bar w/Power Adapter & 5ft Cable

Product ID: RKPNLLT

This 1U rack-mount light panel installs into any EIA-310 compliant cabinet and enables you to complete tasks inside your server rack that require lighting. The panel mounts into 1U of rack space in any standard 19 in. rack and features two adjustable gooseneck lights, each 17 in. (432 mm) in length. For easy installation, the light panel also includes a 5 ft. (1.5 m) power cord that can easily reach a PDU that's mounted inside of your rack.

Target illumination with adjustable lights

This rack-mount light enables you to direct light exactly where you need it. The lamp features two easy-to-adjust lights that can be positioned independently with flexible gooseneck arms. You can also direct the lights so they'll work together, to intensify the light in a specific location.

The gooseneck design provides virtually limitless movement and easily bends 360 degrees in any direction. The lights tilt, turn and rotate, so you can instantly switch from any position, and back again.

Precise lighting control, with dimming and power switches

For simple operation, the rack-mount light features a dimming dial, which makes it easy for you to adjust the light to the perfect settings. Unlike some rack-mount lighting systems that require you to physically disconnect the power cable in order to turn them off, this LED rack light features a built-in on/off switch.

Save energy with LED lights

The 1U rack light features LED lights which are long lasting and emit very little heat, unlike some systems that use incandescent lighting. With this rack-mount light, you can be confident your equipment won't overheat due to residual heat generated from your lighting.

The RKPNLLT is backed by a 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

![RoHS & REACH DOWNLOAD DECLARATION]

![WEEE]

![CE]

![FC]

![TAA COMPLIANT]

![C-Tick]

Applications

- Install into your server rack to easily see equipment
- Ideal for multimedia cabinets in dark settings

Features

- Direct light exactly where you need it with two easy-to-adjust lights on independent gooseneck arms
- Get perfect illumination with a dimming dial that adjusts the intensity of both lights
- Save energy and be confident that your equipment won't overheat, with LED lights
- Features an on/off switch making it easy to control
- Installs into only 1U of space

Hardware	Warranty	2 Years
	Industry Standards	EIA-310-D
	U Height	1U
Performance	Diffused Light Intensity	21 Lumens
	Direct Light Intensity	42 Lumens
	Maximum Arm Extension	17 in [432 mm]
Power	Center Tip Polarity	Positive
	Input Current	0.25 A
	Input Voltage	100 - 240 AC
	Output Current	0.5 A
	Output Voltage	12V DC
	Power Consumption (In Watts)	6
	Power Source	AC Adapter Included
Physical Characteristics	Product Height	1.7 in [4.4 cm]
	Product Length	19 in [48.3 cm]
	Product Width	1.8 in [45 mm]
	Weight of Product	26.5 oz [750 g]
Packaging Information	Package Height	3.9 in [10 cm]
	Package Length	19.3 in [49 cm]
	Package Width	4.3 in [11 cm]
	Shipping (Package) Weight	1.6 lb [0.7 kg]
What's in the Box	Included in Package	1 - light panel
		4 - M5 cage nuts
		4 - M5 screws
		1 - universal power adapter (NA/JP, UK, EU, ANZ)
	Cable Length	60 in [152.4 cm]

Product appearance and specifications are subject to change without notice.