

# HP JD092B Compatible SFP+ Transceiver Module - 10GBASE-SR

Product ID: JD092BST



The JD092BST is an HP JD092B compatible fiber transceiver module that has been designed, programmed and tested to work with HP® brand switches and routers. It delivers dependable 10 GbE connectivity over fiber cable, for 10GBASE-SR compliant networks, with a maximum distance of up to 300 m (984 ft).

#### **Technical Specifications:**

- Wavelength: 850 nm
- Maximum Data Transfer Rate: 11.1 Gbps
- Type: Multi Mode Fiber
- Connection Type: LC Connector
- Maximum Transfer Distance: 300 m (984 ft)
- MTBF: 1,967,709 hours
- **Power Consumption:** Less than 1.2 Watts
- Digital Diagnostics Monitoring (DDM): Yes

This SFP+ fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

www.startech.com 1 800 265 1844



### StarTech.com SFPs

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.



## **Data Sheet**

# Certifications, Reports and Compatibility









- Replacing defective or damaged SFP+ modules in HP switches and routers
- Expand your network to remote segments

#### Features

- 100% compatibility with HP JD092B guaranteed
- StarTech.com SFP modules are backed by a lifetime warranty
- Meets or exceeds OEM specifications and Multi-Source Agreement (MSA) industry standards
- Low power consumption of less than 1.2 W
- Hot-swappable with fiber-optic modules

www.startech.com 1 800 265 1844



Hard-to-find made easy\*

# **Data Sheet**

	Warranty	Lifetime
Hardware	Compatible Brand	HPE
	Industry Standards	IEEE 802.3ae 10GBASE-SR
	WDM	No
Performance	Compatible Networks	10 Gbps
	DDM	Yes
	Fiber Operating Mode	Full-Duplex
	Max Transfer Distance	300 m (984 ft)
	Maximum Data Transfer Rate	11.1 Gbps
	MTBF	1,967,709 hours
	Туре	Multi Mode
	Wavelength	850nm
Connector(s)	Local Unit Connectors	1 - Fiber Optic LC Duplex Female
Special Notes / Requirements	Note	For use in 10 Gigabit fiber networking equipment and media converters
	System and Cable Requirements	MSA or HP compliant SFP+ port
Power	Power Consumption (In Watts)	< 1.2 W
Environmental	Humidity	30~75% RH
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Physical Characteristics	Color	Silver
	Product Height	0.5 in [1.3 cm]
	Product Length	2.2 in [57 mm]
	Product Width	0.6 in [14 mm]
	Weight of Product	0.6 oz [17 g]
Packaging Information	Package Height	1.3 in [33 mm]
	Package Length	3.7 in [93 mm]
	Package Width	4.6 in [11.8 cm]
	Shipping (Package) Weight	1.6 oz [44 g]
What's in the Box	Included in Package	1 - SFP+ transceiver
	Material	Aluminum

www.startech.com 1 800 265 1844



**Data Sheet** 

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844