

6 ft. (1.8 m) USB-C to Mini DisplayPort Cable - 4K 60Hz - Black

Product ID: CDP2MDPMM6B



This USB-C to Mini DisplayPort cable lets you connect your Thunderbolt 3 or USB Type-C enabled device to a Mini DP monitor with just one cable, for a convenient, clutter-free connection.

Astonishing Picture Quality

Harness the video capabilities that are built into your USB-C connection. The USB Type-C to Mini DisplayPort cable delivers the astonishing quality of Ultra HD to your 4K display, at resolutions up to 3840×2160 . Plus, the adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other work environments.





Clutter-Free Installation

At 6 ft. (1.8 m) in length, this Mini DP cable delivers a compact connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For shorter installations, we also offer a $\underline{1}$ \underline{m} (3.3 ft.) USB C to \underline{m} cable, enabling you to choose the right cable length for your custom installation needs.

Hassle-Free Setup

For easy operation and installation, this USB 3.1 Type-C to Mini DP adapter cable supports plug-and-play installation on both Windows and Mac computers.

CDP2MDPMM6B is backed by a 3-year StarTech.com warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Connect your MacBook or USB-C device to an mDP monitor
- Ideal for home office or hot desk environments
- Deliver enriched presentations on the go
- Experience crisp visuals with support for 4K 60Hz

Features

- Reduce clutter with a USB-C to mDP adapter and cable in one
- Get astonishing picture quality with support for UHD video resolutions up to 4K 60Hz
- Hassle-free connectivity with the reversible USB-C connector
- Make the perfect connection with a Mini DisplayPort cable that works with any USB Type-C enabled device
- Compatible with Thunderbolt 3 and USB 3.1 Type-C ports that support DP Alt Mode



Data Sheet

Hardware Adapter Style AV Input BY Input AV Output AV Output AV Output AV Output BY Output AV Output AV Output AV Output BY Output AV Ou		Warranty	3 Years
AV Output Mini DisplayPort - 1.2 Chipset ID STMicroelectronics - STM32F072CBU6 Ports 1 Performance Audio Specifications DisplayPort - 5.1 Channel Audio Maximum Digital Resolutions 3840x2160 @ 60 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) Wide Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - Mini-DisplayPort (20 pin) Male Output Special Notes / Requirements Humidity 25%-60%RH Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature - 20°C to 60°C (-4°F to 140°F) Physical Characteristics Color Black Product Height 0.4 in [1 cm] Product Length 8.5 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 2 co 258 g] Packaging Information Package Height 0.3 in [8 mm] Information Package Width 0.5 in [12 cm] Packaging (Package) Weight 0.1 ib [0.1 kg]	Hardware	Adapter Style	Cable Adapters
Connector(s) Ports Audio Specifications Parformance Maximum Digital Resolutions Supported Resolutions Connector(s) Connector B Humidity Operating Temperature Storage Temperature Color Characteristics Color Product Height Product Length Product Length Product Length Product Length Packaging Information Package Length Package Width Package Width Package Width Package Width Package Width Package Weight Package Weight Package Weight Package Width Package Weight Package Weight Package Weight Package Weight Picylach Capic Package Package Weight Picylach Capic Package Weight Picylach Capic Package Weight Picylach Capic Package Weight Picylach Capic Package Package Weight Picylach Capic Package Package Package Weight Picylach Package Package Package Package Weight Picylach Package Packa		AV Input	USB-C
Performance Audio Specifications DisplayPort - 5.1 Channel Audio Performance Audio Specifications DisplayPort - 5.1 Channel Audio Maximum Digital Resolutions 3840x2160 @ 60 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) Wide Screen Supported Yes Connector B 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - Mini-DisplayPort (20 pin) Male Output One USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25%-60%RH Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Characteristics Cable Length 6 ft [1.8 m] Product Height 0.4 in [1 cm] Product Length 8.5 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 2 oz [58 g] Packaging Information Package Length 8.7 in [22 cm] Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]		AV Output	Mini DisplayPort - 1.2
Performance Audio Specifications DisplayPort - 5.1 Channel Audio Maximum Digital Resolutions 3840x2160 @ 60 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) Wide Screen Supported Yes Connector S Connector B 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Special Notes / Requirements Note Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25%-60%RH Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature -20°C to 60°C (-4°F to 140°F) Physical Characteristics Color Black Product Height 0.4 in [1 cm] Product Height 0.4 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 2 oz [58 g] Packaging Information Package Length 8.7 in [22 cm] Package Length 8.7 in [22 cm] Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]		Chipset ID	STMicroelectronics - STM32F072CBU6
Maximum Digital Resolutions 3840x2160 @ 60 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) Wide Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - Mini-DisplayPort (20 pin) Male Output Special Notes / Requirements Humidity 25%-60%RH Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 6 ft [1.8 m] Color Black Product Height 0.4 in [1 cm] Product Length 8.5 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 2 20 [58 g] Packaging Information Package Height 0.5 in [12 mm] Package Width 0.5 in [12 mm] Shipping (Package) Weight) 0.1 lb [0.1 kg]		Ports	1
Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) Wide Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - Mini-DisplayPort (20 pin) Male Output Special Notes / Requirements Humidity 25%-60%RH Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature -20°C to 60°C (-4°F to 140°F) Physical Characteristics Color Black Product Height 0.4 in [1 cm] Product Length 8.5 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 0.8 in [8 mm] Packaging Information Package Height 0.5 in [12 mm] Package Width 0.5 in [12 mm] Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]	Performance	Audio Specifications	DisplayPort - 5.1 Channel Audio
Wide Screen Supported Yes		Maximum Digital Resolutions	3840x2160 @ 60 Hz
Connector S Connector A Connector B 1 - Mini-DisplayPort (20 pin) Male Output Special Notes / Requirements Note Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity Operating Temperature Soc to 35°C (41°F to 95°F) Storage Temperature -20°C to 60°C (-4°F to 140°F) Physical Characteristics Color Black Product Height 0.4 in [1 cm] Product Length 8.5 in [21.5 cm] Product Width Weight of Product Veight of Product 2 oz [58 g] Packaging Information Package Height Nackage Height Nackage Width Shipping (Package) Weight O.1 lb [0.1 kg]		Supported Resolutions	(High-definition 1080p) 1920x1200 2560x1440 2560x1600
Special Notes / Note Requirements Humidity Operating Temperature Color Spacial Poduct Height Product Length Product Length Weight of Product Product Width Weight of Product Spackage Height Note Spackage Width Shipping (Package) Weight Spor USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 25%-60%RH Spor C to 60°C (-4°F to 140°F) 6 ft [1.8 m] 6 ft [1.8 m] 6 ft [1.8 m] 6 ft [1.8 m] Fine I color Spor Spor Spor Spor Spor Spor Spor Spor		Wide Screen Supported	Yes
Special Notes / RequirementsNoteYour USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.EnvironmentalHumidity25%-60%RHOperating Temperature5°C to 35°C (41°F to 95°F)Storage Temperature-20°C to 60°C (-4°F to 140°F)Physical CharacteristicsColorBlackProduct Height0.4 in [1 cm]Product Length8.5 in [21.5 cm]Product Width0.8 in [20 mm]Weight of Product2 oz [58 g]Packaging InformationPackage Height0.3 in [8 mm]Package Width0.5 in [12 mm]Package Width0.5 in [12 mm]Shipping (Package) Weight0.1 lb [0.1 kg]	Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
Requirements Alt mode) in order to work with this adapter. Environmental Humidity 25%-60%RH Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature -20°C to 60°C (-4°F to 140°F) Physical Characteristics Color Black Product Height 0.4 in [1 cm] Product Length 8.5 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 2 oz [58 g] Packaging Information Package Height 0.3 in [8 mm] Package Length 8.7 in [22 cm] Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]		Connector B	1 - Mini-DisplayPort (20 pin) Male Output
Operating Temperature Soc to 35°C (41°F to 95°F) Storage Temperature -20°C to 60°C (-4°F to 140°F) Physical Characteristics Color Black Product Height 0.4 in [1 cm] Product Length Product Width 0.8 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 2 oz [58 g] Packaging Information Package Height 8.7 in [22 cm] Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]	_	Note	
Physical Characteristics Color Product Height Product Width Weight of Product Package Height Package Length Package Width Package Width Shipping (Package) Weight Physical Characteristics Color Black Black Product Length Black B	Environmental	Humidity	25%-60%RH
Physical CharacteristicsCable Length6 ft [1.8 m]ColorBlackProduct Height0.4 in [1 cm]Product Length8.5 in [21.5 cm]Product Width0.8 in [20 mm]Weight of Product2 oz [58 g]Packaging InformationPackage Height0.3 in [8 mm]Package Length8.7 in [22 cm]Package Width0.5 in [12 mm]Shipping (Package) Weight0.1 lb [0.1 kg]		Operating Temperature	5°C to 35°C (41°F to 95°F)
Characteristics Color Black Product Height 0.4 in [1 cm] Product Length 8.5 in [21.5 cm] Product Width Weight of Product Veight of Product 2 oz [58 g] Packaging Information Package Length Package Length Package Width O.5 in [22 cm] Package Width O.5 in [12 mm] Shipping (Package) Weight O.1 lb [0.1 kg]		Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Product Height 0.4 in [1 cm] Product Length 8.5 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 2 oz [58 g] Packaging Information Package Height 8.7 in [22 cm] Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]	-	Cable Length	6 ft [1.8 m]
Product Length 8.5 in [21.5 cm] Product Width 0.8 in [20 mm] Weight of Product 2 oz [58 g] Packaging Information Package Length 8.7 in [22 cm] Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]		Color	Black
Product Width Weight of Product 2 oz [58 g] Packaging Information Package Height Package Length Package Width Package Width Shipping (Package) Weight 0.8 in [20 mm] 0.3 in [8 mm] 8.7 in [22 cm] Package Width 0.5 in [12 mm] O.1 lb [0.1 kg]		Product Height	0.4 in [1 cm]
Weight of Product 2 oz [58 g] Packaging Information Package Height Package Length Package Width Package Width Shipping (Package) Weight Date of Product 2 oz [58 g] 0.3 in [8 mm] 8.7 in [22 cm] Package Width 0.5 in [12 mm] Ont b [0.1 kg]		Product Length	8.5 in [21.5 cm]
Packaging Information Package Height Package Length Package Width Package Width Shipping (Package) Weight Package Width O.1 lb [0.1 kg]		Product Width	0.8 in [20 mm]
Package Length 8.7 in [22 cm] Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]		Weight of Product	2 oz [58 g]
Package Width 0.5 in [12 mm] Shipping (Package) Weight 0.1 lb [0.1 kg]		Package Height	0.3 in [8 mm]
Shipping (Package) Weight 0.1 lb [0.1 kg]		Package Length	8.7 in [22 cm]
		Package Width	0.5 in [12 mm]
What's in the Box Included in Package 1 - USB-C to Mini DisplayPort cable		Shipping (Package) Weight	0.1 lb [0.1 kg]
	What's in the Box	Included in Package	1 - USB-C to Mini DisplayPort cable

Product appearance and specifications are subject to change without notice.