

USB-C to HDMI Adapter - White - 4K 60Hz

Product ID: CDP2HD4K60W



This USB-CTM to HDMI® adapter lets you output HDMI video and audio from a USB Type-CTM device, with support for Ultra HD 4K at 60Hz. The adapter works with USB-C devices that pass a DisplayPort video signal, and it's also compatible with ThunderboltTM 3 ports. The USB-C video adapter features a sleek white design that looks great with your USB Type-C enabled MacBook or HP® ENVY 13.

Astonishing Picture Quality

The adapter lets you harness the video capabilities that are built into your USB Type-C connection, to deliver the astonishing quality of UHD to your 4K 60Hz display. This makes it easier for you to multitask, while working on the most resource-demanding applications imaginable. With this adapter, you can achieve an output resolution of up to $3840 \times 2160p$ at 60Hz, which is perfect for performing high-resolution tasks such as viewing and editing 4K video.

The adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other workspace applications.





The Perfect Travel Companion

With its all-white design, this USB-C video adapter is the perfect accessory for your MacBook with USB-C. The adapter is compact and lightweight so it fits easily into your MacBook bag or carrying case, which is great for BYOD (Bring Your Own Device) applications at the office. While the adapter looks great next your Mac and HP ENVY, it also works with any USB-C computer that supports DisplayPort ALT mode, such as your Windows® laptop.

Hassle-Free Connection with USB Type-C

This adapter lets you utilize the versatile USB Type-C port on your portable device. USB Type-C is a reversible connector, so it doesn't matter which way you plug it in. The reversible connector means you will always plug it in correctly on your first try. It saves you the hassle and distraction of repeatedly attempting to connect your laptop to a display or projector, while you're delivering a presentation or speaking to a group.

The CDP2HD4K60W is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Note:

- Your USB-C equipped device must support video to work with this adapter.
- This product may experience display detection issues with certain models of Mac. If you're experiencing
 issues please contact our technical support. For hassle-free compatibility with Mac we recommend
 CDP2HD4K60H.





Certifications, Reports and Compatibility











Applications

- Keep the adapter with you while traveling, to connect to any HDMI monitor, television or projector you come across
- Connect your BYOD MacBook or HP ENVY to an HDMI display at work
- Connect an HDMI display to your USB-C laptop to use as a secondary monitor

Features

- Astonishing picture quality for resource-demanding applications that require 4K resolution up to 60 Hz
- Hassle-free connection with the reversible USB-C connector
- Thunderbolt 3 port compatible
- Maximum portability with a small footprint and lightweight design
- 7.1 audio support



Data Sheet

Warranty	3 Years
AV Input	USB-C
AV Output	HDMI - 2.0
Chipset ID	Parade - PS176 STMicroelectronics - STM32F072CBU6
Ports	1
Audio Specifications	HDMI - 32 Channel Audio
Maximum Cable Distance To Display	23 ft [7 m]
Maximum Digital Resolutions	3840 x 2160 (Ultra HD 4K) @ 60hz
Supported Resolutions	1024x768 1280x720 1920x1080 1920x1200 2560x1440 2560x1600 3840 x 2160 @ 60Hz
Wide Screen Supported	Yes
Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
Connector A Connector B	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Female Output
Connector B	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use
Connector B Note	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP
Connector B Note System and Cable Requirements	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
Connector B Note System and Cable Requirements Cable Length	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm]
Connector B Note System and Cable Requirements Cable Length Color	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm]
Connector B Note System and Cable Requirements Cable Length Color Product Height	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm]
Connector B Note System and Cable Requirements Cable Length Color Product Height Product Length	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm]
Connector B Note System and Cable Requirements Cable Length Color Product Height Product Length Product Width	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm] 1 in [25 mm]
Connector B Note System and Cable Requirements Cable Length Color Product Height Product Length Product Width Weight of Product	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm] 1 in [25 mm] 0.7 oz [21 g]
Connector B Note System and Cable Requirements Cable Length Color Product Height Product Length Product Width Weight of Product Package Height	1 - HDMI (19 pin) Female Output This video adapter is not compatible with cables that use RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm] 1 in [25 mm] 0.7 oz [21 g] 0.5 in [12 mm]
	AV Input AV Output Chipset ID Ports Audio Specifications Maximum Cable Distance To Display Maximum Digital Resolutions Supported Resolutions



Data Sheet

What's in the Box

Included in Package

1 - USB-C to HDMI adapter

Product appearance and specifications are subject to change without notice.