

USB-C to HDMI Adapter - 4K 60Hz

Product ID: CDP2HD4K60



This USB-CTM to HDMI® adapter lets you output HDMI video and audio from a USB Type-CTM device, such as a USB-C equipped MacBook, with support for Ultra HD 4K at 60 Hz. This adapter works with USB-C devices that pass a DisplayPort video signal, and it's also compatible with ThunderboltTM 3 ports.

Astonishing Picture Quality

The adapter lets you harness the video capabilities that are built into your USB Type-C connection, to deliver the astonishing quality of UHD to your 4K 60 Hz display. This makes it easier for you to multitask, while working on the most resource-demanding applications imaginable. With this adapter, you can achieve an output resolution of up to 3840 x 2160p at 60 Hz, which is perfect for performing high-resolution tasks such as viewing 4K video. Plus, the adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other workspace applications.





Ultimate Portability

This USB Type-C video adapter is highly portable, with a small footprint and a lightweight design. The adapter is the perfect accessory for your new slim USB-C device, fitting easily into your laptop bag or carrying case, which is great for BYOD (Bring Your Own Device) applications at the office.

Hassle-Free Connection with USB Type-C

This adapter lets you utilize the versatile USB Type-C port on your portable device. USB Type-C is a reversible connector, so it doesn't matter which way you plug it in. The reversible connector means you will always plug it in correctly on your first try, saving you the hassle and distraction of repeatedly attempting to connect your laptop to a display or projector, while you're delivering a presentation or speaking to a group.

The CDP2HD4K60 is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Note:

- Your USB-C equipped device must support video to work with this adapter.
- This product may experience display detection issues with certain models of Mac. If you're experiencing
 issues please contact our technical support. For hassle-free compatibility with Mac we recommend
 CDP2HD4K60H.



Data Sheet

Certifications, Reports and Compatibility











Applications

- Keep the adapter with you while traveling, to connect to any HDMI monitor, television or projector you come across
- Connect your BYOD MacBook or Chromebook™ to an HDMI display at work
- Connect an HDMI display to your USB-C laptop to use as a secondary monitor

Features

- Run resource-demanding applications on 4K displays at 60 hz
- Maximum portability with a small footprint and lightweight design
- Hassle-free connection with the reversible USB-C connector
- Thunderbolt 3 port compatible
- 7.1 audio support



Data Sheet

Alt mode) in order to work with this adapter. Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]			
AV Output Chipset ID Parade - PS176 STMicroelectronics - STM32F072CBU6 Ports 1 Performance Audio Specifications HDMI - 7.1 Channel Audio Maximum Cable Distance To Display Maximum Digital Resolutions 3840 x 2160 (Ultra HD 4K) @ 60hz Supported Resolutions 1024x768 1286x720 1920x1000 19		Warranty	3 Years
Chipset ID Parade - PS176 STMicroelectronics - STM32F072CBU6 Ports 1 1 1 1 1 1 1 1 1	Hardware	AV Input	USB-C
Performance Performance Audio Specifications Audio Aud		AV Output	HDMI - 2.0
Performance Audio Specifications HDMI - 7.1 Channel Audio Maximum Cable Distance To Display 23 ft [7 m] Maximum Digital Resolutions 3840 x 2160 (Ultra HD 4K) @ 60hz Supported Resolutions 1024x768 1280x720 1920x1080 1920x1200 2560x1400 25		Chipset ID	
Maximum Cable Distance To Display 23 ft [7 m] Maximum Digital Resolutions 3840 x 2160 (Ultra HD 4K) @ 60hz Supported Resolutions 1024x768 1280x720 1920x1080 1920x1200 2560x1440 2560x1600 3840 x 2160 Video Revision HDMI 2.0 Wide Screen Supported Yes Connector B 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements Note This video adapter is not compatible with cables that use RedMere™ technology. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Cloor Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]		Ports	1
Display Maximum Digital Resolutions 3840 x 2160 (Ultra HD 4K) @ 60hz Supported Resolutions 1024x768 1280x720 1920x1080 1920x1200 2560x1440 2560x1400 3840 x 2160 Video Revision HDMI 2.0 Wide Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm]	Performance	Audio Specifications	HDMI - 7.1 Channel Audio
Supported Resolutions 1024x768 1280x720 1920x1080 1920x1200 2560x1440 2560x1440 2560x1600 3840 x 2160 Video Revision HDMI 2.0 Wide Screen Supported Yes Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]			23 ft [7 m]
1280x720 1920x1080 1920x1200 2560x1440 2560x1640 3840 x 2160 Video Revision MDMI 2.0 Wide Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature Black Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]		Maximum Digital Resolutions	3840 x 2160 (Ultra HD 4K) @ 60hz
Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Special Notes / Requirements Note This video adapter is not compatible with cables that use RedMere™ technology. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Accent Color Black Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]		Supported Resolutions	1280x720 1920x1080 1920x1200 2560x1440 2560x1600
Connector(s) Connector A Connector B 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Female Output Note Requirements Special Notes / Requirements System and Cable Requirements System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity Operating Temperature S°C to 35°C (41°F to 95°F) Storage Temperature S°C to 35°C (41°F to 95°F) Storage Temperature S°C to 35°C (41°F to 95°F) Slack Characteristics Cable Length Color Black Product Height O.4 in [1.1 cm] Product Length Froduct Width 1 in [25 mm]		Video Revision	HDMI 2.0
Special Notes / RequirementsNoteThis video adapter is not compatible with cables that use RedMere™ technology.System and Cable RequirementsYour USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.EnvironmentalHumidity25% to 85% RH Non-CondensingOperating Temperature5°C to 35°C (41°F to 95°F)Storage Temperature5°C to 35°C (41°F to 95°F)Physical CharacteristicsCable Length3.7 in [9.3 cm]ColorBlackProduct Height0.4 in [1.1 cm]Product Length5.9 in [15 cm]Product Width1 in [25 mm]		Wide Screen Supported	Yes
Special Notes / Requirements Note This video adapter is not compatible with cables that use RedMere™ technology. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]	Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
RedMere™ technology. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]		Connector B	1 - HDMI (19 pin) Female Output
Environmental Humidity 25% to 85% RH Non-Condensing Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]	-	Note	
Operating Temperature 5°C to 35°C (41°F to 95°F) Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]		System and Cable Requirements	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
Storage Temperature 5°C to 35°C (41°F to 95°F) Physical Characteristics Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]	Environmental	Humidity	25% to 85% RH Non-Condensing
Physical CharacteristicsAccent ColorBlackCable Length3.7 in [9.3 cm]ColorBlackProduct Height0.4 in [1.1 cm]Product Length5.9 in [15 cm]Product Width1 in [25 mm]		Operating Temperature	5°C to 35°C (41°F to 95°F)
Cable Length 3.7 in [9.3 cm] Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]		Storage Temperature	5°C to 35°C (41°F to 95°F)
Color Black Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]	-	Accent Color	Black
Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]		Cable Length	3.7 in [9.3 cm]
Product Length 5.9 in [15 cm] Product Width 1 in [25 mm]		Color	Black
Product Width 1 in [25 mm]		Product Height	0.4 in [1.1 cm]
		Product Length	5.9 in [15 cm]
Weight of Product 0.8 oz [23 a]		Product Width	1 in [25 mm]
		Weight of Product	0.8 oz [23 g]



Data Sheet

Packaging Information	Package Height	0.2 in [6 mm]
	Package Length	8.7 in [22 cm]
	Package Width	7.9 in [20 cm]
	Shipping (Package) Weight	1.1 oz [32 g]
What's in the Box	Included in Package	1 - USB-C to HDMI adapter

Product appearance and specifications are subject to change without notice.