

## WX29 DLP® Projector

Designed for smaller meeting rooms or classrooms, the Optoma WX29 widescreen projector delivers digital high performance projected images with all the benefits of DLP® technology.

Ideally suited for use with modern widescreen laptops, Mac™ devices, DVD and Blu-Ray™ players, or HD sources such as digital satellite TV boxes; the WX29 delivers superb widescreen video performance with detailed graphics that also handle 4:3 PowerPoint presentations with ease.

Use the simple HDMI input to deliver a bright, clear projected image with audio. If there is ambient light in the room the WX29 delivers an impressive 2600L of brightness where it matters to ensure everyone can clearly see the projected image, even during the day.

Ceiling mounted or on the move this dual-purpose projector multi-tasks in both office, school and home environments. The useful built-in 2W speaker is more than enough for a small meeting and for a bigger audience, connect to an external audio system using the dedicated audio output.

The WX29 is designed with the environment in mind. With energy saving features including <1W standby mode and long lamp-life of 4000hrs, it saves you both time and money. Combine that with our unique 5 year Optoma colour and imager guarantee and you're sure of hassle-free, long lasting projection.

The WX29 comes with a comprehensive selection of accessories including a remote control, 1.8 metre power cord, VGA cable, carry bag, user manual, quick start card and 2 x AAA batteries so you have everything you need to get started.



# High Definition Widescreen

- Widescreen presentations and HD entertainment
- 2600 ANSI Lumens
- Native WXGA resolution
- 3000:1 Contrast Ratio – Sharp, crystal clear images
- Energy saving <1W standby mode
- BrilliantColor™ technology - bright, vibrant projected images
- Digital and Analogue connectivity includes: HDMI, VGA (RGB/YpPr/SCART), S-video, Composite, Audio In/Out, VGA Out & RS232
- Fully functional remote with direct source selection
- Express Power up & Shutdown
- Soft carry bag for easy transportation
- Lightweight and Portable
- 3D-XL Ready, for 3D movies, games and sport
- Kensington Lock & Password Security – extra security for your projector



## SPECIFICATIONS

Native Resolution	WXGA 1280 x 800
Compressed Resolution	up to UXGA (1600 x 1200)
Brightness	2600 ANSI Lumens
Contrast	3000:1
Noise Level	28dB ECO Mode
Lamp Life**	4000/3000 (ECO/BRIGHT mode)
Projection Lens	F/2.5 ~ 2.67, f=21.86 ~ 24.0mm, 1.1x Manual Zoom
Throw Ratio	1.55 - 1.7:1 (Projection Distance:Image Width)
Projection Distance	1.2 - 12m
Image Size	0.83 - 9.13m (32.77" - 359.44") Diagonal 16:10
Display Technology	Single 0.65" WXGA DC3 DMD chip DLP® Technology by Texas Instruments
Weight / Dimensions (W x D x H)	2.3 kg / 286 x 192 x 84mm
Remote Control	Full function remote with direct source selecting
INPUTS	HDMI (HDCP) - audio supported (DVI-D via adaptor) 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Audio Mini Jack
CONTROL	RS232 3 Pin Mini DIN
OUTPUTS	15 Pin D-Sub VGA (monitor loop-through) 3.5mm Audio Mini Jack
Audio	1 x 2W Speaker
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible
Keystone Correction	± 40° Vertical
On Screen Display	18 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Swedish, Greek, Norwegian, Danish, Hungarian, Czech, Turkish, Farsi & Arabic
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p
Uniformity	85%
Displayable Colours	16.7 Million
Horizontal Scan Rate	15.3 - 91.1kHz
Vertical Scan Rate	24 - 120Hz
Power Supply	100 - 240V, 50 - 60Hz
Power Consumption	233W BRIGHT mode < 1W Standby mode 207W STD mode < 1W Standby mode
Operating Conditions	Operating: 5 - 35°C, 85% Humidity (Max), 3000m Altitude (Max)
Security	One Kensington Lock Port, Password Protection
Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, Carry Bag, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card
RoHS	Compliant
Lamp Warranty	6 months or 1000 hours - whichever comes sooner
Warranty	Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details
Colour Guarantee*	5 Years
Imager Guarantee***	5 Years
3D Support	120Hz frame sequential 3D for resolutions up to 720P. 60Hz field sequential 3D for resolutions up to 480i
3D Viewing	Requires Optoma DLP® Link™ active shutter glasses - sold separately
3D Compatibility	The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. Support for 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 will require the Optoma 3D-XL that is available separately. See website for updates.

## EASY TO USE REMOTE CONTROL

### WX29 Remote Control

- 1 Vertical Keystone Correction
- 2 Volume Control
- 3 Brightness Adjustment
- 4 AV Mute
- 5 Direct Input Source Selection

### WX29 Connections

- 6 VGA In - SCART & Component
- 7 VGA Out
- 8 HDMI (audio supported)
- 9 S-Video
- 10 Composite Video
- 11 RS232 - 3 Pin
- 12 Audio In
- 13 Audio Out
- 14 Security Bar
- 15 Kensington™ Lock



### Exceptional Connectivity/ Multiple Terminals



Easy to use remote with buttons to change the input sources



### WX29 Projection Distance 1.2 - 12m (16:10 Aspect Ratio)

Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Vertical Image Size (m)	Min. Vertical Image Size (m)	Max Diagonal Image Size (m)	Max Diagonal Image Size (inch)	Max. Image Offset (m)
1.20	0.77	0.71	0.48	0.44	0.91	35.94	0.06
2.00	1.29	1.18	0.81	0.74	1.52	59.91	0.10
2.50	1.61	1.47	1.01	0.92	1.90	74.88	0.13
3.00	1.94	1.76	1.21	1.10	2.28	89.86	0.15
4.00	2.58	2.35	1.61	1.47	3.04	119.81	0.20
5.00	3.23	2.94	2.02	1.84	3.80	149.76	0.25
6.00	3.87	3.53	2.42	2.21	4.56	179.72	0.30
7.00	4.52	4.12	2.82	2.57	5.33	209.67	0.35
8.00	5.16	4.71	3.23	2.94	6.09	239.62	0.40
9.00	5.81	5.29	3.63	3.31	6.85	269.58	0.45
10.00	6.45	5.88	4.03	3.68	7.61	299.53	0.50
11.00	7.10	6.47	4.44	4.04	8.37	329.48	0.55
12.00	7.74	7.06	4.84	4.41	9.13	359.44	0.60

For guide purposes only

WX29 is capable of 4:3 and 16:9 aspect ratio projection. When projecting a 4:3/16:9 image the image sizes, screen height and offset information will differ from the above.

### Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

[www.optoma.co.uk](http://www.optoma.co.uk)



\*Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Exclusions: (1) Guarantee is voided if the projector is subject to damage through misuse. (2) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (3) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other faults. (4) Over time worn lamps within all projector types will show a slight colour variance. \*\*Typical lamp life achieved through testing. Will vary according to operational use and environment conditions. \*\*\* Optoma guarantees that in normal use, the DLP® imager will retain image quality for at least 5 years and provide consistent pixel performance. Exclusions: (1) Guarantee is voided if the projector is subject to damage through misuse. (2) Guarantee may be void in industrial or commercial environments where dust or smoke is excessive. Copyright © 2011, Optoma Europe Ltd. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments.