

# Dual-Slot SD Card Reader/Writer - USB 3.0 with USB-C - SD 4.0, UHS II

Product ID: 2SD4FCRU3C



This portable USB 3.0 card reader gives you fast read and write access to two SD™ memory cards simultaneously, including SD (Secure Digital), SDHC™ (Secure Digital High Capacity) and SDXC™ (Secure Digital Extended Capacity) flash memory cards. It's easy to connect to the USB-C™ port on your tablet, smartphone, laptop or desktop computer and it's Thunderbolt™ 3 port compatible. Among its advanced features, this high-performance card reader supports SD 4.0 and UHS II.

### **Ultra-fast performance for workflow efficiency**

The USB 3.0 SD card reader/writer offers fast read and write access to two SD cards simultaneously, with support for the speed of USB 3.0 (also known as USB 3.1 Gen 1), up to 5Gbps. The card reader features SD 4.0 and UHS-II support, allowing high speed file transfers. With bus speed up to 312MB/s, the card reader offers uncompromising read and write speeds.



### **Data Sheet**

The card reader is ideal for creative professionals, including photographers, videographers, and graphic designers, who need ultra-fast access to SD cards to offload raw images or edit video or photos, and quickly back up files. It saves time and increases productivity in your daily workload, letting your transfer files quickly when working with multiple SD cards, out in the field or in the studio. By supporting the faster speeds of UHS-II, the card reader saves you valuable time when offloading videos and high volumes of photos to your computer, and increases efficiency during editing and post-production.

### **Supports a wide range of SD cards**

With the dual card reader, you can transfer data to and from two different cards at the same time, saving you time in the studio or out in the field. The card reader supports all popular SD cards such as SDSC, SDHC and SDXC including UHS cards, and is backwards compatible with older SD card versions. By providing two separate slots and support for a wide range of SD cards, the dual card reader helps you overcome the challenges of working with multiple card readers to offload videos and photos.

The card reader will also support microSD<sup>TM</sup> and miniSD<sup>TM</sup> (with adapter) and MMCmobile<sup>TM</sup>, RS-MMC<sup>TM</sup> and MMCplus<sup>TM</sup> (with adapter).

### **Designed for portability**

With a small form-factor and integrated cable, the dual SD card reader is a highly portable solution for accessing your SD cards on a laptop or desktop computer. The wrap-around USB Type-C cable lets you quickly connect to a computer or pack it up quickly when you're done using it, without carrying an additional cable with you. The external SD card reader is OS independent, with no driver or software installation required.

The card reader/writer connects easily to the USB-C port on your laptop, tablet, smartphone or desktop computer and is USB powered, providing sufficient power for most applications. If you require additional power, you can simply connect the USB cable on your power source to the auxiliary Micro-B power port on the 2SD4FCRU3C.


StarTech.com also offers this same card reader and writer with a USB Type-A connector (<u>2SD4FCRU3</u>) to provide wide compatibility, for those who do not have a USB-C enabled device. The 2SD4FCRU3C is backed by a StarTech.com 2-year warranty and free lifetime technical support.





# Certifications, Reports and Compatibility







### **Applications**

- Gain fast access to multimedia content such as images, videos, and music for high-speed file transfers or to review and edit content ideal for creative professionals
- Access two SD cards simultaneously to review or edit files on multiple
   SD cards out in the field or in the studio

#### **Features**

- Provides read and write access for two SD, SDHC or SDXC memory cards simultaneously
- Fast USB 3.0 performance connects to the USB-C port on laptops, tablets, smartphones and desktop computers
- Supports SD 4.0 and UHS-II (Ultra High Speed) for high speed file transfers, with bus speed up to 312MB/s
- Thunderbolt 3 port compatible
- Compact form-factor and integrated USB-C cable for portability
- Plug-and-play no additional software or drivers required
- USB powered
- Backward compatible with USB 2.0 and older SD card versions



## **Data Sheet**

Warranty 2	Years
Hardware Bus Type Us	SB 3.0
	Genesys Logic - GL3215 Genesys Logic - GL3522
Interface U:	SB 3.0
·	upports SD 4.0 and UHS-II (Ultra High Speed) for high peed file transfers, with bus speed up to 312MB/s
Maximum Data Transfer Rate 5	Gbps
Memory Media Type SI	D/MMC (Secure Digital/Multimedia Card)
SI	DHC (Secure Digital High Capacity)
SI	DXC (Secure Digital eXtended Capacity)
Type and Rate U:	SB 3.0 - 5 Gbit/s
Connector(s) Drive Connectors 2	- SD / MMC Slot Female
Host Connectors 1	- USB Type-C (24 pin) USB 3.0 (5Gbps) Receptacle
Other Interface(s) 1	- USB Micro-B (5 pin) Receptacle
Software OS Compatibility O	S independent; No software or drivers required
	ISB powered. For additional power, connect the USB cable n your power source to the AUX Micro-B power port.
System and Cable Requirements Av	vailable USB port
Power Output Current 20	000 mA
	000 mA DC
Output Voltage 5	
Output Voltage 5 Plug Type U:	DC
Output Voltage 5 Plug Type U: Power Source No	DC ISB Micro-B
Output Voltage 5 Plug Type Us Power Source No Environmental Humidity 55	DC ISB Micro-B lot Included (not required for standard applications)
Output Voltage 5 Plug Type Us Power Source No Environmental Humidity 55 Operating Temperature 05	DC ISB Micro-B lot Included (not required for standard applications) % ~ 90%
Output Voltage 5 Plug Type Us Power Source No Environmental Humidity 59 Operating Temperature 09 Storage Temperature -2	DC ISB Micro-B Iot Included (not required for standard applications) % ~ 90% °C to 40°C (32°F to 104°F)
Output Voltage 5 Plug Type Use Power Source Note Power Source Storage Temperature Cable Length 5 Characteristics S  Plug Type Use Power Source Note Power Source Storage Temperature Storage Temperature 5 Cable Length 5  Characteristics S	DC ISB Micro-B Iot Included (not required for standard applications)  % ~ 90%  °C to 40°C (32°F to 104°F)  20°C to 70°C (-4°F to 158°F)
Output Voltage 5 Plug Type Use Power Source Note Power Source Note Power Source Note Power Source Storage Temperature Cable Length 5 Characteristics Color Bill	DC  ISB Micro-B  Iot Included (not required for standard applications)  % ~ 90%  °C to 40°C (32°F to 104°F)  20°C to 70°C (-4°F to 158°F)  in [127 mm]
Output Voltage 5 Plug Type Use Power Source Note Power Note	DC  ISB Micro-B  lot Included (not required for standard applications)  % ~ 90%  °C to 40°C (32°F to 104°F)  20°C to 70°C (-4°F to 158°F)  in [127 mm]
Output Voltage 5 Plug Type Use Power Source Note Power Note P	DC  ISB Micro-B  lot Included (not required for standard applications)  % ~ 90%  °C to 40°C (32°F to 104°F)  20°C to 70°C (-4°F to 158°F)  in [127 mm]  llack  lastic



## **Data Sheet**

	Weight of Product	2 oz [56 g]
Packaging Information	Package Height	1.3 in [34 mm]
	Package Length	5.7 in [14.4 cm]
	Package Width	6.9 in [17.4 cm]
	Shipping (Package) Weight	5 oz [141 g]
What's in the Box Included in Package  External Ports	Included in Package	1 - dual-slot SD card reader
		1 - quick-start guide
	External Ports	2 - SD / MMC Slot Female

Product appearance and specifications are subject to change without notice.