

HP LaserJet Pro P1600 Printer series

Ideal for up to 5 users in small and medium offices where a shared, fast laser printer helps reduce environmental impact with automatic two-sided printing and energy-conserving features.





Handle the printing demands of a busy small office with this fast HP LaserJet printer.

- Connect and share this compact printer within a small office, using built-in 10/100 Ethernet networking
- Print documents fast at up to 25 ppm A4.
- Get a first page out in as fast as 7 seconds from Powersave (Auto-Off) with Instant-on Technology.
- Choose the media that suits your business purpose as the 250-sheet paper tray and 10-sheet priority input slot handle a wide variety of media types such as card stock, transparencies, labels, envelopes and paper.

Choose a printer that helps you save paper, energy and money.

- Save paper with automatic two-sided printing.
- Get up to 50 percent energy savings over competitive laser products, using Instant-on Technology[1].
- Save even more with HP Auto-On/Auto-Off Technology[2] which senses your printing activity, turning on and off automatically.
- Reduce wasted paper by printing only the content you want, using HP Smart Web Printing[3].

Make a professional impression with cost-effective laser printing.

- Produce professional-quality business prints with bold, crisp text and sharp images.
- Receive improved print quality with HP FastRes 1200 which delivers smaller print files, crisp text, even tones and smooth business graphics.
- Save space and reduce printer noise with an ultra-compact, space-saving printer with a "quiet" mode[4].
- Support for HP PCL 5e enables effective, reliable processing of documents and helps ensure consistent communication across a wide range of devices.

- [1] Energy savings based on HP testing using the ENERGY STAR® programme's Typical Energy Consumption (TEC) method on HP LaserJet products with Instant-on Technology vs. top competitive models as of March 2009. [2] HP Auto-On/Auto-Off capabilities subject to printer settings.
- [3] Requires Microsoft Internet Explorer 6.0 or higher.
- [4] Pages will print at half speed in quiet mode

Technical specifications					Ordering information								
Print technology	Laser				CE749A	HP LaserJet Pro P1606d							
Print speed	A4 black: Up to 25 ppm					Printer; introductory H							
	First page out (black, A4): As fast as 7 sec (from Auto-Off) Exact speed varies depending on the system configuration, software application, driver and document complexity.					LaserJet Black prir							
Processor	400 MHz, Tensilica®					cartridge (average cartridg							
	32 MB Not expandable					yield 1000 standard pages							
Memory						declared yield value i accordance with ISO/IE							
Print resolution	Up to 600 x 600 dpi (1200 effective dpi with HP FastRes 1200)					19752); power cord; pape							
Print quality	600 dpi, HP FastRes 1200					tray cover; CD(s) wit							
Printer languages	Host-based printing, HP PCL 5e					printer software an							
Typefaces/fonts	45 TrueType fonts					documentation; Gettin							
Duty cycle (monthly, A4)	Up to 8000 pages					Started Guide, support flye							
Recommended Monthly Page Volume	250 to 2000					Smart Install Flye							
Print margins		mm, right: 4 mm, bottom: 4 mm											
Media handling	Input	Capacity	Weight	Size		Supplie							
	Tray 1	sheets: 250, envelopes: 15;	60 to 163 g/m ²	A4; A5; B5; postcards;	CE278A	HP LaserJet CE278A Blac							
		sheets: 10 (priority feed slot)		envelopes (C5, DL, B5) 147 x 211 to 216 x 356 mm; priority		Print Cartridg							
				feed slot: A6, 76 x 127 to 216 x		Average cartridge yield							
		356 mm				2100 standard pages							
	Output:	Sheets: Up to 150 sheets. Envelo	opes: Up to 15 envelopes. Tr	ansparencies: Up to 100 sheets; 150-sheet	Declared yield value								
		face-down bin	poor op io to ontolopoor it			accordance with ISO/IEC							
	Duplex printing: Automatic (standard), A4, 60 to 105 g/m ²					19752							
Media types	Paper (laser, plain, photo, rough, vellum), envelopes, labels, cardstock, transparencies, postcards					Media supplie							
Interface and connectivity	Hi-Speed USB 2.0 port, 10/100 Ethernet networking; optional: HP Jetdirect ew2500 802.11b/g Wireless Print Server (J8021A)				CHP110	HP Office Paper-50							
Operating systems compatibility	Windows® 7 (32-bit/64-bit); Windows Vista® (32-bit/64-bit); Microsoft® Windows® XP (32-bit/64-bit), Server 2008					sht/A4/210 x 297 mr							
	(32-bit/64-bit), Server 2003 (32-bit/64-bit); Mac OS X v10.4, v10.5, v10.6; Linux (see http://www.hplip.net for current print				CHP210	HP Printing Paper-50							
	driver); Unix				CHF210	sht/A4/210 x 297 mr							
	Optional: Latest drivers available from the HP support Web site at http://www.hp.com/support				CHP310	HP LaserJet Paper-500							
	w Windows® 7 (32-bit/64-bit); Windows Vista® (32-bit/64-bit); Microsoft® Windows® XP (32-bit/64-bit), Server 2008				CHP310								
	(32-bit/64-bit), Server 2003 (32-bit/64-bit); Mac OS X v10.4, v10.5, v10.6; Linux (see http://www.hplip.net for current print driver); Unix					sht/A4/210 x 297 mr							
					Connectivity								
Minimum system requirements	Windows® 7 (32-bit/64-bit): 1 GB RAM; Windows Vista® (32-bit/64-bit); Microsoft® Windows® XP, Server 2008 (32-bit/64-bit), Server 2003: 512 MB RAM; all systems: 350 MB free hard disk space, CD-ROM drive, USB port, Mac OS X v10.4, v10.5, v10.6; 256 MB RAM; 150 MB available hard disk space; CD-ROM drive; USB port HP Usage tracking, HP Status and Alerts, CD Launch Pad, Control Panel Simulator, Print Driver, Software Installer/uninstaller				J8021A	HP Jetdirect ew2500							
						802.11b/g Wireless Prin							
						Serve							
	4 LED indicator lights (Go, Ready, Attention, Toner Low); 2 buttons (Go, Job cancel)												
Control panel Printer management	HP Status and Alerts; HP Easy Printer Care Software; HP Usage tracking (CD install only)					Service & suppor							
	Requirements: Input voltage 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 7 amp; 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz)				UG086E HP Care Pack, Next Business								
Power Dimensions (w x d x h)	4.0 amp. Consumption: 440 watts (active), 2.2 watts (standby), 1.6 watts (Auto-Off), 0.4 watts (off); Typical Electricity					ange Service, 3 years							
	Consumption (TEC): 0.895 kWh/Week					HP Care Pack, Exchange							
	Out of package: 387 x 284 x 246 mm				,	standard turn around time), 3							
	Packaged: 497 x 330 x 330 mm				years	LID Come Develo Determina							
Weight	Out of package: 7.0 kg Packaged: 9.0 kg					HP Care Pack, Return to							
g					Depot service, 3 years. (UG289E: Only Baltics, Greece, Poland, Turkey,								
Operating environment	Operating temperature: 15 to 32.5° C. Recommended operating temperature: 17.5 to 25° C. Operating humidity: 10 to 80% RH. Recommended operating humidity: 30 to 70% RH. Storage temperature: -20 to 40° C. Storage humidity: 10 to 90% RH. Noise level per ISO 9296: Sound power : LwAd 6.6 B(A)				,	venia, Czech Republic,							
					Slovakia, Hungary. UG086E/UG206E: Rest of Europe).								
							Product certifications	Safety certifications: IEC 60950-1 (International), EN 60950-1 +A11 (EU), GS License (Europe), EN 60825-1+A1+A2 Class 1,21 CFR 1040.10 and 1040.11 except for deviations; pursuant to Laser notice No. 50, Dated June 24, 2007 (Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 2006/95/EC with CE Marking (Europe). Other safety approvals as required by individual countries					
For a complete list of supplies, accessories and services, please refer to http://www.hp.com													
		Warranty	One-vear limited w	varranty. Warranty and support opti	ons vary by product, country	and local legal requirements.							

http://www.hp.com/uk



© Copyright 2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

