



- Low noise level
- Integrated Auto Reverse
 Function for easy removal of paper jams
- Illuminated indicators for stand-by, basket full, door open and paper jam
- Sealed dust-free design with robust wooden cabinet
- Mounted on rollers for flexible use



PROFESSIONAL DATA SHREDDERS

- a Synthesis of Technology, Performance and Design. All intimus® shredders are built from durable, precision engineered, high-performance components, designed for a long life of high volume usage. The product range covers all requirements from day-to-day office use up to High Security Shredding machines in use for destruction of classified material in line with all current legal requirements such as DIN 66399 or NSA 02/01. intimus® shredders carry various features which make them unique in user-friendliness and operating efficiency.



| SPECIFICATION | | | |
|-----------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| Model | 45 SP2 | 45 CP4 | 45 CP5 |
| Cutting size | 3,8 mm | 3,8 x 30 mm | 1,9 x 15 mm |
| Bin volume | 45 I | 45 I | 45 I |
| Suitable for | 2-4 Personen | 2-4 Personen | 2-4 Personen |
| Security Level (DIN 66 399) | P-2 / 0-1 / T-2 ⁺ | P-4 / F-1 / 0-1 / T-2 ⁺ | P-5 / F-2 / 0-1 / T-2 ⁺ |
| Shredding capacity* | 22-24 (sheets) 70 g/m ² | 13-15 (sheets) 70 g/m ² | 10-11 (sheets) 70 g/m ² |
| | 19-21 (sheets) 80 g/m ² | 11-13 (sheets) 80 g/m ² | 9-10 (sheets) 80 g/m ² |
| Cutting speed | 8 mm/s | 8 mm/s | 8 mm/s |
| Throughput** | 388 (sheets/min) 70 g/m ² | 291 (sheets/min) 70 g/m ² | 210 (sheets/min) 70 g/m ² |
| (sheets/min) | 339 (sheets/min) 80 g/m ² | 259 (sheets/min) 80 g/m ² | 178 (sheets/min) 80 g/m² |
| Shreddert auch | 700 - 8 | 7 0 | 7 0 |
| Dimensions (W/D/H) | 45 x 39 x 66 cm | 45 x 39 x 66 cm | 45 x 39 x 66 cm |

^{*}only floppy disks / ID cards

HIGH SECURITY SHREDDER

| SPECIFICATION | | |
|--------------------------|--------------------------------------|--|
| Model | 45 CP7 | |
| Schnittgröße | 0,8 x 4,5 mm | |
| Auffangbehälter Volumen | 45 I | |
| Geeignet für | 2-4 Personen | |
| Sicherheitsstufen | P-7 / F-3 | |
| (DIN 66 399) | , | |
| Schneidleistung* | 5-6 (Blätter) 70 g/m ² | |
| odiniolaloistang | 4-5 (Blätter) 80 g/m ² | |
| Schnittgeschwindigkeit | 15 mm/s | |
| Schnittgeschwindigkeit** | 97 (Blätter/min) 70 g/m ² | |
| (Blatt/min) | 81 (Blätter/min) 80 g/m ² | |
| Abmessungen (B/T/H) | 45 x 39 x 66 cm | |

^{*}NSA approved (NSA / CSS EPL 02/01)

^{*} based on 70 g/m2 A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

^{**} theoretical average performance paper/min

^{*} based on 70 g/m2 A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

^{**} theoretical average performance paper/min